

Capadecor CapaSilber



technical data

Specific use(s)	Water-borne coatings
Density	1,08 g/cm ³
consumption	150 ml/m ²
gloss level	gloss (in accordance with DIN EN 13300)

Components

product code/GISCODE	M-DF02
declaration of ingredients	Emulsion paint, aqueous
preservatives	contained
VOC content in accordance with Directive 2004/42/EC	< 0.1 %
VOC-indhold LEED [less water]	< 1 g/l
water-dilutable in accordance with 2004/42/EC (Decopaint)	< 1 g/l
lead, cadmium, chromium VI * (* not contained in the formulation)	yes
	not contained

environmental labels

building certifications

suitability for DGNB criteria ENV 1.2 (2012) "Risks for the Local Environment"

No.	application site	Product Type	QS 1	QS 2	QS 3	QS 4
2	Liquid coatings on primarily mineral undercoats, such as concrete, masonry, mortar, filler, plaster, wallpaper, fleece or plasterboard. Floor space and thoroughfares such as underground car parks, access roads, etc are not taken into account.	Decorative paints, decorative fillers, dust-binding coatings, floor coverings without special resistance requirements, concrete protection coatings	yes	yes	no	no

Suitability for use in accordance with LEED	category (IEQ4.2 - 2009)	non flat topcoat with colorant added at the point-of-sale
	VOC limit below limit	150 g/l yes
recycling share	not contained	
production location	DAW SE Roßdörfer Straße 50 DE-64372 Ober-Ramstadt	