

# Capacryl EffektLack seidenmatt Silber RA



## technical data

Specific use(s)	Water-borne coatings
Density	1,03 g/cm <sup>3</sup>

## Components

product code/GISCODE	M-LW01
preservatives	contained
VOC content in accordance with Directive 2004/42/EC	< 6 % < 60 g/l
VOC-indhold LEED [less water]	< 70 g/l
water-dilutable in accordance with 2004/42/EC (Decopaint)	yes
lead, cadmium, chromium VI * (* not contained in the formulation)	not contained

## environmental labels

complies with the VOC requirements in accordance with	RAL-UZ 12a
---	------------

**building certifications**

suitability for DGNB criteria ENV 1.2 (2012) "Risks for the Local Environment"

No.	application site	product type	QS 1	QS 2	QS 3	QS 4
		varnishes/glazes	yes	yes	yes	yes
26	components made of aluminium and stainless steel on the façade: cladding	products for surface coating of metal	yes	yes	yes	yes
27	Factory-coated components, e.g. façade elements, doors, radiators, etc. Galvanising is not considered coating under this criterion.	primer and top coating (e.g. paints, varnishes)	yes	yes	yes	yes

Suitability for use in accordance with LEED	category (IEQ4.2 - 2009)	pigmented lacquer
	VOC limit below limit	550 g/l yes
recycling share	not contained	
production location	DAW SE Roßdörfer Straße 50 DE-64372 Ober-Ramstadt	