

Capamix Capacryl PU-Satin

BasisW



technical data

Specific use(s)	Coating material
Density	1,28 g/cm ³
wet-scrub consumption	class 1, complies with abrasion resistance in accordance with DIN 53778
gloss level	120 ml/m ² silky matt (in accordance with DIN EN 53778)

Components

product code/GISCODE	M-LW01
declaration of ingredients	Polyurethane/polyacrylate-based lacquer, aqueous
preservatives	contained
VOC content in accordance with Directive 2004/42/EC	< 9 %
VOC-indhold LEED [less water]	< 120 g/l
water-dilutable in accordance with 2004/42/EC (Decopaint)	< 250 g/l
lead, cadmium, chromium VI *	yes
(* not contained in the formulation)	not contained

environmental labels

complies with the VOC requirements in accordance with	RAL-UZ 12a
---	------------

building certifications

suitability for DGNB criteria ENV 1.2 (2012) "Risks for the Local Environment"

No.	application site	Product Type	QS 1	QS 2	QS 3	QS 4
	liquid coatings on non-mineral undercoats: metals, wood, plastics	varnishes/glazes	yes	yes	yes	yes
26	components made of aluminium and stainless steel on the façade: cladding	products for surface coating of metal	yes	yes	yes	yes
27	Factory-coated components, e.g. façade elements, doors, radiators, etc. Galvanising is not considered coating under this criterion.	primer and top coating (e.g. paints, varnishes)	yes	yes	yes	yes

Suitability for use in accordance with LEED	category (IEQ4.2 - 2009)	pigmented lacquer
	VOC limit	550 g/l
	below limit	yes
recycling share	not contained	
production location	DAW SE Roßdörfer Straße 50 DE-64372 Ober-Ramstadt	