

# Capatect-Klebe-und Armierungsmasse 131SL



## Technical data

Specific use(s)	Glue and reinforcing compound
Density	1,40 g/cm <sup>3</sup>
Gloss level	Matt (in accordance with DIN EN 13300)

## Components

Product Code/GISCODE	ZP1
Declaration of ingredients	Cement mortar with hydrated lime
preservatives	not contained
VOC content in accordance with Directive 2004/42/EC	< 0.1 %
VOC content LEED [less water]	< 1 g/l
Solvent and plasticiser-free in accordance with VdL- RL 01	< 1 g/l
Water-dilutable in accordance with 2004/42/EC (Decopaint)	yes
Lead, cadmium, chromium VI *	yes
(* not contained in the formulation)	not contained

## Environmental labels

## Building certifications

Suitability for DGNB criteria ENV 1.2 (2012) "Risks for the Local Environment"

No.	Application site	Product type	QS 1	QS 2	QS 3	QS 4
3	Liquid coating materials for outdoor mineral surfaces. E.g. concrete, masonry, mineral mortar and filler, plaster, ETICS	Decorative paints	yes	yes	yes	yes

Suitability for use in accordance with LEED	Category (IEQ4.2 - 2009)	flat topcoat
	VOC limit	50 g/l
	Limit fulfilled	yes
Recycling share	not contained	
Production site	DAW SE Roßdörfer Straße 50 DE-64372 Ober-Ramstadt	

**Sustainability Data Sheet Update: 06.12.2017**

This data sheet has been compiled based on state-of-the-art technology and our experience. However, in light of the wide range of requirements regarding buildings certifications, the buyer/user remains personally responsible for checking that our assessment is suitable for the intended certification system and its respective requirements. This data sheet is only valid in its latest version and in combination with the current Technical Information and the Material Safety Data Sheet. Please refer to our website to check the up-to-dateness of this version, if necessary.