

Caparol AmphiSilan

Fassadenputz FEIN



Technical data

Specific use(s)	Plaster
Density	1,80 g/cm ³
Consumption	1,5 kg/m ²
Gloss level	Matt (in accordance with DIN EN 13300)

Components

Product Code/GISCODE	M-DF02
Declaration of ingredients	Silicone resin plaster, aqueous , with film protection
preservatives	contained
VOC content in accordance with	< 2 %
Directive 2004/42/EC	< 20 g/l
VOC content LEED [less water]	< 30 g/l
Water-dilutable in accordance with	yes
2004/42/EC (Decopaint)	
Film protection	contained (agent corresponds to 98/8 EC)
Lead, cadmium, chromium VI *	not contained
(* not contained in the formulation)	

Environmental labels

Building certifications

Suitability for DGNB criteria ENV 1.2 (2012) "Risks for the Local Environment"

No.	Application site	Product type	QS 1	QS 2	QS 3	QS 4
3	Liquid coating materials for outdoor mineral surfaces. E.g. concrete, masonry, mineral mortar and filler, plaster, ETICS	Decorative paints	yes	yes	yes	yes
25	Biocide treatment for products needed for material protection (wood) and the façade	Wood protection products, exterior plaster, façade coatings, adhesives, coatings	yes	yes	yes	yes

Suitability for use in accordance with LEED	Category (IEQ4.2 - 2009)	cannot be classified
	VOC limit	
	Limit fulfilled	
Recycling share	not contained	
Production site	DAW SE Roßdörfer Straße 50 DE-64372 Ober-Ramstadt	