

Capadur GreyWood Basis



Technical data

Specific use(s)	Coating material
Density	1,03 g/cm ³
Consumption	70 - 100 ml/m ²
Gloss level	Silky gloss (in accordance with DIN EN 53778)

Components

Product Code/GISCODE	M-KH01F
Declaration of ingredients	Polyacrylate-based wood varnish, aqueous
VOC content in accordance with Directive 2004/42/EC	< 3 %
VOC content LEED [less water]	< 30 g/l
Water-dilutable in accordance with 2004/42/EC (Decopaint)	90 g/l
Film protection	yes
Lead, cadmium, chromium VI *	contained (agent corresponds to 98/8 EC)
(* not contained in the formulation)	not contained

Environmental labels

Building certifications

Suitability for DGNB criteria ENV 1.2 (2012) "Risks for the Local Environment"

No.	Application site	Product type	QS 1	QS 2	QS 3	QS 4
1	Liquid coatings on non-mineral undercoats: metals, wood, plastics	Varnishes/Glazes	yes	yes	yes	no
25	Biocide treatment for products needed for material protection (wood) and the façade	Wood protection products, exterior plaster, façade coatings, adhesives, coatings	yes	yes	yes	yes

Suitability for use in accordance with LEED	Category (IEQ4.2 - 2009)	varnish
	VOC limit	350 g/l
	Limit fulfilled	yes
Recycling share	not contained	
Production site	DAW SE Roßdörfer Straße 50 DE-64372 Ober-Ramstadt	