

CaparolColor Vollton- und Abtönfarbe Sav					
Version	Revision Date:	SDS Number:	Date of last issue: 02.02.2023		
4.0	20.10.2023	6002138	Date of first issue: 20.10.2023		

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier		
Trade name	:	CaparolColor Vollton- und Abtönfarbe Sav
1.2 Relevant identified uses of t	he s	ubstance or mixture and uses advised against
Use of the Sub- stance/Mixture	:	Water-borne coatings
Recommended restrictions on use	:	within adequate application - none
1.3 Details of the supplier of the	e saf	ety data sheet
Company	:	Caparol Farben Lacke GmbH Roßdörfer Straße 50 64372 Ober-Ramstadt
Telephone	:	+496154710
Telefax	:	+4961547170222
Website E-mail address Responsi-	:	msds@dr-rmi.com

1.4 Emergency telephone

ble/issuing person

Emergency telephone 1	: +49613284463 GBK GmbH
-----------------------	-------------------------

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 12	72/2008)
Skin sensitization, Category 1	H317: May cause an allergic skin reaction.

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008)

by Commission Regulation (EU) 2020/878



DE / EN

Capa	CaparolColor Vollton- und Abtönfarbe Sav			
Version 4.0	Revision Date: 20.10.2023		DS Number: 002138	Date of last issue: 02.02.2023 Date of first issue: 20.10.2023
Hazard pictograms		:	(!)	
Sig	nal Word	:	Warning	
Haz	Hazard Statements		H317 May cause	an allergic skin reaction.
Pre	Precautionary Statements		label at hand.	advice is needed, have product container or of reach of children.
				thing mist or vapors. active gloves.
			Response: P302 + P352 IF	ON SKIN: Wash with plenty of water.
			Disposal: P501 Dispose of disposal plant.	contents/ container to an approved waste

Hazardous ingredients which must be listed on the label:

1,2-benzisothiazol-3(2H)-one 2-methylisothiazol-3(2H)-one reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature



CaparolColor Vollton- und Abtönfarbe Sav

Version	Revision Date:	SDS Number:	Date of last issue: 02.02.2023
4.0	20.10.2023	6002138	Date of first issue: 20.10.2023

Components

Components Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
1,2-benzisothiazol-3(2H)-one	2634-33-5 220-120-9 613-088-00-6 01-2120761540-60	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 2; H411 Acute Tox. 2; H330 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1 specific concentration limit Skin Sens. 1; H317 >= 0,05 %	>= 0,0025 - < 0,025
2-methylisothiazol-3(2H)-one	2682-20-4 220-239-6 613-326-00-9 01-2120764690-50	Acute Tox. 2; H330 Acute Tox. 3; H311 Acute Tox. 3; H301 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071 M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 1 	>= 0,0025 - < 0,025

by Commission Regulation (EU) 2020/878



DE / EN

CaparolColor Vollton- und Abtönfarbe Sav

sion	Revision Date: 20.10.2023	SDS Number: 6002138	Date of last issue: 02.02.2023 Date of first issue: 20.10.2023
			>= 0,0015 %
methy	on mass of 5-chloro-2- /l-2H-isothiazol-3-one a /l-2H-isothiazol-3-one (Acute Tox. 2; H330 Acute Tox. 2; H310 Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071 M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100 specific concentration limit Skin Corr. 1C; H314 >= 0,6 % Skin Irrit. 2; H315 0,06 - < 0,6 % Eye Irrit. 2; H319 0,06 - < 0,6 % Skin Sens. 1A; H317 >= 0,0015 % Eye Dam. 1; H318
Subst	ances with a workplace	exposure limit :	>= 0,6 %
	n sulfate	7727-43-7 231-784-4 01-21194	
kaolin)	1332-58-7 310-194-1	
	uth vanadium tetraoxide	237-898-0 01-21194	36965-17
mang	anese ferrite black spir	el 68186-94 269-056-3 01-21194	

For explanation of abbreviations see section 16.



CaparolColor Vollton- und Abtönfarbe Sav					
Version	Revision Date:	SDS Number:	Date of last issue: 02.02.2023		
4.0	20.10.2023	6002138	Date of first issue: 20.10.2023		

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice	 Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). Move out of dangerous area. First aider needs to protect himself.
If inhaled	: Move to fresh air.
In case of skin contact	: Do NOT use solvents or thinners. In case of contact, immediately flush skin with soap and plenty of water.
In case of eye contact	 If eye irritation persists: Get medical advice/ attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If swallowed	: Seek medical advice. Clean mouth with water and drink afterwards plenty of water. If swallowed, DO NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Risks

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment
- : No information available.

: May cause an allergic skin reaction.

SECTION 5: Firefighting measures

5.1 Extinguishing media					
	Suitable extinguishing media	:	Use water spray, alcohol-resistant foam, dry chemical or car- bon dioxide. Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment. Do not use a solid water stream as it may scatter and spread fire.		
	Unsuitable extinguishing media	:	None known.		



Cap	CaparolColor Vollton- und Abtönfarbe Sav				
Vers	on Revision Date:	S	DS Number:	Date of last issue: 02.02.2023	
4.0	20.10.2023	60	02138	Date of first issue: 20.10.2023	
5.2 S	5.2 Special hazards arising from the substance or mixture				
Specific hazards during fire : In case of fire hazardous decomposition products may be produced such as: Carbon monoxide, carbon dioxide and unburned hydroca bons (smoke).				S:	
5.3 A	dvice for firefighters				
	Special protective equipment for fire-fighters	:	Wear self-contain essary.	ed breathing apparatus for firefighting if nec-	
	Further information	:	Standard procedu The product itself	ure for chemical fires. does not burn.	

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	:	Use protective shoes or boots with rough rubber sole. Material can create slippery conditions. Do not get in eyes, on skin, or on clothing.
6.2 Environmental precautions		
Environmental precautions	:	Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities. Do not flush into surface water or sanitary sewer system.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Keep in suitable, closed containers for disposal. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

6.4 Reference to other sections

For further information see Section 7 of the safety data sheet. , For personal protection see section 8., For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	For personal protection see section 8. No special technical protective measures required.
	In addition, the current technical information for this product and its application on www.caparol.com must be observed.



Capar	olColor Vollton-	uno	d Abtönfarbe	Sav
Version 4.0	Revision Date: 20.10.2023		OS Number: 02138	Date of last issue: 02.02.2023 Date of first issue: 20.10.2023
Hyg	ene measures	:	drink or smoke wh	re eating, drinking, or smoking. Do not eat, nen using this product. Remove contaminat- rotective equipment before entering eating
7.2 Conc	litions for safe storage,	incl	luding any incom	patibilities
	uirements for storage s and containers	:	in heat or direct s original container	en. To maintain product quality, do not store unlight. Store at room temperature in the . Containers which are opened must be care- kept upright to prevent leakage.
Adv	ce on common storage	:	Keep away from o materials.	oxidizing agents and strongly acid or alkaline
Stor	age class (TRGS 510)	:	12	
-	ific end use(s) cific use(s)	:	This information is	s not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis			
barium sulfate	7727-43-7	AGW (Inhalable	10 mg/m3	DE TRGS			
Danum Sullate	1121-43-1		TO HIg/HIS				
		fraction)		900			
	Peak-limit cat	egory: 2;(II)					
	Further inform	nation: When there is	compliance with the OEL a	nd biological			
			of harming the unborn child	0			
		AGW (Alveolate	1,25 mg/m3	DE TRGS			
		fraction)		900			
	Peak-limit category: 2;(II)						
	Further information: When there is compliance with the OEL ar						
	tolerance values, there is no risk of harming the unborn child						
		BM (Alveolar	0,5 mg/m3	DE TRGS			
		dust fraction)		527			
kaolin	1332-58-7	TWA (Respirable	0,1 mg/m3	2004/37/EC			
		dust)	-, 3				
	Further information: Carcinogens or mutagens						
bismuth vanadium	14059-33-7	AGW (Alveolate	0,001 mg/m3	DE TRGS			
tetraoxide		fraction)		900			
	Peak-limit cat	egory: 8;(II)					
manganese ferrite	68186-94-7	AGW (Inhalable	0,2 mg/m3	DE TRGS			



CaparolColor Vollton- und Abtönfarbe SavVersionRevision Date:SDS Number:Date of last issue: 02.02.20234.020.10.20236002138Date of first issue: 20.10.2023

black spinel		fraction)	(Manganese)	900		
	Peak-limit cate	egory: 8;(II)				
	Further inform	ation: For Permang	anates an excursion fa	ctor of 1(II) applies.,		
			e OEL and biological to	lerance values, there		
	is no risk of ha	arming the unborn cl	nild			
		AGW (Alveolate	0,02 mg/m3	DE TRGS		
		fraction)	(Manganese)	900		
	Peak-limit cate	Peak-limit category: 8;(II)				
	Further inform	Further information: For Permanganates an excursion factor of 1(II) applies.,				
		When there is compliance with the OEL and biological tolerance values, there				
	is no risk of ha	arming the unborn cl	nild			
		TWA (inhalable	0,2 mg/m3	2017/164/EU		
		fraction)	(Manganese)			
	Further inform	Further information: Indicative				
		TWA (Respirable	0,05 mg/m3	2017/164/EU		
		fraction)	(Manganese)			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Routes of expo- sure	Potential health ef- fects	Value
barium sulfate	Consumers	Inhalation	Long-term systemic effects	10,00 mg/m3
	Consumers	Ingestion	Long-term systemic effects	13000,00 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	10,00 mg/m3
	Workers	Inhalation	Long-term local ef- fects	10,00 mg/m3
bismuth vanadium tetraoxide	Consumers	Ingestion	Long-term systemic effects	0,33 mg/kg bw/day
	Consumers	Skin contact	Long-term systemic effects	0,33 mg/kg bw/day
	Consumers	Inhalation	Long-term local ef- fects	0,01 mg/m3
	Workers	Inhalation	Long-term local ef- fects	0,02 mg/m3
	Workers	Skin contact	Long-term systemic effects	0,67 mg/kg bw/day
manganese ferrite black spinel	Workers	Inhalation	Long-term systemic effects	10,00 mg/m3
	Workers	Inhalation	Long-term local ef- fects	10,00 mg/m3

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
barium sulfate	Fresh water	115 µg/l
	Fresh water sediment	600,4 mg/kg dry



CaparolColor Vollton- und Abtönfarbe Sav

Version 4.0	Revision Date: 20.10.2023		S Number: 02138	Date of last issue: 02 Date of first issue: 20		
			Soil		weight (d.w.) 207,7 mg/kg dry weight (d.w.)	
			Sewage treatme	ent plant	62,2 mg/l	
bismu	uth vanadium tetraoxide	;	Sewage treatme	ent plant	10000 mg/l	
8.2 Expos	sure controls					
Pers	onal protective equipn	nent				
	ace protection	:	DGUV Regulation	n 112-192 - Use of eye	and face protection	
			Goggles			
M G	l protection aterial love thickness rotective index	:	Nitrile rubber 0,2 mm Class 3			
R	emarks	:	 Before removing gloves clean them with soap and water. Wear suitable gloves tested to EN374. DGUV Regulation 112-195 - Use of protective gloves 			
Skin	and body protection	:	Safety shoes Long sleeved clo	thing		
				tection according to the dangerous substance a		
			Skin should be w	ashed after contact.		
				h contaminated clothir lication: impervious clo		
Resp	iratory protection	:	No personal resp quired.	iratory protective equip	oment normally re-	
			DGUV Regulation	n 112-190 - Use of bre	athing equipment	
				lication: Do not breath on filter for paint sprayi		

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid



Caparo	IColor Vollton-ι	und	l Abtönfarbe	Sav
Version 4.0	Revision Date: 20.10.2023	SD	S Number: 02138	Date of last issue: 02.02.2023 Date of first issue: 20.10.2023
Color		:	tan	
Odor		:	No data available	
Melting	g point/freezing point	:	ca. 0 °C	
Boiling	point/boiling range	:	ca. 100 °C	
Upper flamm	explosion limit / Upper ability limit	:	not determined	
	explosion limit / Lower ability limit	:	not determined	
Flash	point	:	Not applicable	
Autoig	nition temperature	:	not determined	
Decon	nposition temperature	:	Not applicable	
рН		:	8 - 9 Concentration: 10	00 %
Viscos Vis	ity cosity, dynamic	:	No data available	
	lity(ies) iter solubility	:	completely miscil	ble
	on coefficient: n- ol/water	:	Not applicable	
Vapor	pressure	:	ca. 23,4 hPa (20	°C)
Relativ	ve density	:	not determined	



Version	Revision Date:	 und Abtönfarbe SDS Number: 	Date of last issue: 02.02.2023
4.0	20.10.2023	6002138	Date of first issue: 20.10.2023
Dens	ity	: 1,3200 g/cm3	
Relat	ive vapor density	: Not applicable	
	information		
Explo	osives	: Not applicable	
Oxidi	zing properties	: Not applicable	
Flam	mability (liquids)	: The product is r	not flammable.
	N 10: Stability and	reactivity	
1 0.1 Reac No de	-	and applied as directed.	
10.2 Cher	nical stability	and applied as directed.	
10.3 Poss	ibility of hazardous	reactions	
	rdous reactions	: No decomposition	on if stored and applied as directed.
Haza			
	litions to avoid		

10.5 Incompatible materials

 Materials to avoid
 : Incompatible with acids and bases.

 Incompatible with oxidizing agents.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.



CaparolColor Vollton- und Abtönfarbe Sav

Version	Revision Date:	SDS Number:	Date of last issue: 02.02.2023
4.0	20.10.2023	6002138	Date of first issue: 20.10.2023

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

1,2-benzisothiazol-3(2H)-one:

Acute oral toxicity	:	LD50 (Rat): 532 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): 0,4 mg/l Exposure time: 4 h Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg

2-methylisothiazol-3(2H)-one:

Acute oral toxicity	: LD50 (Rat): 120 mg/kg
Acute inhalation toxicity	: LC50 (Rat): 0,145 mg/l Exposure time: 4 h Test atmosphere: dust/mist

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):

Acute oral toxicity	:	LD50 (Rat): 66 mg/kg Method: OECD Test Guideline 401
Acute inhalation toxicity	:	LC50 (Rat): 0,17 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: OECD Test Guideline 403
Acute dermal toxicity	:	LD50 (Rat): > 141 mg/kg Method: OECD Test Guideline 402

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.



CaparolColor Vollton- und Abtönfarbe Sav

Version	Revision Date:	SDS Number:	Date of last issue: 02.02.2023
4.0	20.10.2023	6002138	Date of first issue: 20.10.2023

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

1,2-benzisothiazol-3(2H)-one	:	
Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): 2,2 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia): 3,27 mg/l Exposure time: 48 h



sion	Revision Date: 20.10.2023		OS Number: 02138	Date of last issue: 02.02.2023 Date of first issue: 20.10.2023
			Method: OECD To	est Guideline 202
Toxic plants	ity to algae/aquatic	:	EC50 (Selenastru Exposure time: 72 Method: OECD Te	
M-Fac icity)	ctor (Acute aquatic tox-	:	1	
M-Fac toxicit	ctor (Chronic aquatic y)	:	1	
2-met	thylisothiazol-3(2H)-on	e:		
M-Fao icity)	ctor (Acute aquatic tox-	:	10	
M-Fac toxicit	ctor (Chronic aquatic y)	:	1	
reacti (3:1):	ion mass of 5-chloro-2-	-me	ethyl-2H-isothiazol	-3-one and 2-methyl-2H-isothiazol-3-o
M-Fac icity)	ctor (Acute aquatic tox-	:	100	
M-Factoric to xicit	ctor (Chronic aquatic y)	:	100	
bariu	m sulfate:			
Toxic	ity to fish	:	Remarks: No toxi	city at the limit of solubility.
	ity to daphnia and other ic invertebrates	:	Remarks: No toxi	city at the limit of solubility.
Toxic plants	ity to algae/aquatic	:	Remarks: No toxi	city at the limit of solubility.
Toxici icity)	ity to fish (Chronic tox-	:	Remarks: No toxi	city at the limit of solubility.
	ity to daphnia and other ic invertebrates (Chron-	:	Remarks: No toxi	city at the limit of solubility.

12.2 Persistence and degradability

No data available



CaparolColor Vollton- und Abtönfarbe Sav				
Version	Revision Date:		Number:	Date of last issue: 02.02.2023
4.0	20.10.2023	6002	138	Date of first issue: 20.10.2023
12.3 Bioac	cumulative potential			
<u>Comp</u>				
-	enzisothiazol-3(2H)-or	ne:		
	on coefficient: n- bl/water		og Pow: 0,63 - 0, H: 7	76
2-met	hylisothiazol-3(2H)-oı	ne:		
	on coefficient: n- bl/water		og Pow: -0,486 (2 H: 7	25 °C)
reaction (3:1):	on mass of 5-chloro-2	2-meth	yl-2H-isothiazol	-3-one and 2-methyl-2H-isothiazol-3-one
	on coefficient: n- ol/water		og Pow: <= 0,75 lethod: OECD Te	est Guideline 117
12.4 Mobil No dat	ity in soil ta available			
	ts of PBT and vPvB a	ssessi	ment	
Produ	ict:			
	sment	to Ve	be either persis	ixture contains no components considered tent, bioaccumulative and toxic (PBT), or d very bioaccumulative (vPvB) at levels of
12.6 Endo	crine disrupting prop	erties		
Produ	ict:			
Asses	sment	e R (E	red to have endo EACH Article 57	xture does not contain components consid- ocrine disrupting properties according to (f) or Commission Delegated regulation r Commission Regulation (EU) 2018/605 at higher.
12.7 Other	adverse effects			
Produ Additio matior	onal ecological infor-			hazard cannot be excluded in the event of ndling or disposal.



Caparo	Color Vollton-	und Abtönfark	be Sav
Version	Revision Date:	SDS Number:	Date of last issue: 02.02.2023
4.0	20.10.2023	6002138	Date of first issue: 20.10.2023

SECTION 13: Disposal considerations

13.1 Waste treatment methods

••••			
	Product	:	
			Waste should not be disposed of via wastewater.
	Contaminated packaging	:	Only completely emptied containers should be given for recy- cling.
	Waste Code	:	used product 080112, waste paint and varnish other than those mentioned in 08 01 11*

SECTION 14: Transport information

14.1 UN number or ID number						
ADN	:	Not regulated as a dangerous good				
ADR	:	Not regulated as a dangerous good				
RID	:	Not regulated as a dangerous good				
IMDG	:	Not regulated as a dangerous good				
ΙΑΤΑ	:	Not regulated as a dangerous good				
14.2 UN proper shipping name						
ADN	:	Not regulated as a dangerous good				
ADR	:	Not regulated as a dangerous good				
RID	:	Not regulated as a dangerous good				
IMDG	:	Not regulated as a dangerous good				
ΙΑΤΑ	:	Not regulated as a dangerous good				
14.3 Transport hazard class(es)						
ADN	:	Not regulated as a dangerous good				
ADR	:	Not regulated as a dangerous good				
RID	:	Not regulated as a dangerous good				
IMDG	:	Not regulated as a dangerous good				
ΙΑΤΑ	:	Not regulated as a dangerous good				
14.4 Packing group						
ADN	:	Not regulated as a dangerous good				
		10/00				



CaparolColor Vollton- und Abtönfarbe Sav						
Version	Revision Date:	SDS Number:	Date of last issue: 02.02.2023			
4.0	20.10.2023	6002138	Date of first issue: 20.10.2023			
ADR		: Not regulated	as a dangerous good			
RID		: Not regulated	as a dangerous good			
IMDO	6	: Not regulated	as a dangerous good			
ΙΑΤΑ	(Cargo)	: Not regulated	l as a dangerous good			
ΙΑΤΑ	(Passenger)	: Not regulated	as a dangerous good			
14.5 Environmental hazards						
Not re	egulated as a dangerou	us good				
14.6 Special precautions for user						
Rema	arks	: Not classified lations.	as dangerous in the meaning of transport regu-			
14.7 Maritime transport in bulk according to IMO instruments						

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	:	Conditions of restriction for the fol- lowing entries should be considered: Number on list 75, 3
		If you intend to use this product as tattoo ink, please contact your ven- dor.
REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59).	:	This product is a mixture and does not contain Substances of Very High Concern (SVHC) equal or above 0.1%. Therefore no advised uses have to be defined and no chemical safety assessment has to be gener- ated.
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	:	Not applicable
Regulation (EU) 2019/1021 on persistent organic pollu- tants (recast)	:	Not applicable
REACH - List of substances subject to authorisation (Annex XIV)	:	None



CaparolColor Vollton- und Abtönfarbe Sav

4.0	20.10.2023	6002138	Date of first issue: 20.10.2023	
Version	Revision Date:	SDS Number:	Date of last issue: 02.02.2023	

Seveso III: Directive 2012/18/E pean Parliament and of the Co control of major-accident haza dangerous substances.	ouncil on the	
Water hazard class (Germa- ny)	: WGK 1 slightly water endangering Classification according to AwSV, Annex 1 (5.2)	
Volatile organic compounds	: Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: < 0,01 %	
Volatile organic compounds	: Directive 2004/42/EC < 0.1 % < 1 g/l	

Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

Due to the low water solubility of the bismuth vanadate pigments used, the criteria for classifying the mixture with water contaminating class 3 are not met.

15.2 Chemical Safety Assessment

A Chemical Safety Assessment is not required for this mixture.

SECTION 16: Other information

Full text of H-Statements

H301 :	Toxic if swallowed.
H302 :	Harmful if swallowed.
H310 :	Fatal in contact with skin.
H311 :	Toxic in contact with skin.
H314 :	Causes severe skin burns and eye damage.
H315 :	Causes skin irritation.
H317 :	May cause an allergic skin reaction.
H318 :	Causes serious eye damage.
H330 :	Fatal if inhaled.
H400 :	Very toxic to aquatic life.
H410 :	Very toxic to aquatic life with long lasting effects.
H411 :	Toxic to aquatic life with long lasting effects.



CaparolColor Vollton- und Abtönfarbe Sav								
Versio	n Revision Date:	S	DS Number:	Date of last issue: 02.02.2023				
4.0	20.10.2023	60	02138	Date of first issue: 20.10.2023				
EUH071 :			Corrosive to the respiratory tract.					
Full text of other abbreviations								
A	cute Tox.	:	Acute toxicity					
Aquatic Acute		:	Short-term (acute) aquatic hazard					
Aquatic Chronic		:	Long-term (chronic) aquatic hazard					
E	ye Dam.	:	Serious eye damage					
S	kin Corr.	:	: Skin corrosion					
S	kin Irrit.	:	Skin irritation					
	kin Sens.	:	Skin sensitization					
2004/37/EC		:	Europe. Directive 2004/37/EC on the protection of workers					
			from the risks rela at work	ated to exposure to carcinogens or mutagens				
20	017/164/EU		Europe. Commission Directive 2017/164/EU establishing a fourth list of indicative occupational exposure limit values					
D	E TRGS 527	•	Germany. TRGS 527 - Activities with nanomaterials					
	E TRGS 900	:	Germany. TRGS 900 - Occupational exposure limit values.					
	004/37/EC / TWA	:	Long term exposure limit					
	017/164/EU / TWA	:	Limit Value - eight hours					
	E TRGS 527 / BM		Assessment scal					
D	E TRGS 900 / AGW	:	Time Weighted Average					

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Car-riage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community num-ber; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EMS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Prac-tice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Civil Aviation Organization; IECSC - Inven-tory of Evicting Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inven-tory of Evicting Chemicals Distances in China Marting Dangerous Goode; MOC - International Civil Aviation Organization; IECSC - Invenment of ships cartying Dangerous Chemicals in built, ICo0 - naminating mining contentiation, ICO0 - international over Avalation organization, ICO0 - international Automation organization, ICO0 - international Convention for the Prevention of Pollution from Sphips; no.s. - Not Otherwise Specified; NQ(A)EC - No Observed (Adverse) Effect Concentration; NQ(A)EL - No Observed (Adverse) Effect Loading Rate; NZIOC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Offective Convention of Pollicity Operation and Development; OPPTS - Offective Convention of Pollicity Operation and Development; OPPTS - Offective Convention of Pollicity Operation of Policity Operation of Gree of Charles and Provide Field Loading Acte, N2DC - New Zealand Inventory of Chernicals, OECD - Organization for Economic Co-operation and Development, OFP 13 - Of-fice of Chernical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chernicals and Cherni-cal Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chernicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rait; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substances of Very High Concern; TCSI - Taiwan Chernical Sub-stance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information:

No exposure scenario communication is required for this product according to REACH Regulation No. 1907/2006 EC.

Communication of Uses is not required in accordance with REACH Article 31(1)(a) - registered substances / mixtures do not meet the criteria for classification as hazardous in accordance with Regulations 1272/2008 EC or 1999/45/EC.

Sources of key data used to compile the Material Safety Data Sheet: ECHA WebSite



CaparolColor Vollton- und Abtönfarbe Sav

H317

Version	Revision Date:	SDS Number:	Date of last issue: 02.02.2023
4.0	20.10.2023	6002138	Date of first issue: 20.10.2023

ACGIH (American Conference of Government Industrial Hygienists). 2014 TLVs and BEIs. Threshold Limit Values (TLVs) for chemical substances and physical agents and Biological Exposure Indices (BEIs) with Seventh Edition documentation. 2014 ACGIH, Cincinnati OH NIOSH - Registry of toxic effects of chemical substances ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities SAX'S - Dangerous properties of industrial materials GESTIS - Database on hazardous substances - Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA, Institute for Occupational Safety and Health of the German Social Accident Insurance) Toxnet - Toxicology Data Network

Classification of the mixture:

Classification procedure:

Skin Sens. 1

Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

REACH Information

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our upstream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly.

DE / EN