

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended  
by Commission Regulation (EU) 2020/878



DE / EN

## CaparolColor Vollton- und Abtönfarbe Ing

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 05.09.2023  |
| 5.0     | 20.10.2023     | 6002177     | Date of first issue: 20.10.2023 |

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : CaparolColor Vollton- und Abtönfarbe Ing

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-  
stance/Mixture : Water-borne coatings

Recommended restrictions : within adequate application - none  
on use

#### 1.3 Details of the supplier of the safety data sheet

Company : Caparol Farben Lacke GmbH  
Roßdörfer Straße 50  
64372 Ober-Ramstadt

Telephone : +496154710  
Telefax : +4961547170222

Website :  
E-mail address Responsible/issuing person : msds@dr-rmi.com

#### 1.4 Emergency telephone

Emergency telephone 1 : +49613284463 GBK GmbH

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Skin sensitization, Category 1 H317: May cause an allergic skin reaction.

#### 2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended  
by Commission Regulation (EU) 2020/878



DE / EN

## CaparolColor Vollton- und Abtönfarbe Ing

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 05.09.2023  |
| 5.0     | 20.10.2023     | 6002177     | Date of first issue: 20.10.2023 |

Hazard pictograms :



Signal Word : Warning

Hazard Statements : H317 May cause an allergic skin reaction.

Precautionary Statements : P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.

### Prevention:

P261 Avoid breathing mist or vapors.  
P280 Wear protective gloves.

### Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.

### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

### Hazardous ingredients which must be listed on the label:

1,2-benzisothiazol-3(2H)-one  
2-methylisothiazol-3(2H)-one  
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one  
(3:1)

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature : Emulsion paint, aqueous

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended  
by Commission Regulation (EU) 2020/878



DE / EN

## CaparolColor Vollton- und Abtönfarbe Ing

Version 5.0      Revision Date: 20.10.2023      SDS Number: 6002177      Date of last issue: 05.09.2023  
Date of first issue: 20.10.2023

### Components

| Chemical name   | CAS-No.<br>EC-No.<br>Index-No.<br>Registration number       | Classification   | Concentration<br>(% w/w) |
|---|---|--|--------------------------|
| titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq$ 10 $\mu\text{m}$ ] | 13463-67-7<br>236-675-5<br>022-006-00-2<br>01-2119489379-17 | Carc. 2; H351  | $\geq$ 0,1 - < 1         |
| 1,2-benzisothiazol-3(2H)-one  | 2634-33-5<br>220-120-9<br>613-088-00-6<br>01-2120761540-60  | Acute Tox. 4; H302<br>Skin Irrit. 2; H315<br>Eye Dam. 1; H318<br>Skin Sens. 1; H317<br>Aquatic Acute 1;<br>H400<br>Aquatic Chronic 2;<br>H411<br>Acute Tox. 2; H330<br><br>M-Factor (Acute aquatic toxicity): 1<br>M-Factor (Chronic aquatic toxicity): 1<br><br>specific concentration limit<br>Skin Sens. 1; H317<br>$\geq$ 0,05 % | $\geq$ 0,0025 - < 0,025  |
| 2-methylisothiazol-3(2H)-one  | 2682-20-4<br>220-239-6<br>613-326-00-9<br>01-2120764690-50  | Acute Tox. 2; H330<br>Acute Tox. 3; H311<br>Acute Tox. 3; H301<br>Skin Corr. 1B; H314<br>Eye Dam. 1; H318<br>Skin Sens. 1A; H317<br>Aquatic Acute 1;<br>H400<br>Aquatic Chronic 1;<br>H410<br>EUH071<br><br>M-Factor (Acute aquatic toxicity): 10<br>M-Factor (Chronic aquatic toxicity): 1  | $\geq$ 0,0025 - < 0,025  |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended  
by Commission Regulation (EU) 2020/878



DE / EN

## CaparolColor Vollton- und Abtönfarbe Ing

Version 5.0      Revision Date: 20.10.2023      SDS Number: 6002177      Date of last issue: 05.09.2023  
Date of first issue: 20.10.2023

|   |  |  |                      |
|---|--|--|----------------------|
|   |  | specific concentration limit<br>Skin Sens. 1A; H317<br>>= 0,0015 %   |                      |
| reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) | 55965-84-9<br>613-167-00-5<br>01-2120764691-48 | Acute Tox. 3; H301<br>Acute Tox. 2; H330<br>Acute Tox. 2; H310<br>Skin Corr. 1C; H314<br>Eye Dam. 1; H318<br>Skin Sens. 1A; H317<br>Aquatic Acute 1;<br>H400<br>Aquatic Chronic 1;<br>H410<br>EUH071<br><br>M-Factor (Acute aquatic toxicity): 100<br>M-Factor (Chronic aquatic toxicity): 100<br><br>specific concentration limit<br>Skin Corr. 1C; H314<br>>= 0,6 %<br>Skin Irrit. 2; H315<br>0,06 - < 0,6 %<br>Eye Irrit. 2; H319<br>0,06 - < 0,6 %<br>Skin Sens. 1A; H317<br>>= 0,0015 %<br>Eye Dam. 1; H318<br>>= 0,6 % | >= 0,0002 - < 0,0015 |
| Substances with a workplace exposure limit :  |  |  |                      |
| barium sulfate  | 7727-43-7<br>231-784-4<br>01-2119491274-35     |  | >= 1 - < 10          |
| kaolin  | 1332-58-7<br>310-194-1                         |  | >= 1 - < 10          |
| bismuth vanadium tetraoxide   | 14059-33-7<br>237-898-0<br>01-2119486965-17    |  | >= 1 - < 10          |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended  
by Commission Regulation (EU) 2020/878



DE / EN

## CaparolColor Vollton- und Abtönfarbe Ing

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 05.09.2023  |
| 5.0     | 20.10.2023     | 6002177     | Date of first issue: 20.10.2023 |

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first-aid measures

- General advice : Never give anything by mouth to an unconscious person.  
If you feel unwell, seek medical advice (show the label where possible).  
Move out of dangerous area.  
First aider needs to protect himself.
- If inhaled : Move to fresh air.
- In case of skin contact : Do NOT use solvents or thinners.  
In case of contact, immediately flush skin with soap and plenty of water.
- In case of eye contact : If eye irritation persists: Get medical advice/ attention.  
IF IN EYES: Rinse cautiously with water for several minutes.  
Remove contact lenses, if present and easy to do. Continue rinsing.
- If swallowed : Seek medical advice.  
Clean mouth with water and drink afterwards plenty of water.  
If swallowed, DO NOT induce vomiting.

#### 4.2 Most important symptoms and effects, both acute and delayed

- Risks : May cause an allergic skin reaction.

#### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : No information available.

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

- Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.  
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Do not use a solid water stream as it may scatter and spread fire.
- Unsuitable extinguishing media : None known.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended  
by Commission Regulation (EU) 2020/878



DE / EN

## CaparolColor Vollton- und Abtönfarbe Ing

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 05.09.2023  |
| 5.0     | 20.10.2023     | 6002177     | Date of first issue: 20.10.2023 |

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire fighting : In case of fire hazardous decomposition products may be produced such as:  
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

### 5.3 Advice for firefighters

Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Standard procedure for chemical fires.  
The product itself does not burn.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use protective shoes or boots with rough rubber sole.  
Material can create slippery conditions.  
Do not get in eyes, on skin, or on clothing.

### 6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.  
Do not flush into surface water or sanitary sewer system.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Keep in suitable, closed containers for disposal.  
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

### 6.4 Reference to other sections

For further information see Section 7 of the safety data sheet.

, For personal protection see section 8., For disposal considerations see section 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : For personal protection see section 8.  
No special technical protective measures required.

In addition, the current technical information for this product

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended  
by Commission Regulation (EU) 2020/878



DE / EN

## CaparolColor Vollton- und Abtönfarbe Ing

Version 5.0      Revision Date: 20.10.2023      SDS Number: 6002177      Date of last issue: 05.09.2023  
Date of first issue: 20.10.2023

and its application on [www.caparol.com](http://www.caparol.com) must be observed.

Hygiene measures : Wash hands before eating, drinking, or smoking. Do not eat, drink or smoke when using this product. Remove contaminated clothing and protective equipment before entering eating areas.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Perishable if frozen. To maintain product quality, do not store in heat or direct sunlight. Store at room temperature in the original container. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Advice on common storage : Keep away from oxidizing agents and strongly acid or alkaline materials.

Storage class (TRGS 510) : 12

### 7.3 Specific end use(s)

Specific use(s) : This information is not available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

| Components                  | CAS-No.    | Value type (Form of exposure)  | Control parameters      | Basis       |
|-----------------------------|------------|--|-------------------------|-------------|
| barium sulfate              | 7727-43-7  | AGW (Inhalable fraction)   | 10 mg/m <sup>3</sup>    | DE TRGS 900 |
|                             |            | Peak-limit category: 2;(II)  |                         |             |
|                             |            | Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child |                         |             |
|                             |            | AGW (Alveolate fraction)   | 1,25 mg/m <sup>3</sup>  | DE TRGS 900 |
|                             |            | Peak-limit category: 2;(II)  |                         |             |
|                             |            | Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child |                         |             |
|                             |            | BM (Alveolar dust fraction)  | 0,5 mg/m <sup>3</sup>   | DE TRGS 527 |
| kaolin                      | 1332-58-7  | TWA (Respirable dust)  | 0,1 mg/m <sup>3</sup>   | 2004/37/EC  |
|                             |            | Further information: Carcinogens or mutagens   |                         |             |
| bismuth vanadium tetraoxide | 14059-33-7 | AGW (Alveolate fraction)   | 0,001 mg/m <sup>3</sup> | DE TRGS 900 |
|                             |            | Peak-limit category: 8;(II)  |                         |             |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended  
by Commission Regulation (EU) 2020/878



DE / EN

## CaparolColor Vollton- und Abtönfarbe Ing

Version 5.0      Revision Date: 20.10.2023      SDS Number: 6002177      Date of last issue: 05.09.2023  
Date of first issue: 20.10.2023

|  |            |                             |  |             |
|--|------------|-----------------------------|--|-------------|
| titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$ ]                  | 13463-67-7 | AGW (Inhalable fraction)    | 10 mg/m <sup>3</sup><br>(Titanium dioxide)   | DE TRGS 900 |
| Peak-limit category: 2;(II)  |            |                             |  |             |
| Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child |            |                             |  |             |
|  |            | AGW (Alveolate fraction)    | 1,25 mg/m <sup>3</sup><br>(Titanium dioxide) | DE TRGS 900 |
| Peak-limit category: 2;(II)  |            |                             |  |             |
| Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child |            |                             |  |             |
|  |            | BM (Alveolar dust fraction) | 0,5 mg/m <sup>3</sup>                        | DE TRGS 527 |

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

| Substance name  | End Use   | Routes of exposure | Potential health effects   | Value                   |
|---|-----------|--------------------|----------------------------|-------------------------|
| barium sulfate  | Consumers | Inhalation         | Long-term systemic effects | 10,00 mg/m <sup>3</sup> |
|   | Consumers | Ingestion          | Long-term systemic effects | 13000,00 mg/kg bw/day   |
|   | Workers   | Inhalation         | Long-term systemic effects | 10,00 mg/m <sup>3</sup> |
|   | Workers   | Inhalation         | Long-term local effects    | 10,00 mg/m <sup>3</sup> |
| bismuth vanadium tetraoxide   | Consumers | Ingestion          | Long-term systemic effects | 0,33 mg/kg bw/day       |
|   | Consumers | Skin contact       | Long-term systemic effects | 0,33 mg/kg bw/day       |
|   | Consumers | Inhalation         | Long-term local effects    | 0,01 mg/m <sup>3</sup>  |
|   | Workers   | Inhalation         | Long-term local effects    | 0,02 mg/m <sup>3</sup>  |
|   | Workers   | Skin contact       | Long-term systemic effects | 0,67 mg/kg bw/day       |
| titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$ ] | Consumers | Ingestion          | Long-term systemic effects | 700,00 mg/kg bw/day     |
|   | Workers   | Inhalation         | Long-term local effects    | 10,00 mg/m <sup>3</sup> |

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

| Substance name | Environmental Compartment | Value |
|----------------|---------------------------|-------|
|----------------|---------------------------|-------|



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended  
by Commission Regulation (EU) 2020/878



DE / EN

## CaparolColor Vollton- und Abtönfarbe Ing

Version 5.0      Revision Date: 20.10.2023      SDS Number: 6002177      Date of last issue: 05.09.2023  
Date of first issue: 20.10.2023

|  |                          |                               |
|--|--------------------------|-------------------------------|
| barium sulfate   | Fresh water              | 115 µg/l                      |
|  | Fresh water sediment     | 600,4 mg/kg dry weight (d.w.) |
|  | Soil                     | 207,7 mg/kg dry weight (d.w.) |
|  | Sewage treatment plant   | 62,2 mg/l                     |
| bismuth vanadium tetraoxide  | Sewage treatment plant   | 10000 mg/l                    |
| titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] | Sewage treatment plant   | 100 mg/l                      |
|  | Fresh water              | 0,184 mg/l                    |
|  | Soil                     | 100 mg/kg dry weight (d.w.)   |
|  | Sea water                | 0,0184 mg/l                   |
|  | Fresh water sediment     | 1000 mg/kg dry weight (d.w.)  |
|  | Sea sediment             | 100 mg/kg dry weight (d.w.)   |
|  | Intermittent use/release | 0,193 mg/l                    |

### 8.2 Exposure controls

#### Personal protective equipment

Eye/face protection : DGUV Regulation 112-192 - Use of eye and face protection

Goggles

#### Hand protection

Material : Nitrile rubber  
Glove thickness : 0,2 mm  
Protective index : Class 3

Remarks : Before removing gloves clean them with soap and water.  
Wear suitable gloves tested to EN374.  
DGUV Regulation 112-195 - Use of protective gloves

Skin and body protection : Safety shoes  
Long sleeved clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Skin should be washed after contact.

Remove and wash contaminated clothing before re-use.  
During spray application: impervious clothing

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended  
by Commission Regulation (EU) 2020/878



DE / EN

## CaparolColor Vollton- und Abtönfarbe Ing

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 05.09.2023  |
| 5.0     | 20.10.2023     | 6002177     | Date of first issue: 20.10.2023 |

Respiratory protection : No personal respiratory protective equipment normally required.

DGUV Regulation 112-190 - Use of breathing equipment

During spray application: Do not breathe spray dust. Use A2/P2 combination filter for paint spraying.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

|  |   |                               |
|--|---|-------------------------------|
| Physical state                                   | : | liquid                        |
| Color  | : | yellow                        |
| Odor   | : | No data available             |
| Melting point/freezing point                     | : | ca. 0 °C                      |
| Boiling point/boiling range                      | : | ca. 100 °C                    |
| Upper explosion limit / Upper flammability limit | : | not determined                |
| Lower explosion limit / Lower flammability limit | : | not determined                |
| Flash point                                      | : | Not applicable                |
| Autoignition temperature                         | : | not determined                |
| Decomposition temperature                        | : | Not applicable                |
| pH   | : | 8 - 9<br>Concentration: 100 % |
| Viscosity<br>Viscosity, dynamic                  | : | No data available             |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended  
by Commission Regulation (EU) 2020/878



DE / EN

## CaparolColor Vollton- und Abtönfarbe Ing

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 05.09.2023  |
| 5.0     | 20.10.2023     | 6002177     | Date of first issue: 20.10.2023 |

Solubility(ies)  
Water solubility : completely miscible

Partition coefficient: n-  
octanol/water : Not applicable

Vapor pressure : ca. 23,4 hPa (20 °C)

Relative density : not determined

Density : 1,3100 g/cm<sup>3</sup>

Relative vapor density : Not applicable

### 9.2 Other information

Explosives : Not applicable

Oxidizing properties : Not applicable

Flammability (liquids) : The product is not flammable.

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

### 10.4 Conditions to avoid

Conditions to avoid : Protect from frost, heat and sunlight.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended  
by Commission Regulation (EU) 2020/878



DE / EN

## CaparolColor Vollton- und Abtönfarbe Ing

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 05.09.2023  |
| 5.0     | 20.10.2023     | 6002177     | Date of first issue: 20.10.2023 |

### 10.5 Incompatible materials

Materials to avoid : Incompatible with acids and bases.  
Incompatible with oxidizing agents.

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Not classified based on available information.

#### Components:

##### **1,2-benzisothiazol-3(2H)-one:**

Acute oral toxicity : LD50 (Rat): 532 mg/kg  
Acute inhalation toxicity : LC50 (Rat): 0,4 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg

##### **2-methylisothiazol-3(2H)-one:**

Acute oral toxicity : LD50 (Rat): 120 mg/kg  
Acute inhalation toxicity : LC50 (Rat): 0,145 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

##### **reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):**

Acute oral toxicity : LD50 (Rat): 66 mg/kg  
Method: OECD Test Guideline 401  
Acute inhalation toxicity : LC50 (Rat): 0,17 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
Acute dermal toxicity : LD50 (Rat): > 141 mg/kg  
Method: OECD Test Guideline 402

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended  
by Commission Regulation (EU) 2020/878



DE / EN

## CaparolColor Vollton- und Abtönfarbe Ing

|                |                              |                        |   |
|----------------|------------------------------|------------------------|---|
| Version<br>5.0 | Revision Date:<br>20.10.2023 | SDS Number:<br>6002177 | Date of last issue: 05.09.2023<br>Date of first issue: 20.10.2023 |
|----------------|------------------------------|------------------------|---|

### **Skin corrosion/irritation**

Not classified based on available information.

### **Serious eye damage/eye irritation**

Not classified based on available information.

### **Respiratory or skin sensitization**

#### **Skin sensitization**

May cause an allergic skin reaction.

#### **Respiratory sensitization**

Not classified based on available information.

#### **Germ cell mutagenicity**

Not classified based on available information.

#### **Carcinogenicity**

Not classified based on available information.

#### **Reproductive toxicity**

Not classified based on available information.

#### **STOT-single exposure**

Not classified based on available information.

#### **STOT-repeated exposure**

Not classified based on available information.

#### **Aspiration toxicity**

Not classified based on available information.

## 11.2 Information on other hazards

### **Endocrine disrupting properties**

#### **Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### **Components:**

##### **1,2-benzisothiazol-3(2H)-one:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2,2 mg/l

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended  
by Commission Regulation (EU) 2020/878



DE / EN

## CaparolColor Vollton- und Abtönfarbe Ing

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 05.09.2023  |
| 5.0     | 20.10.2023     | 6002177     | Date of first issue: 20.10.2023 |

Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia): 3,27 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Selenastrum capricornutum (green algae)): 0,11 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

M-Factor (Acute aquatic toxicity) : 1

M-Factor (Chronic aquatic toxicity) : 1

### **2-methylisothiazol-3(2H)-one:**

M-Factor (Acute aquatic toxicity) : 10

M-Factor (Chronic aquatic toxicity) : 1

### **reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):**

M-Factor (Acute aquatic toxicity) : 100

M-Factor (Chronic aquatic toxicity) : 100

### **barium sulfate:**

Toxicity to fish : Remarks: No toxicity at the limit of solubility.

Toxicity to daphnia and other aquatic invertebrates : Remarks: No toxicity at the limit of solubility.

Toxicity to algae/aquatic plants : Remarks: No toxicity at the limit of solubility.

Toxicity to fish (Chronic toxicity) : Remarks: No toxicity at the limit of solubility.

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : Remarks: No toxicity at the limit of solubility.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended  
by Commission Regulation (EU) 2020/878



DE / EN

## CaparolColor Vollton- und Abtönfarbe Ing

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 05.09.2023  |
| 5.0     | 20.10.2023     | 6002177     | Date of first issue: 20.10.2023 |

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

#### Components:

#### **1,2-benzisothiazol-3(2H)-one:**

Partition coefficient: n-  
octanol/water : log Pow: 0,63 - 0,76  
pH: 7

#### **2-methylisothiazol-3(2H)-one:**

Partition coefficient: n-  
octanol/water : log Pow: -0,486 (25 °C)  
pH: 7

#### **reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):**

Partition coefficient: n-  
octanol/water : log Pow: <= 0,75  
Method: OECD Test Guideline 117

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

#### Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended  
by Commission Regulation (EU) 2020/878



DE / EN

## CaparolColor Vollton- und Abtönfarbe Ing

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 05.09.2023  |
| 5.0     | 20.10.2023     | 6002177     | Date of first issue: 20.10.2023 |

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

- Product : .  
Waste should not be disposed of via wastewater.
- Contaminated packaging : Only completely emptied containers should be given for recycling.
- Waste Code : used product  
080112, waste paint and varnish other than those mentioned  
in 08 01 11\*

### SECTION 14: Transport information

#### 14.1 UN number or ID number

- ADN : Not regulated as a dangerous good
- ADR : Not regulated as a dangerous good
- RID : Not regulated as a dangerous good
- IMDG : Not regulated as a dangerous good
- IATA : Not regulated as a dangerous good

#### 14.2 UN proper shipping name

- ADN : Not regulated as a dangerous good
- ADR : Not regulated as a dangerous good
- RID : Not regulated as a dangerous good
- IMDG : Not regulated as a dangerous good
- IATA : Not regulated as a dangerous good

#### 14.3 Transport hazard class(es)

- ADN : Not regulated as a dangerous good
- ADR : Not regulated as a dangerous good
- RID : Not regulated as a dangerous good
- IMDG : Not regulated as a dangerous good
- IATA : Not regulated as a dangerous good

#### 14.4 Packing group



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended  
by Commission Regulation (EU) 2020/878



DE / EN

## CaparolColor Vollton- und Abtönfarbe Ing

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 05.09.2023  |
| 5.0     | 20.10.2023     | 6002177     | Date of first issue: 20.10.2023 |

|                         |   |                                   |
|-------------------------|---|-----------------------------------|
| <b>ADN</b>              | : | Not regulated as a dangerous good |
| <b>ADR</b>              | : | Not regulated as a dangerous good |
| <b>RID</b>              | : | Not regulated as a dangerous good |
| <b>IMDG</b>             | : | Not regulated as a dangerous good |
| <b>IATA (Cargo)</b>     | : | Not regulated as a dangerous good |
| <b>IATA (Passenger)</b> | : | Not regulated as a dangerous good |

### 14.5 Environmental hazards

Not regulated as a dangerous good

### 14.6 Special precautions for user

|         |   |  |
|---------|---|--|
| Remarks | : | Not classified as dangerous in the meaning of transport regulations. |
|---------|---|--|

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

|  |   |  |
|--|---|--|
| REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) | : | Conditions of restriction for the following entries should be considered:<br>Number on list 75, 3<br><br>If you intend to use this product as tattoo ink, please contact your vendor.                          |
| REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59).  | : | This product is a mixture and does not contain Substances of Very High Concern (SVHC) equal or above 0.1%. Therefore no advised uses have to be defined and no chemical safety assessment has to be generated. |
| Regulation (EC) No 1005/2009 on substances that deplete the ozone layer  | : | Not applicable   |
| Regulation (EU) 2019/1021 on persistent organic pollutants (recast)  | : | Not applicable   |
| REACH - List of substances subject to authorisation  | : | None   |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended  
by Commission Regulation (EU) 2020/878



DE / EN

## CaparolColor Vollton- und Abtönfarbe Ing

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 05.09.2023  |
| 5.0     | 20.10.2023     | 6002177     | Date of first issue: 20.10.2023 |

(Annex XIV)

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. Not applicable

Water hazard class (Germany) : **WGK 1 slightly water endangering**  
**Classification according to AwSV, Annex 1 (5.2)**

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: < 0,01 %

Volatile organic compounds : Directive 2004/42/EC  
< 0.1 %  
< 1 g/l

### Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

Due to the low water solubility of the bismuth vanadate pigments used, the criteria for classifying the mixture with water contaminating class 3 are not met.

## 15.2 Chemical Safety Assessment

A Chemical Safety Assessment is not required for this mixture.

## SECTION 16: Other information

### Full text of H-Statements

|      |  |
|------|--|
| H301 | : Toxic if swallowed.                      |
| H302 | : Harmful if swallowed.                    |
| H310 | : Fatal in contact with skin.              |
| H311 | : Toxic in contact with skin.              |
| H314 | : Causes severe skin burns and eye damage. |
| H315 | : Causes skin irritation.                  |
| H317 | : May cause an allergic skin reaction.     |
| H318 | : Causes serious eye damage.               |
| H330 | : Fatal if inhaled.                        |
| H351 | : Suspected of causing cancer if inhaled.  |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended  
by Commission Regulation (EU) 2020/878



DE / EN

## CaparolColor Vollton- und Abtönfarbe Ing

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 05.09.2023  |
| 5.0     | 20.10.2023     | 6002177     | Date of first issue: 20.10.2023 |

H400 : Very toxic to aquatic life.  
H410 : Very toxic to aquatic life with long lasting effects.  
H411 : Toxic to aquatic life with long lasting effects.  
EUH071 : Corrosive to the respiratory tract.

### Full text of other abbreviations

Acute Tox. : Acute toxicity  
Aquatic Acute : Short-term (acute) aquatic hazard  
Aquatic Chronic : Long-term (chronic) aquatic hazard  
Carc. : Carcinogenicity  
Eye Dam. : Serious eye damage  
Skin Corr. : Skin corrosion  
Skin Irrit. : Skin irritation  
Skin Sens. : Skin sensitization  
2004/37/EC : Europe. Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens or mutagens at work  
DE TRGS 527 : Germany. TRGS 527 - Activities with nanomaterials  
DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.  
2004/37/EC / TWA : Long term exposure limit  
DE TRGS 527 / BM : Assessment scale  
DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

#### Other information:

No exposure scenario communication is required for this product according to REACH Regulation No. 1907/2006 EC.

Communication of Uses is not required in accordance with REACH Article 31(1)(a) - registered substances / mixtures do not meet the criteria for classification as hazardous in accordance with Regulations 1272/2008 EC or 1999/45/EC.

### Sources of key data used to compile the Material Safety Data Sheet:

ECHA WebSite

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended  
by Commission Regulation (EU) 2020/878



DE / EN

## CaparolColor Vollton- und Abtönfarbe Ing

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 05.09.2023  |
| 5.0     | 20.10.2023     | 6002177     | Date of first issue: 20.10.2023 |

ACGIH (American Conference of Government Industrial Hygienists). 2014 TLVs and BEIs. Threshold Limit Values (TLVs) for chemical substances and physical agents and Biological Exposure Indices (BEIs) with Seventh Edition documentation. 2014 ACGIH, Cincinnati OH  
NIOSH - Registry of toxic effects of chemical substances  
ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities  
SAX'S - Dangerous properties of industrial materials  
GESTIS - Database on hazardous substances - Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA, Institute for Occupational Safety and Health of the German Social Accident Insurance)  
Toxnet - Toxicology Data Network

### Classification of the mixture:

Skin Sens. 1

H317

### Classification procedure:

Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

## REACH Information

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our upstream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly.

DE / EN