

Caparo	OCOIOR VOIItON	- und Abtönfar	be Nia
Version	Revision Date:	SDS Number:	Date of last issue: 02.02.2023
4.0	20.10.2023	6002206	Date of first issue: 13.08.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1	Product identifier Trade name	:	CaparolColor Vollton- und Abtönfarbe Nia
1.2	Relevant identified uses of the	e s	ubstance or mixture and uses advised against
	Use of the Sub- stance/Mixture	:	Water-borne coatings
	Recommended restrictions on use	:	within adequate application - none
1.3	Details of the supplier of the s	safe	ety data sheet
	Company	:	Caparol Farben Lacke GmbH Roßdörfer Straße 50 64372 Ober-Ramstadt
	Telephone	:	+496154710
	Telefax	:	+4961547170222
	Website E-mail address Responsi- ble/issuing person	:	msds@dr-rmi.com

1.4 Emergency telephone

Emergency telephone 1 :	+49613284463 GBK GmbH
-------------------------	-----------------------

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 12	272/2008)
Skin sensitization, Category 1	H317: May cause an allergic skin reaction.

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008)

by Commission Regulation (EU) 2020/878



DE / EN

Caparo Version 4.0	Revision Date: 20.10.2023	S	Abtönfarbe DS Number: 002206	Date of last issue: 02.02.2023 Date of first issue: 13.08.2019
Haza	rd pictograms	:		
Signa	l Word	:	Warning	
Haza	rd Statements	:	H317 May caus	e an allergic skin reaction.
Preca	autionary Statements	:	label at hand.	advice is needed, have product container or of reach of children.
			Prevention:	
				athing mist or vapors. ective gloves.
			Response: P302 + P352 IF	ON SKIN: Wash with plenty of water.
			Disposal: P501 Dispose o disposal plant.	f contents/ container to an approved waste

Hazardous ingredients which must be listed on the label:

1,2-benzisothiazol-3(2H)-one 2-methylisothiazol-3(2H)-one reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Additional Labeling

EUH211

11 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.



CaparolColor Vollton- und Abtönfarbe Nia

Version	Revision Date:	SDS Number:	Date of last issue: 02.02.2023
4.0	20.10.2023	6002206	Date of first issue: 13.08.2019

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature

: Emulsion paint, aqueous

Components

Classification Carc. 2; H351 Carc. 2; H351 Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 2;	Concentration (% w/w) >= 1 - < 10 >= 0,0025 - < 0,025
Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400	>= 1 - < 10
Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400	>= 0,0025 - <
Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400	>= 0,0025 - <
Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400	>= 0,0025 - <
Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400	· ·
Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400	· ·
Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400	· ·
H411 Acute Tox. 2; H330 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	
specific concentration limit Skin Sens. 1; H317 >= 0,05 %	
Acute Tox. 2; H330 Acute Tox. 3; H311 Acute Tox. 3; H301 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071	>= 0,0025 - < 0,025
	Aquatic Chronic 2; H411 Acute Tox. 2; H330 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1 specific concentration limit Skin Sens. 1; H317 >= 0,05 % Acute Tox. 2; H330 Acute Tox. 3; H311 Acute Tox. 3; H311 Acute Tox. 3; H311 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

rsion	Revision Date: 20.10.2023	SDS Number: 6002206	Date of last issue: 02.02.2023 Date of first issue: 13.08.2019
			M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 1
			specific concentration limit Skin Sens. 1A; H317 >= 0,0015 %
methy	on mass of 5-chloro-2 /I-2H-isothiazol-3-one /I-2H-isothiazol-3-one	and 2-	,
Pyridi salt	ne-2-thiol 1-oxide, so	dium 3811-73-2 223-296-5 613-344-00 01-2119493	

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

		SDS Number: 6002206	Date of last issue: 02.02.2023 Date of first issue: 13.08.2019		
			STOT RE 1; H372 (Nervous system) Aquatic Acute 1; H400 Aquatic Chronic 2; H411 EUH070 M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 1 Acute toxicity: 1 Acute toxicity esti- mate Acute oral toxicity: 500 mg/kg Acute inhalation tox- icity (dust/mist): 0,5 mg/l Acute dermal toxicity:		
0.1.1		Bur Y	790 mg/kg		
	ances with a workplace ended with a morkplace ended and a second se	7727-43-7	>= 1 - <		
		231-784-4 01-2119491274	-35		
kaolin		1332-58-7 310-194-1	>= 1 - <		
mang	anese ferrite black spine	68186-94-7 269-056-3 01-2119457599	>= 1 - <		

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice	:	Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). Move out of dangerous area. First aider needs to protect himself.
If the local		

If inhaled

: Move to fresh air.



Caparo	IColor Vollton-	und Abtönfa	rbe Nia
Version	Revision Date:	SDS Number:	Date of last issue: 02.02.2023
4.0	20.10.2023	6002206	Date of first issue: 13.08.2019
In cas	e of skin contact		solvents or thinners. htact, immediately flush skin with soap and plenty
In cas	e of eye contact	: If eye irritatio IF IN EYES:	n persists: Get medical advice/ attention. Rinse cautiously with water for several minutes. act lenses, if present and easy to do. Continue
If swa	llowed		l advice. with water and drink afterwards plenty of water. DO NOT induce vomiting.
4.2 Most ir	nportant symptoms	and effects, both a	cute and delayed
Risks			n allergic skin reaction.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment

: No information available.

SECTION 5: Firefighting measures

5.1	Extinguishing media		
	Suitable extinguishing media	:	Use water spray, alcohol-resistant foam, dry chemical or car- bon dioxide. Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment. Do not use a solid water stream as it may scatter and spread fire.
	Unsuitable extinguishing media	:	None known.
5.2	Special hazards arising from	the	substance or mixture
	Specific hazards during fire fighting	:	In case of fire hazardous decomposition products may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocar- bons (smoke).
5.3	Advice for firefighters		
	Special protective equipment for fire-fighters	:	Wear self-contained breathing apparatus for firefighting if nec- essary.
	Further information	:	Standard procedure for chemical fires. The product itself does not burn.



CaparolColor Vollton- und Abtönfarbe Nia

Version	Revision Date:	SDS Number:	Date of last issue: 02.02.2023
4.0	20.10.2023	6002206	Date of first issue: 13.08.2019

SECTION 6: Accidental release measures

6.1 Personal precautions, prote	ctive equipment and emergency procedures
Personal precautions	: Use protective shoes or boots with rough rubber sole. Material can create slippery conditions. Do not get in eyes, on skin, or on clothing.
6.2 Environmental precautions	
Environmental precautions	 Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities. Do not flush into surface water or sanitary sewer system.
6.3 Methods and material for co	ntainment and cleaning up
Methods for cleaning up	 Keep in suitable, closed containers for disposal. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

6.4 Reference to other sections

For further information see Section 7 of the safety data sheet. , For personal protection see section 8., For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	:	For personal protection see section 8. No special technical protective measures required.
		In addition, the current technical information for this product and its application on www.caparol.com must be observed.
Hygiene measures	:	Wash hands before eating, drinking, or smoking. Do not eat, drink or smoke when using this product. Remove contaminat- ed clothing and protective equipment before entering eating areas.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers	:	Perishable if frozen. To maintain product quality, do not store in heat or direct sunlight. Store at room temperature in the original container. Containers which are opened must be care- fully resealed and kept upright to prevent leakage.

Advice on common storage : Keep away from oxidizing agents and strongly acid or alkaline



CaparolColor Vollton- und Abtönfarbe Nia

Version	Revision Date:	SDS Number:	Date of last issue: 02.02.2023	
4.0	20.10.2023	6002206	Date of first issue: 13.08.2019	

materials.

Storage class (TRGS 510) : 10

7.3 Specific end use(s)

Specific use(s) : This information is not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis		
barium sulfate	7727-43-7	AGW (Inhalable fraction)	10 mg/m3	DE TRGS 900		
	Peak-limit cat	egory: 2;(II)				
			compliance with the OEL a of harming the unborn child	and biological		
		AGW (Alveolate fraction)	1,25 mg/m3	DE TRGS 900		
	Peak-limit cat					
			compliance with the OEL a of harming the unborn child	and biological		
		BM (Alveolar dust fraction)	0,5 mg/m3	DE TRGS 527		
kaolin	1332-58-7	TWA (Respirable dust)	0,1 mg/m3	2004/37/EC		
	Further information: Carcinogens or mutagens					
manganese ferrite black spinel	68186-94-7	AGW (Inhalable fraction)	0,2 mg/m3 (Manganese)	DE TRGS 900		
·	Peak-limit category: 8;(II)					
Further information: For Permanganates an excursion factor			of 1(II) applies.,			
		compliance with the arming the unborn cl	e OEL and biological tolerar hild	nce values, there		
		AGW (Alveolate fraction)	0,02 mg/m3 (Manganese)	DE TRGS 900		
	Peak-limit category: 8;(II)					
	Further information: For Permanganates an excursion factor When there is compliance with the OEL and biological tolerar is no risk of harming the unborn child					
		TWA (inhalable fraction)	0,2 mg/m3 (Manganese)	2017/164/EU		
	Further inform	nation: Indicative	· · · · · · · · · · · · · · · · · · ·			
		TWA (Respirable fraction)	0,05 mg/m3 (Manganese)	2017/164/EU		



CaparolColor Vollton- und Abtönfarbe Nia

ersion 0	Revision Da 20.10.2023	te: SDS 6002		Date of last issue: 02.02.20 Date of first issue: 13.08.20				
					-			
		Further inform	nation: Indicative					
titaniu	ım dioxide; [in	13463-67-7	AGW (Inhalable	10 mg/m3	DE TRGS			
powd	er form con-		fraction)	(Titanium dioxide)	900			
tainin	g 1 % or		,					
	of particles							
with a	erodynamic							
	eter ≤ 10 µm]							
	·	Peak-limit category: 2;(II)						
		Further information: When there is compliance with the OEL and biological						
		tolerance values, there is no risk of harming the unborn child						
			AGW (Alveolate	1,25 mg/m3	DE TRGS			
			fraction)	(Titanium dioxide)	900			
		Peak-limit cat	egory: 2;(II)					
		Further inform	nation: When there	is compliance with the OE	L and biological			
		tolerance valu	ies, there is no risł	of harming the unborn chi	ld			
			BM (Alveolar	0,5 mg/m3	DE TRGS			
			dust fraction)		527			
Pyridi	ne-2-thiol 1-	3811-73-2	AGW (Inhalable	0,2 mg/m3	DE TRGS			
	, sodium salt		fraction)	5	900			
		Peak-limit cat	egory: 2;(II)	·	·			
				tion, When there is complia	ance with the OE			
				there is no risk of harming				

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

	. ,			
Substance name	End Use	Routes of expo- sure	Potential health ef- fects	Value
barium sulfate	Consumers	Inhalation	Long-term systemic effects	10,00 mg/m3
	Consumers	Ingestion	Long-term systemic effects	13000,00 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	10,00 mg/m3
	Workers	Inhalation	Long-term local ef- fects	10,00 mg/m3
manganese ferrite black spinel	Workers	Inhalation	Long-term systemic effects	10,00 mg/m3
	Workers	Inhalation	Long-term local ef- fects	10,00 mg/m3
titanium dioxide; [in powder form contain- ing 1 % or more of particles with aerody- namic diameter ≤ 10 µm]	Consumers	Ingestion	Long-term systemic effects	700,00 mg/kg bw/day
	Workers	Inhalation	Long-term local ef- fects	10,00 mg/m3

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

 Substance name
 Environmental Compartment
 Value



CaparolColor Vollton- und Abtönfarbe Nia

ersion	Revision Date:	SDS Number: 6002206	Date of last issue:	
.0	0 20.10.2023 6002		Date of first issue:	13.08.2019
bariur	m sulfate	Fresh water		115 μg/l
		Fresh water	sediment	600,4 mg/kg dry weight (d.w.)
		Soil		207,7 mg/kg dry weight (d.w.)
		Sewage trea	tment plant	62,2 mg/l
conta cles v	titanium dioxide; [in powder form containing 1 % or more of parti- cles with aerodynamic diameter ≤ 10 µm]		tment plant	100 mg/l
		Fresh water		0,184 mg/l
				100 mg/kg dry weight (d.w.)
		Sea water		0,0184 mg/l
		Fresh water	sediment	1000 mg/kg dry weight (d.w.)
		Sea sedimer	nt	100 mg/kg dry weight (d.w.)
		Intermittent u	ise/release	0,193 mg/l

8.2 Exposure controls

Personal protective equipment						
Eye/face protection	:	DGUV Regulation 112-192 - Use of eye and face protection				
		Goggles				
Hand protection Material Glove thickness Protective index	:	Nitrile rubber 0,2 mm Class 3				
Remarks	:	Before removing gloves clean them with soap and water. Wear suitable gloves tested to EN374. DGUV Regulation 112-195 - Use of protective gloves				
Skin and body protection	:	Safety shoes Long sleeved clothing				
		Choose body protection according to the amount and con- centration of the dangerous substance at the work place.				
		Skin should be washed after contact.				
		Remove and wash contaminated clothing before re-use. During spray application: impervious clothing				
Respiratory protection	:	No personal respiratory protective equipment normally re-				



CaparolColor Vollton- und Abtönfarbe Nia

4.0 20.10.2023 6002206 Date of first issue: 13.08.2019	Version	Revision Date:	SDS Number:	Date of last issue: 02.02.2023	
	4.0	20.10.2023	6002206	Date of first issue: 13.08.2019	

quired.

DGUV Regulation 112-190 - Use of breathing equipment

During spray application: Do not breathe spray dust. Use A2/P2 combination filter for paint spraying.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	:	liquid
Color	:	blue
Odor	:	No data available
Melting point/freezing point	:	ca. 0 °C
Boiling point/boiling range	:	ca. 100 °C
Upper explosion limit / Upper flammability limit	:	not determined
Lower explosion limit / Lower flammability limit	:	not determined
Flash point	:	> 100 °C
Autoignition temperature	:	not determined
Decomposition temperature	:	Not applicable
рН	:	8 Concentration: 100 %
Viscosity Viscosity, dynamic	:	No data available



ty(ies) er solubility			
,	:	completely miscil	ble
	:	Not applicable	
pressure	:	ca. 23,4 hPa (20	°C)
e density	:	not determined	
,	:	1,3100 g/cm3	
e vapor density	:	Not applicable	
	:	Not applicable	
ng properties	:	Not applicable	
ability (liquids)	:	The product is no	ot flammable.
	n coefficient: n- /water oressure e density e vapor density oformation ves ng properties ability (liquids)	/water //water	/water //water // water // water // water // water // water // ca. 23,4 hPa (20) e density : not determined // : 1,3100 g/cm3 e vapor density : Not applicable formation // // // // // // // // // // // // //

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions	: No decompo	osition if stored and applied as directed.
---------------------	--------------	--

10.4 Conditions to avoid

Conditions to avoid : Protect from frost, heat and sunlight.



CaparolColor Vollton- und Abtönfarbe Nia

Version	Revision Date:	SDS Number:	Date of last issue: 02.02.2023	
4.0	20.10.2023	6002206	Date of first issue: 13.08.2019	

10.5 Incompatible materials

Materials to avoid

: Incompatible with acids and bases. Incompatible with oxidizing agents.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

1,2-benzisothiazol-3(2H)-c	one:
----------------------------	------

Acute oral toxicity	:	LD50 (Rat): 532 mg/kg				
Acute inhalation toxicity	:	LC50 (Rat): 0,4 mg/l Exposure time: 4 h Test atmosphere: dust/mist				
Acute dermal toxicity	:	LD50 (Rat): > 2.000 mg/kg				
2-methylisothiazol-3(2H)-one	:					
Acute oral toxicity	:	LD50 (Rat): 120 mg/kg				
Acute inhalation toxicity	:	LC50 (Rat): 0,145 mg/l Exposure time: 4 h Test atmosphere: dust/mist				
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):						
Acute oral toxicity	:	LD50 (Rat): 66 mg/kg Method: OECD Test Guideline 401				

Acute inhalation toxicity	:	LC50 (Rat): 0,17 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: OECD Test Guideline 403
Acute dermal toxicity	:	LD50 (Rat): > 141 mg/kg Method: OECD Test Guideline 402

Pyridine-2-thiol 1-oxide, sodium salt:



Version 4.0	Revision Date: 20.10.2023		Number:	Date of last issue: 02.02.2023 Date of first issue: 13.08.2019			
Acute	e oral toxicity	M		mate: 500 mg/kg kicity estimate according to Regulation (EC)			
Acute	inhalation toxicity	Te M	cute toxicity estinest atmosphere: ethod: Acute tox o. 1272/2008				
Acute	e dermal toxicity	M		mate: 790 mg/kg kicity estimate according to Regulation (EC)			
-	corrosion/irritation lassified based on ava	ilable info	ormation.				
	us eye damage/eye i lassified based on ava		ormation.				
Resp	iratory or skin sensit	ization					
-	sensitization cause an allergic skin i	eaction.					
•	iratory sensitization lassified based on ava	ilable info	ormation.				
	a cell mutagenicity lassified based on ava	ilable info	ormation.				
	i nogenicity lassified based on ava	ilable info	ormation.				
-	oductive toxicity lassified based on ava	ilable info	ormation.				
	F-single exposure lassified based on ava	ilable info	ormation.				
	STOT-repeated exposure Not classified based on available information.						
-	ration toxicity lassified based on ava	ilable info	ormation.				
1.2 Infor	mation on other haza	irds					
Endo	crine disrupting pro	perties					
<u>Prod</u> Asses	uct: ssment			ixture does not contain components consid- pcrine disrupting properties according to			



CaparolColor Vollton- und Abtönfarbe Nia

	4.0 20.10.2023 6002206 Date of first issue: 13.08.207	Version Revision Date: SDS Number: Date of last issue: 02.02.2023				
--	---	---	--	--	--	--

REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

1,2-benzisothiazol-3(2H)-one:	
Toxicity to fish :	LC50 (Oncorhynchus mykiss (rainbow trout)): 2,2 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other : aquatic invertebrates	EC50 (Daphnia): 3,27 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae/aquatic : plants	EC50 (Selenastrum capricornutum (green algae)): 0,11 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
M-Factor (Acute aquatic tox- : icity)	1
M-Factor (Chronic aquatic : toxicity)	1
2-methylisothiazol-3(2H)-one:	
M-Factor (Acute aquatic tox- : icity)	10
M-Factor (Chronic aquatic : toxicity)	1
reaction mass of 5-chloro-2-m (3:1):	ethyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one
M-Factor (Acute aquatic tox- : icity)	100
M-Factor (Chronic aquatic : toxicity)	100
Pyridine-2-thiol 1-oxide, sodiu	m salt:



Version 4.0	Revision Date: 20.10.2023		0S Number: 02206	Date of last issue: 02.02.2023 Date of first issue: 13.08.2019
icity)				
M-Fac toxicity	tor (Chronic aquatic y)	:	1	
bariu	n sulfate:			
Toxici	ty to fish	:	Remarks: No toxi	city at the limit of solubility.
	ty to daphnia and other c invertebrates	:	Remarks: No toxi	city at the limit of solubility.
Toxici plants	ty to algae/aquatic	:	Remarks: No toxi	city at the limit of solubility.
Toxici icity)	ty to fish (Chronic tox-	:	Remarks: No toxi	city at the limit of solubility.
	ty to daphnia and other c invertebrates (Chron- city)	:	Remarks: No toxi	city at the limit of solubility.
	stence and degradabil ta available	ity		
12.3 Bioac	cumulative potential			
Comp	onents:			
1,2-be	enzisothiazol-3(2H)-on	e:		
	on coefficient: n- bl/water	:	log Pow: 0,63 - 0, pH: 7	,76
2-met	hylisothiazol-3(2H)-on	e:		
	on coefficient: n- bl/water	:	log Pow: -0,486 (pH: 7	25 °C)
reacti (3:1):	on mass of 5-chloro-2	-me	thyl-2H-isothiazo	I-3-one and 2-methyl-2H-isothiazol-3-on
	on coefficient: n- bl/water	:		est Guideline 117
Pvridi	ne-2-thiol 1-oxide, soc	liun	n salt:	



Capar	olColor Vollton-	un	d Abtönfar	be Nia
Version 4.0	Revision Date: 20.10.2023	S	OS Number: 02206	Date of last issue: 02.02.2023 Date of first issue: 13.08.2019
	ility in soil ata available			
	ults of PBT and vPvB	2660	semont	
		a555	55111EIII	
<u>Proc</u> Asse	luct: essment	:	to be either pe	e/mixture contains no components considered rsistent, bioaccumulative and toxic (PBT), or and very bioaccumulative (vPvB) at levels of
12.6 End	ocrine disrupting pro	pertie	S	
Proc	luct:			
Asse	essment	:	ered to have e REACH Article	e/mixture does not contain components consid- ndocrine disrupting properties according to a 57(f) or Commission Delegated regulation 0 or Commission Regulation (EU) 2018/605 at or higher.
12.7 Othe	er adverse effects			
Proc Addi matio	tional ecological infor-	:		ntal hazard cannot be excluded in the event of I handling or disposal.
SECTIO	N 13: Disposal cons	sider	ations	
13.1 Was	te treatment methods	5		
Prod	uct	:		
			Waste should	not be disposed of via wastewater.
Cont	aminated packaging	:	Only complete cling.	ly emptied containers should be given for recy-

Waste Code : used product 080112, waste paint and varnish other than those mentioned in 08 01 11*

SECTION 14: Transport information

14.1 UN number or ID number

ADN

: Not regulated as a dangerous good



Caparo Version	Revision Date:		d Abtönfarbe DS Number:	Date of last issue: 02.02.2023			
4.0	20.10.2023	60	02206	Date of first issue: 13.08.2019			
ADR			Not regulated as	a dangerous good			
RID		:	Not regulated as	a dangerous good			
IMDG	ì	:	Not regulated as	a dangerous good			
ΙΑΤΑ		:	Not regulated as	a dangerous good			
14.2 UN p	roper shipping name						
ADN		:	Not regulated as	a dangerous good			
ADR		:	Not regulated as	a dangerous good			
RID		:	Not regulated as	a dangerous good			
IMDG	;	:	Not regulated as	a dangerous good			
ΙΑΤΑ		:	Not regulated as	a dangerous good			
14.3 Transport hazard class(es)							
ADN		:	Not regulated as	a dangerous good			
ADR		:	Not regulated as	a dangerous good			
RID		:	Not regulated as	a dangerous good			
IMDG	;	:	Not regulated as	a dangerous good			
ΙΑΤΑ		:	Not regulated as	a dangerous good			
14.4 Pack	ing group						
ADN		:	Not regulated as	a dangerous good			
ADR		:	Not regulated as	a dangerous good			
RID		:	Not regulated as	a dangerous good			
IMDG	;	:	Not regulated as	a dangerous good			
ΙΑΤΑ	(Cargo)	:	Not regulated as	a dangerous good			
ΙΑΤΑ	(Passenger)	:	Not regulated as	a dangerous good			
14.5 Envii	ronmental hazards						
Not re	egulated as a dangerou	is go	od				
-	ial precautions for us	er					
Rema	arks	:	Not classified as lations.	dangerous in the meaning of transport regu-			

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.



CaparolColor Vollton- und Abtönfarbe Nia

Version	Revision Date:	SDS Number:	Date of last issue: 02.02.2023
4.0	20.10.2023	6002206	Date of first issue: 13.08.2019

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mix- ture				
REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the fol- lowing entries should be considered Number on list 75, 3	d:			
If you intend to use this product as tattoo ink, please contact your ven- dor.				
REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59).	al			
Regulation (EC) No 1005/2009 on substances that de- : Not applicable plete the ozone layer				
Regulation (EU) 2019/1021 on persistent organic pollu- : Not applicable tants (recast)				
REACH - List of substances subject to authorisation : None (Annex XIV)				
Seveso III: Directive 2012/18/EU of the Euro- pean Parliament and of the Council on the control of major-accident hazards involving dangerous substances.				
Water hazard class (Germa- : WGK 1 slightly water endangering ny) Classification according to AwSV, Annex 1 (5.2)				
Product code for laquers and : M-DF01 Water-based paints, solvent-free paints / Giscode				
. ESW20 Coating materials, water-based				
Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 0,02 %				



CaparolColor Vollton- und Abtönfarbe Nia

Version	Revision Date:	SDS Number:	Date of last issue: 02.02.2023
4.0	20.10.2023	6002206	Date of first issue: 13.08.2019

Volatile organic compounds

: Directive 2004/42/EC < 0.1 % < 1 g/l

Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical Safety Assessment

A Chemical Safety Assessment is not required for this mixture.

SECTION 16: Other information

Full text of H-Statements

H301	:	Toxic if swallowed.
H302	:	Harmful if swallowed.
H310	:	Fatal in contact with skin.
H311	:	Toxic in contact with skin.
H314	:	Causes severe skin burns and eye damage.
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H318	:	Causes serious eye damage.
H319	:	Causes serious eye irritation.
H330	:	Fatal if inhaled.
H331	:	Toxic if inhaled.
H351	:	Suspected of causing cancer if inhaled.
H372	:	Causes damage to organs through prolonged or repeated
H400		exposure.
	:	Very toxic to aquatic life.
H410	:	Very toxic to aquatic life with long lasting effects.
H411	:	Toxic to aquatic life with long lasting effects.
EUH070	:	Toxic by eye contact.
EUH071	:	Corrosive to the respiratory tract.

Full text of other abbreviations

Acute Tox. :	Acute toxicity
Aquatic Acute :	Short-term (acute) aquatic hazard
Aquatic Chronic :	Long-term (chronic) aquatic hazard
Carc. :	Carcinogenicity
Eye Dam. :	Serious eye damage
Eye Irrit.	Eye irritation
Skin Corr. :	Skin corrosion
Skin Irrit.	Skin irritation
Skin Sens. :	Skin sensitization



CaparolColor Vollton- und Abtönfarbe Nia

Version 4.0	Revision Date: 20.10.2023		0S Number: 02206	Date of last issue: 02.02.2023 Date of first issue: 13.08.2019	
STOT 2004/	RE 37/EC	:	Europe. Directive	gan toxicity - repeated exposure 2004/37/EC on the protection of workers ated to exposure to carcinogens or mutagens	
2017/164/EU		:	Europe. Commission Directive 2017/164/EU establishing a fourth list of indicative occupational exposure limit values		
DE TR	RGS 527	:		527 - Activities with nanomaterials	
DE TR	RGS 900	:		900 - Occupational exposure limit values.	
2004/	37/EC / TWA	:	Long term exposi	ure limit	
2017/	164/EU / TWA	:	Limit Value - eigh	t hours	
DE TR	RGS 527 / BM	:	Assessment scale	9	
DE TR	RGS 900 / AGW	:	Time Weighted A	verage	

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with %^k response; ELx - Loading rate associated with x^k response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x^k growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Could Avistem and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECS - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISC1 - International Concentration of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Loading Rate; NZIOC - New Zealand Inventory of Chemicals; OECD - Organization (Co) - Substances; (IOS - Phileines Inventory of Chemicals, OECD - Organization for Economic Co-operation and Development; OPPTS - OI Gic of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Levin Persistent, Bioaccumulative and Toxic substance; TICS - Thaimanet and of the Council concerning the Registratio

Further information

Other information:

No exposure scenario communication is required for this product according to REACH Regulation No. 1907/2006 EC.

Communication of Uses is not required in accordance with REACH Article 31(1)(a) - registered substances / mixtures do not meet the criteria for classification as hazardous in accordance with Regulations 1272/2008 EC or 1999/45/EC.

Sources of key data used to compile the Material Safety Data Sheet:

ECHA WebSite

ACGIH (American Conference of Government Industrial Hygienists). 2014 TLVs and BEIs. Threshold Limit Values (TLVs) for chemical substances and physical agents and Biological Exposure Indices (BEIs) with Seventh Edition documentation. 2014 ACGIH, Cincinnati OH NIOSH - Registry of toxic effects of chemical substances

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX'S - Dangerous properties of industrial materials

GESTIS - Database on hazardous substances - Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA, Institute for Occupational Safety and Health of the German Social Accident Insurance)

Toxnet - Toxicology Data Network



CaparolColor Vollton- und Abtönfarbe Nia

Version	Revision Date:	SDS Number:	Date of last issue: 02.02.2023
4.0	20.10.2023	6002206	Date of first issue: 13.08.2019

Classification procedure:

Skin Sens. 1 H317

Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

REACH Information

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our upstream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly.

DE / EN