

DE / EN

CaparolColor Vollton- und Abtönfarbe Ode				
Version	Revision Date:	SDS Number:	Date of last issue: 02.02.2023	
4.0	20.10.2023	6002209	Date of first issue: 13.08.2019	

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1	Product identifier Trade name	:	CaparolColor Vollton- und Abtönfarbe Ode
1.2	Relevant identified uses of the	e s	ubstance or mixture and uses advised against
	Use of the Sub- stance/Mixture	:	Water-borne coatings
	Recommended restrictions on use	:	within adequate application - none
1.3	Details of the supplier of the s	safe	ety data sheet
	Company	:	Caparol Farben Lacke GmbH Roßdörfer Straße 50 64372 Ober-Ramstadt
	Telephone	:	+496154710
	Telefax	:	+4961547170222
	Website E-mail address Responsi- ble/issuing person	:	msds@dr-rmi.com

1.4 Emergency telephone

Emergency telephone 1 :	+49613284463 GBK GmbH
-------------------------	-----------------------

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)			
Skin sensitization, Category 1	H317: May cause an allergic skin reaction.		

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008)

by Commission Regulation (EU) 2020/878



DE / EN

Caparo Version 4.0	Revision Date: 20.10.2023	S	DS Number: 002209	Date of last issue: 02.02.2023 Date of first issue: 13.08.2019
Hazard pictograms		:		
Signa	l Word	:	Warning	
Haza	rd Statements	:	H317 May cause	e an allergic skin reaction.
Preca	autionary Statements	:	label at hand.	advice is needed, have product container or of reach of children.
			Prevention:	
				thing mist or vapors. ective gloves.
			Response: P302 + P352 IF	ON SKIN: Wash with plenty of water.
			Disposal: P501 Dispose of disposal plant.	f contents/ container to an approved waste

Hazardous ingredients which must be listed on the label:

1,2-benzisothiazol-3(2H)-one 2-methylisothiazol-3(2H)-one reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Additional Labeling

EUH211

11 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.



CaparolColor Vollton- und Abtönfarbe Ode

Version	Revision Date:	SDS Number:	Date of last issue: 02.02.2023
4.0	20.10.2023	6002209	Date of first issue: 13.08.2019

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Color

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
titanium dioxide; [in powder form containing 1 % or more of parti- cles with aerodynamic diameter ≤ 10 µm]	13463-67-7 236-675-5 022-006-00-2 01-2119489379-17	Carc. 2; H351	>= 1 - < 10
1,2-benzisothiazol-3(2H)-one	2634-33-5 220-120-9 613-088-00-6 01-2120761540-60	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 2; H411 Acute Tox. 2; H330 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1 specific concentration limit Skin Sens. 1; H317 >= 0,05 %	>= 0,0025 - < 0,025
2-methylisothiazol-3(2H)-one	2682-20-4 220-239-6 613-326-00-9 01-2120764690-50	Acute Tox. 2; H330 Acute Tox. 3; H311 Acute Tox. 3; H301 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071	>= 0,0025 - < 0,025

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

rsion	Revision Date: 20.10.2023	SDS Number: 6002209	Date of last issue: 02.02.2023 Date of first issue: 13.08.2019
			M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 1
			specific concentration limit Skin Sens. 1A; H317 >= 0,0015 %
methy	on mass of 5-chloro-2 /I-2H-isothiazol-3-one /I-2H-isothiazol-3-one	and 2-	-5 Acute Tox. 2; H330 0,0015 Acute Tox. 2; H310
Pyridi salt	ne-2-thiol 1-oxide, so	dium 3811-73-2 223-296-5 613-344-00 01-2119493	

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

sion	Revision Date:	SDS Number:	Date of last issue: 02.02.2023			
	20.10.2023	6002209	Date of first issue: 13.08.2019			
			STOT RE 1; H372 (Nervous system) Aquatic Acute 1; H400 Aquatic Chronic 2; H411 EUH070			
			M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 1			
			Acute toxicity esti- mate			
			Acute oral toxicity: 500 mg/kg Acute inhalation tox- icity (dust/mist): 0,5 mg/l Acute dermal toxicity: 790 mg/kg			
	ances with a workplace					
bariur	n sulfate	7727-43-7 231-784-4 01-2119491274	-35	< 1		
kaolin		1332-58-7 310-194-1	>= 1 - <	< 1		
mang	anese ferrite black spine	l 68186-94-7 269-056-3 01-2119457599	>= 1 - <	< 1		

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice	:	Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). Move out of dangerous area. First aider needs to protect himself.
If the local		

If inhaled

: Move to fresh air.



Caparo	OColor Vollton-	und Abtönfa	rbe Ode			
Version	Revision Date:	SDS Number:	Date of last issue: 02.02.2023			
4.0	20.10.2023	6002209	Date of first issue: 13.08.2019			
In cas	se of skin contact		solvents or thinners. htact, immediately flush skin with soap and plenty			
In cas	se of eye contact	IF IN EYES: F	n persists: Get medical advice/ attention. Rinse cautiously with water for several minutes. act lenses, if present and easy to do. Continue			
lf swa	llowed		advice. with water and drink afterwards plenty of water. DO NOT induce vomiting.			
4.2 Most i	4.2 Most important symptoms and effects, both acute and delayed					
Risks		: May cause ar	allergic skin reaction.			

4.3 Indication of any immediate medical attention and special treatment needed

Treatment

: No information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media		
Suitable extinguishing media	:	Use water spray, alcohol-resistant foam, dry chemical or car- bon dioxide. Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment. Do not use a solid water stream as it may scatter and spread fire.
Unsuitable extinguishing media	:	None known.
5.2 Special hazards arising from	the	e substance or mixture
Specific hazards during fire fighting	:	In case of fire hazardous decomposition products may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocar- bons (smoke).
5.3 Advice for firefighters		
Special protective equipment for fire-fighters	:	Wear self-contained breathing apparatus for firefighting if nec- essary.
Further information	:	Standard procedure for chemical fires. The product itself does not burn.
		0.100



CaparolColor Vollton- und Abtönfarbe Ode

Version	Revision Date:	SDS Number:	Date of last issue: 02.02.2023
4.0	20.10.2023	6002209	Date of first issue: 13.08.2019

SECTION 6: Accidental release measures

6.1 Personal precautions, prote	ctive equipment and emergency procedures
Personal precautions	: Use protective shoes or boots with rough rubber sole. Material can create slippery conditions. Do not get in eyes, on skin, or on clothing.
6.2 Environmental precautions	
Environmental precautions	 Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities. Do not flush into surface water or sanitary sewer system.
6.3 Methods and material for co	ontainment and cleaning up
Methods for cleaning up	 Keep in suitable, closed containers for disposal. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

6.4 Reference to other sections

For further information see Section 7 of the safety data sheet. , For personal protection see section 8., For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	:	For personal protection see section 8. No special technical protective measures required.
		In addition, the current technical information for this product and its application on www.caparol.com must be observed.
Hygiene measures	:	Wash hands before eating, drinking, or smoking. Do not eat, drink or smoke when using this product. Remove contaminat- ed clothing and protective equipment before entering eating areas.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers	:	Perishable if frozen. To maintain product quality, do not store in heat or direct sunlight. Store at room temperature in the original container. Containers which are opened must be care- fully resealed and kept upright to prevent leakage.

Advice on common storage : Keep away from oxidizing agents and strongly acid or alkaline



CaparolColor Vollton- und Abtönfarbe Ode

Version	Revision Date:	SDS Number:	Date of last issue: 02.02.2023	
4.0	20.10.2023	6002209	Date of first issue: 13.08.2019	

materials.

Storage class (TRGS 510) : 10

7.3 Specific end use(s)

Specific use(s) : This information is not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis			
barium sulfate	7727-43-7	AGW (Inhalable fraction)	10 mg/m3	DE TRGS 900			
	Peak-limit cat	egory: 2;(II)					
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child						
		AGW (Alveolate fraction)	1,25 mg/m3	DE TRGS 900			
	Peak-limit cat						
			compliance with the OEL a of harming the unborn child	and biological			
		BM (Alveolar dust fraction)	0,5 mg/m3	DE TRGS 527			
kaolin	1332-58-7	TWA (Respirable dust)	0,1 mg/m3	2004/37/EC			
	Further information: Carcinogens or mutagens						
manganese ferrite black spinel	68186-94-7	AGW (Inhalable fraction)	0,2 mg/m3 (Manganese)	DE TRGS 900			
·	Peak-limit category: 8;(II)						
	Further information: For Permanganates an excursion factor of 1(II) applies.,						
	When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child						
		AGW (Alveolate fraction)	0,02 mg/m3 (Manganese)	DE TRGS 900			
	Peak-limit category: 8;(II)						
	Further information: For Permanganates an excursion factor of 1(II) applies., When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child						
		TWA (inhalable fraction)	0,2 mg/m3 (Manganese)	2017/164/EU			
	Further inform	nation: Indicative	· · · · · · · · · · · · · · · · · · ·				
		TWA (Respirable fraction)	0,05 mg/m3 (Manganese)	2017/164/EU			



CaparolColor Vollton- und Abtönfarbe Ode

ersion 0	Revision Da 20.10.2023	te: SDS 6002		Date of last issue: 02.02.2 Date of first issue: 13.08.2				
ĺ		Further inform	nation: Indicative					
titaniu	ım dioxide; [in	13463-67-7	AGW (Inhalable	10 mg/m3	DE TRGS			
	er form con-		fraction)	(Titanium dioxide)	900			
	g 1 % or		,					
	of particles							
	erodynamic							
diame	eter ≤ 10 µm]							
	·	Peak-limit category: 2;(II)						
		Further information: When there is compliance with the OEL and biological						
		tolerance values, there is no risk of harming the unborn child						
			AGW (Alveolate	1,25 mg/m3	DE TRGS			
			fraction)	(Titanium dioxide)	900			
		Peak-limit category: 2;(II)						
		Further information: When there is compliance with the OEL and biological						
		tolerance valu	ues, there is no risł	c of harming the unborn ch	nild			
			BM (Alveolar	0,5 mg/m3	DE TRGS			
			dust fraction)		527			
Pyridi	ne-2-thiol 1-	3811-73-2	AGW (Inhalable	0,2 mg/m3	DE TRGS			
oxide,	, sodium salt		fraction)	-	900			
		Peak-limit cat	egory: 2;(II)		•			
				otion, When there is compl	iance with the OEL			
				there is no risk of harming				

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

	. ,			
Substance name	End Use	Routes of expo- sure	Potential health ef- fects	Value
barium sulfate	Consumers	Inhalation	Long-term systemic effects	10,00 mg/m3
	Consumers	Ingestion	Long-term systemic effects	13000,00 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	10,00 mg/m3
	Workers	Inhalation	Long-term local ef- fects	10,00 mg/m3
manganese ferrite black spinel	Workers	Inhalation	Long-term systemic effects	10,00 mg/m3
	Workers	Inhalation	Long-term local ef- fects	10,00 mg/m3
titanium dioxide; [in powder form contain- ing 1 % or more of particles with aerody- namic diameter ≤ 10 µm]	Consumers	Ingestion	Long-term systemic effects	700,00 mg/kg bw/day
	Workers	Inhalation	Long-term local ef- fects	10,00 mg/m3

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

 Substance name
 Environmental Compartment
 Value



CaparolColor Vollton- und Abtönfarbe Ode

ersion 0	Revision Date: 20.10.2023	SDS Number: 6002209	Date of last issue: Date of first issue:	
0	20.10.2023	0002209		. 13.00.2019
bariur	m sulfate	Fresh water		115 µg/l
		Fresh water	sediment	600,4 mg/kg dry weight (d.w.)
		Soil		207,7 mg/kg dry weight (d.w.)
		Sewage trea	itment plant	62,2 mg/l
conta cles v	titanium dioxide; [in powder form containing 1 % or more of parti- cles with aerodynamic diameter ≤ 10 µm]		itment plant	100 mg/l
		Fresh water		0,184 mg/l
		Soil		100 mg/kg dry weight (d.w.)
		Sea water		0,0184 mg/l
		Fresh water	sediment	1000 mg/kg dry weight (d.w.)
		Sea sedimer	nt	100 mg/kg dry weight (d.w.)
		Intermittent u	ise/release	0,193 mg/l

8.2 Exposure controls

Personal protective equipment					
Eye/face protection	:	DGUV Regulation 112-192 - Use of eye and face protection			
		Goggles			
Hand protection Material Glove thickness Protective index	:	Nitrile rubber 0,2 mm Class 3			
Remarks	:	Before removing gloves clean them with soap and water. Wear suitable gloves tested to EN374. DGUV Regulation 112-195 - Use of protective gloves			
Skin and body protection	:	Safety shoes Long sleeved clothing			
		Choose body protection according to the amount and con- centration of the dangerous substance at the work place.			
		Skin should be washed after contact.			
		Remove and wash contaminated clothing before re-use. During spray application: impervious clothing			
Respiratory protection	:	No personal respiratory protective equipment normally re-			



CaparolColor Vollton- und Abtönfarbe Ode

4.0 00.4			
4.0 20.1	0.2023	6002209	Date of first issue: 13.08.2019

quired.

DGUV Regulation 112-190 - Use of breathing equipment

During spray application: Do not breathe spray dust. Use A2/P2 combination filter for paint spraying.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	:	liquid
Color	:	green
Odor	:	No data available
Melting point/freezing point	:	ca. 0 °C
Boiling point/boiling range	:	ca. 100 °C
Upper explosion limit / Upper flammability limit	:	not determined
Lower explosion limit / Lower flammability limit	:	not determined
Flash point	:	> 100 °C
Autoignition temperature	:	not determined
Decomposition temperature	:	Not applicable
рН	:	8 Concentration: 100 %
Viscosity Viscosity, dynamic	:	No data available



Capar	CaparolColor Vollton- und Abtönfarbe Ode						
Version 4.0	Revision Date: 20.10.2023		S Number: 2209	Date of last issue: 02.02.2023 Date of first issue: 13.08.2019			
	ubility(ies) Vater solubility	:	completely misci	ble			
	tition coefficient: n- anol/water	:	Not applicable				
Vap	or pressure	:	ca. 23,4 hPa (20	°C)			
Rela	ative density	:	not determined				
Den	sity	:	1,3300 g/cm3				
Rela	Relative vapor density		Not applicable				
	r information						
Exp	losives	:	Not applicable				
Oxic	dizing properties	:	Not applicable				
Flar	nmability (liquids)	:	The product is no	ot flammable.			

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions	: No decompo	osition if stored and applied as directed.
---------------------	--------------	--

10.4 Conditions to avoid

Conditions to avoid : Protect from frost, heat and sunlight.



CaparolColor Vollton- und Abtönfarbe Ode

Version	Revision Date: 20.10.2023	SDS Number:	Date of last issue: 02.02.2023
4.0		6002209	Date of first issue: 13.08.2019

10.5 Incompatible materials

Materials to avoid

: Incompatible with acids and bases. Incompatible with oxidizing agents.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

1,2-benzisothiazol-3(2H)-c	ne:
----------------------------	-----

Acute oral toxicity	:	LD50 (Rat): 532 mg/kg					
Acute inhalation toxicity	:	LC50 (Rat): 0,4 mg/l Exposure time: 4 h Test atmosphere: dust/mist					
Acute dermal toxicity	:	LD50 (Rat): > 2.000 mg/kg					
2-methylisothiazol-3(2H)-one	e:						
Acute oral toxicity	:	LD50 (Rat): 120 mg/kg					
Acute inhalation toxicity	:	LC50 (Rat): 0,145 mg/l Exposure time: 4 h Test atmosphere: dust/mist					
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):							
Acute oral toxicity	:	LD50 (Rat): 66 mg/kg Method: OECD Test Guideline 401					
A suite introductions to visit.	-						

Acute inhalation toxicity	:	LC50 (Rat): 0,17 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: OECD Test Guideline 403
Acute dermal toxicity	:	LD50 (Rat): > 141 mg/kg Method: OECD Test Guideline 402

Pyridine-2-thiol 1-oxide, sodium salt:



ersion .0	Revision Date: 20.10.2023		S Number: 2209	Date of last issue: 02.02.2023 Date of first issue: 13.08.2019			
Acute	e oral toxicity			estimate: 500 mg/kg toxicity estimate according to Regulation (EC)			
Acute inhalation toxicity			Test atmosphe	toxicity estimate according to Regulation (EC)			
Acute	e dermal toxicity			estimate: 790 mg/kg toxicity estimate according to Regulation (EC)			
	corrosion/irritation lassified based on ava	ilable ir	nformation.				
	ous eye damage/eye i lassified based on ava						
Resp	iratory or skin sensi	tization	1				
-	sensitization cause an allergic skin	reactior	۱.				
-	iratory sensitization lassified based on ava	ilable ir	nformation.				
	n cell mutagenicity lassified based on ava	ilable ir	nformation.				
Carcinogenicity Not classified based on available information. Reproductive toxicity Not classified based on available information.							
						STOT-single exposure Not classified based on available information.	
	STOT-repeated exposure Not classified based on available information.						
-	r ation toxicity lassified based on ava	ilable ir	nformation.				
1.2 Infor	mation on other haza	ards					
Endo	ocrine disrupting pro	perties					
<u>Prod</u> Asse	uct: ssment			/mixture does not contain components consid ndocrine disrupting properties according to			



CaparolColor Vollton- und Abtönfarbe Ode

Version Revision Da	te: SDS Number:	Date of last issue: 02.02.2023
4.0 20.10.2023	6002209	Date of first issue: 13.08.2019

REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

1,2-benzisothiazol-3(2H)-one:		
Toxicity to fish :	LC50 (Oncorhynchus mykiss (rainbow trout)): 2,2 mg/l Exposure time: 96 h Method: OECD Test Guideline 203	
Toxicity to daphnia and other : aquatic invertebrates	EC50 (Daphnia): 3,27 mg/l Exposure time: 48 h Method: OECD Test Guideline 202	
Toxicity to algae/aquatic : plants	EC50 (Selenastrum capricornutum (green algae)): 0,11 Exposure time: 72 h Method: OECD Test Guideline 201	mg/l
M-Factor (Acute aquatic tox- : icity)	1	
M-Factor (Chronic aquatic : toxicity)	1	
2-methylisothiazol-3(2H)-one:		
M-Factor (Acute aquatic tox- : icity)	10	
M-Factor (Acute aquatic tox- :		
M-Factor (Acute aquatic tox- : icity) M-Factor (Chronic aquatic : toxicity)	1	-000
M-Factor (Acute aquatic tox- : icity) M-Factor (Chronic aquatic : toxicity)		-one
M-Factor (Acute aquatic tox- : icity) M-Factor (Chronic aquatic : toxicity) reaction mass of 5-chloro-2-m	1 ethyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3	-one
M-Factor (Acute aquatic tox- icity) M-Factor (Chronic aquatic toxicity) reaction mass of 5-chloro-2-m (3:1): M-Factor (Acute aquatic tox-	1 ethyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3	-one
M-Factor (Acute aquatic tox- icity) M-Factor (Chronic aquatic toxicity) reaction mass of 5-chloro-2-m (3:1): M-Factor (Acute aquatic tox- icity) M-Factor (Chronic aquatic	1 ethyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3 100 100	-one



Version 4.0	Revision Date: 20.10.2023		0S Number: 02209	Date of last issue: 02.02.2023 Date of first issue: 13.08.2019
icity)				
M-Fac toxicit	ctor (Chronic aquatic y)	:	1	
bariu	m sulfate:			
Toxici	ity to fish	:	Remarks: No tox	icity at the limit of solubility.
	ity to daphnia and other ic invertebrates	:	Remarks: No tox	icity at the limit of solubility.
Toxici plants	ity to algae/aquatic	:	Remarks: No tox	icity at the limit of solubility.
Toxici icity)	ity to fish (Chronic tox-	:	Remarks: No tox	icity at the limit of solubility.
	ity to daphnia and other ic invertebrates (Chron- city)	:	Remarks: No tox	icity at the limit of solubility.
	stence and degradabil Ita available	ity		
12.3 Bioad	ccumulative potential			
<u>Comp</u>	oonents:			
Partiti	enzisothiazol-3(2H)-on on coefficient: n- ol/water	e: :	log Pow: 0,63 - 0 pH: 7),76
2-met	thylisothiazol-3(2H)-on	e:		
Partiti	on coefficient: n- ol/water	:	log Pow: -0,486 (pH: 7	(25 °C)
reacti (3:1):	ion mass of 5-chloro-2	-me	ethyl-2H-isothiazo	ol-3-one and 2-methyl-2H-isothiazol-3-one
	on coefficient: n- ol/water	:		; Fest Guideline 117
Pyrid	ine-2-thiol 1-oxide, soc	liur	n salt:	
i yina			ii Valti	



CaparolColor Vollton- und Abtönfarbe Ode									
Version 4.0	Revision Date: 20.10.2023		DS Number: 002209	Date of last issue: 02.02.2023 Date of first issue: 13.08.2019					
12.4 Mobility in soil No data available									
	llts of PBT and vPvB	asse	ssment						
Prod	uct:								
	ssment	:	to be either per	/mixture contains no components considered sistent, bioaccumulative and toxic (PBT), or and very bioaccumulative (vPvB) at levels of					
12.6 Endo	ocrine disrupting prop	oertie	es.						
Prod	uct:								
Asse	ssment	:	ered to have er REACH Article	/mixture does not contain components consid- ndocrine disrupting properties according to 57(f) or Commission Delegated regulation 0 or Commission Regulation (EU) 2018/605 at or higher.					
12.7 Othe	r adverse effects								
<u>Prod</u> Additi matio	ional ecological infor-	:		tal hazard cannot be excluded in the event of handling or disposal.					
SECTION 13: Disposal considerations									
13.1 Waste treatment methods Product : .									
			Waste should r	not be disposed of via wastewater.					
Conta	aminated packaging	:	Only completel cling.	y emptied containers should be given for recy-					

Waste Code : used product 080112, waste paint and varnish other than those mentioned in 08 01 11*

SECTION 14: Transport information

14.1 UN number or ID number

ADN

: Not regulated as a dangerous good



CaparolColor Vollton- und Abtönfarbe Ode					
Version 4.0	Revision Date: 20.10.2023	SI	DS Number:)02209	Date of last issue: 02.02.2023 Date of first issue: 13.08.2019	
ADR		:	Not regulated as	a dangerous good	
RID		:	Not regulated as	a dangerous good	
IMDG	ì	:	Not regulated as	a dangerous good	
ΙΑΤΑ		:	Not regulated as	a dangerous good	
14.2 UN proper shipping name					
ADN		:	Not regulated as	a dangerous good	
ADR		:	Not regulated as	a dangerous good	
RID		:	Not regulated as	a dangerous good	
IMDG	;	:	Not regulated as	a dangerous good	
ΙΑΤΑ		:	Not regulated as	a dangerous good	
14.3 Transport hazard class(es)					
ADN		:	Not regulated as	a dangerous good	
ADR		:	Not regulated as	a dangerous good	
RID		:	Not regulated as	a dangerous good	
IMDG	ì	:	Not regulated as	a dangerous good	
ΙΑΤΑ		:	Not regulated as	a dangerous good	
14.4 Packing group					
ADN		:	Not regulated as	a dangerous good	
ADR		:	Not regulated as	a dangerous good	
RID		:	Not regulated as	a dangerous good	
IMDG	i	:	Not regulated as	a dangerous good	
ΙΑΤΑ	(Cargo)	:	Not regulated as	a dangerous good	
ΙΑΤΑ	(Passenger)	:	Not regulated as	a dangerous good	
14.5 Envii	ronmental hazards				
Not re	egulated as a dangerou	ıs go	ood		
14.6 Spec	ial precautions for us	ser			
Rema	arks	:	Not classified as lations.	dangerous in the meaning of transport regu-	

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.



CaparolColor Vollton- und Abtönfarbe Ode

Version	Revision Date:	SDS Number:	Date of last issue: 02.02.2023
4.0	20.10.2023	6002209	Date of first issue: 13.08.2019

SECTION 15: Regulatory information

15.1 Safety, health and environmenture	ntal regulations/legislatio	on specific for the substance or mix-
REACH - Restrictions on the ma the market and use of certain da mixtures and articles (Annex XV	angerous substances,	: Conditions of restriction for the fol- lowing entries should be considered: Number on list 75, 3
		If you intend to use this product as tattoo ink, please contact your ven- dor.
REACH - Candidate List of Subs Concern for Authorization (Articl		: This product is a mixture and does not contain Substances of Very High Concern (SVHC) equal or above 0.1%. Therefore no advised uses have to be defined and no chemical safety assessment has to be gener- ated.
Regulation (EC) No 1005/2009 of plete the ozone layer	on substances that de-	: Not applicable
Regulation (EU) 2019/1021 on p tants (recast)	persistent organic pollu-	: Not applicable
REACH - List of substances sub (Annex XIV)	ject to authorisation	: None
Seveso III: Directive 2012/18/EL pean Parliament and of the Cou control of major-accident hazard dangerous substances.	ncil on the	ot applicable
Water hazard class (Germa- : ny)	WGK 1 slightly water en Classification according	
	: BSW20 Coating materia	ls, water-based
Volatile organic compounds :	emissions (integrated po	24 November 2010 on industrial ollution prevention and control) nds (VOC) content: 0,02 %
Volatile organic compounds	: Directive 2004/42/EC < 0.1 % < 1 g/l	



CaparolColor Vollton- und Abtönfarbe Ode

Version	Revision Date:	SDS Number:	Date of last issue: 02.02.2023
4.0	20.10.2023	6002209	Date of first issue: 13.08.2019

Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical Safety Assessment

A Chemical Safety Assessment is not required for this mixture.

SECTION 16: Other information

Full text of H-Statements

H301 H302 H310 H311 H314	:	Toxic if swallowed. Harmful if swallowed. Fatal in contact with skin. Toxic in contact with skin. Causes severe skin burns and eye damage.
H315 H315 H317 H318 H319 H330 H331 H351 H351 H372 H400 H410 H411 EUH070 EUH071	· · · · · · · · · · · · · · · · · · ·	Causes severe skin burns and eye damage. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. Causes serious eye irritation. Fatal if inhaled. Toxic if inhaled. Suspected of causing cancer if inhaled. Causes damage to organs through prolonged or repeated exposure. Very toxic to aquatic life. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects. Toxic to aquatic life with long lasting effects. Toxic by eye contact. Corrosive to the respiratory tract.
Full text of other abbreviation	ons	
Acute Tox. Aquatic Acute Aquatic Chronic Carc. Eye Dam. Eye Irrit. Skin Corr. Skin Irrit. Skin Sens. STOT RE 2004/37/EC		Acute toxicity Short-term (acute) aquatic hazard Long-term (chronic) aquatic hazard Carcinogenicity Serious eye damage Eye irritation Skin corrosion Skin irritation Skin sensitization Specific target organ toxicity - repeated exposure Europe. Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens or mutagens



CaparolColor Vollton- und Abtönfarbe Ode

Version 4.0	Revision Date: 20.10.2023	SDS Number: 6002209	Date of last issue: 02.02.2023 Date of first issue: 13.08.2019	
2017/	164/EU	•	mmission Directive 2017/164/EU establishing a indicative occupational exposure limit values	
DE TRGS 527		: Germany. TRGS 527 - Activities with nanomaterials		
DE TRGS 900			: Germany. TRGS 900 - Occupational exposure limit values.	
2004/37/EC / TWA		: Long term exposure limit		
2017/164/EU / TWA		: Limit Value	: Limit Value - eight hours	
DE TI	RGS 527 / BM	: Assessmen	: Assessment scale	
DE TRGS 900 / AGW		: Time Weigh	ted Average	

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECX - Concentration associated with %' response; ELX - Loading rate associated with %' response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCX - Concentration associated with %' growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; ICSO - Half maximal inhibitory concentration; ICAO - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; ICSO - Half maximal inhibitory concentration; ICAO - International Maritime Organization; IESC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIOC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR -

Further information

Other information:

No exposure scenario communication is required for this product according to REACH Regulation No. 1907/2006 EC.

Communication of Uses is not required in accordance with REACH Article 31(1)(a) - registered substances / mixtures do not meet the criteria for classification as hazardous in accordance with Regulations 1272/2008 EC or 1999/45/EC.

Sources of key data used to compile the Material Safety Data Sheet:

ECHA WebSite

ACGIH (American Conference of Government Industrial Hygienists). 2014 TLVs and BEIs. Threshold Limit Values (TLVs) for chemical substances and physical agents and Biological Exposure Indices (BEIs) with Seventh Edition documentation. 2014 ACGIH, Cincinnati OH NIOSH - Registry of toxic effects of chemical substances

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX'S - Dangerous properties of industrial materials

GESTIS - Database on hazardous substances - Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA, Institute for Occupational Safety and Health of the German Social Accident Insurance)

Toxnet - Toxicology Data Network



Caparol Color Vollton- und Abtönfarbe OdeVersionRevision Date:SDS Number:Date of last issue: 02.02.20234.020.10.20236002209Date of first issue: 13.08.2019

Classification of the mixture:

Classification procedure:

Skin Sens. 1 H317

Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

REACH Information

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our upstream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly.

DE / EN