according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

CaparolColor Vollton- und Abtönfarbe Sch

Version Revision Date: SDS Number: Date of last issue: 02.02.2023 4.0 05.09.2023 6002218 Date of first issue: 13.08.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : CaparolColor Vollton- und Abtönfarbe Sch

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Water-borne coatings

stance/Mixture

Recommended restrictions

on use

: within adequate application - none

1.3 Details of the supplier of the safety data sheet

Company : Caparol Farben Lacke GmbH

Roßdörfer Straße 50 64372 Ober-Ramstadt

Telephone : +496154710 Telefax : +4961547170222

Website

E-mail address Responsi-

ble/issuing person

msds@dr-rmi.com

1.4 Emergency telephone

Emergency telephone 1 : +49613284463 GBK GmbH

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin sensitization, Category 1 H317: May cause an allergic skin reaction.

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008)

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

CaparolColor Vollton- und Abtönfarbe Sch

Version Revision Date: SDS Number: Date of last issue: 02.02.2023 4.0 05.09.2023 6002218 Date of first issue: 13.08.2019

Hazard pictograms :

Signal Word : Warning

Hazard Statements : H317 May cause an allergic skin reaction.

Precautionary Statements : P101 If medical advice is needed, have product container or

label at hand.

P102 Keep out of reach of children.

Prevention:

P261 Avoid breathing mist or vapors.

P280 Wear protective gloves.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Hazardous ingredients which must be listed on the label:

1,2-benzisothiazol-3(2H)-one

2-methylisothiazol-3(2H)-one

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Additional Labeling

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not

breathe spray or mist.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

CaparolColor Vollton- und Abtönfarbe Sch

Version Revision Date: SDS Number: Date of last issue: 02.02.2023 4.0 05.09.2023 6002218 Date of first issue: 13.08.2019

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Emulsion paint, aqueous

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7 236-675-5 022-006-00-2 01-2119489379-17	Carc. 2; H351	>= 1 - < 10
1,2-benzisothiazol-3(2H)-one	2634-33-5 220-120-9 613-088-00-6 01-2120761540-60	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 2; H411 Acute Tox. 2; H330 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1 specific concentration limit Skin Sens. 1; H317 >= 0,05 %	>= 0,0025 - < 0,025
2-methylisothiazol-3(2H)-one	2682-20-4 220-239-6 613-326-00-9 01-2120764690-50	Acute Tox. 2; H330 Acute Tox. 3; H311 Acute Tox. 3; H301 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071	>= 0,0025 - < 0,025

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

		600	S Number: 2218	Date of last issue: 02.02.2023 Date of first issue: 13.08.2019
				M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 1
				specific concentration limit Skin Sens. 1A; H317 >= 0,0015 %
methyl-	n mass of 5-chloro-2- 2H-isothiazol-3-one 2H-isothiazol-3-one	and 2-	55965-84-9 613-167-00-5 01-21207646	,
Substa kaolin	nces with a workplac	е ехро	sure limit : 1332-58-7	>= 1 - < 10

For explanation of abbreviations see section 16.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

CaparolColor Vollton- und Abtönfarbe Sch

Version Revision Date: SDS Number: Date of last issue: 02.02.2023 4.0 05.09.2023 6002218 Date of first issue: 13.08.2019

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice : Never give anything by mouth to an unconscious person.

If you feel unwell, seek medical advice (show the label where

possible)

Move out of dangerous area. First aider needs to protect himself.

If inhaled : Move to fresh air.

In case of skin contact : Do NOT use solvents or thinners.

In case of contact, immediately flush skin with soap and plenty

of water.

In case of eye contact : If eye irritation persists: Get medical advice/ attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing.

If swallowed : Seek medical advice.

Clean mouth with water and drink afterwards plenty of water.

If swallowed, DO NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Risks : May cause an allergic skin reaction.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or car-

bon dioxide.

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Do not use a solid water stream as it may scatter and spread

fire.

Unsuitable extinguishing

media

None known.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

CaparolColor Vollton- und Abtönfarbe Sch

Version Revision Date: SDS Number: Date of last issue: 02.02.2023 4.0 05.09.2023 6002218 Date of first issue: 13.08.2019

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire

fighting

In case of fire hazardous decomposition products may be

produced such as:

Carbon monoxide, carbon dioxide and unburned hydrocar-

bons (smoke).

5.3 Advice for firefighters

Special protective equipment:

for fire-fighters

Wear self-contained breathing apparatus for firefighting if nec-

essary.

Further information : Standard procedure for chemical fires.

The product itself does not burn.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use protective shoes or boots with rough rubber sole.

Material can create slippery conditions. Do not get in eyes, on skin, or on clothing.

6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Do not flush into surface water or sanitary sewer system.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Keep in suitable, closed containers for disposal.

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

6.4 Reference to other sections

For further information see Section 7 of the safety data sheet.

, For personal protection see section 8., For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : For personal protection see section 8.

No special technical protective measures required.

In addition, the current technical information for this product and its application on www.caparol.com must be observed.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

CaparolColor Vollton- und Abtönfarbe Sch

Version Revision Date: SDS Number: Date of last issue: 02.02.2023 4.0 05.09.2023 6002218 Date of first issue: 13.08.2019

Hygiene measures : Wash hands before eating, drinking, or smoking. Do not eat,

drink or smoke when using this product. Remove contaminated clothing and protective equipment before entering eating

areas.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Perishable if frozen. To maintain product quality, do not store in heat or direct sunlight. Store at room temperature in the original container. Containers which are opened must be care-

fully resealed and kept upright to prevent leakage.

Advice on common storage : Keep away from oxidizing agents and strongly acid or alkaline

materials.

Storage class (TRGS 510) : 12

7.3 Specific end use(s)

Specific use(s) : This information is not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
kaolin	1332-58-7	TWA (Respirable dust)	0,1 mg/m3	2004/37/EC
	Further inform	Further information: Carcinogens or mutagens		
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7	AGW (Inhalable fraction)	10 mg/m3 (Titanium dioxide)	DE TRGS 900
	Peak-limit category: 2;(II)			
	Further information: When there is compliance with the OEL and biological			
	tolerance values, there is no risk of harming the unborn child			
		AGW (Alveolate fraction)	1,25 mg/m3 (Titanium dioxide)	DE TRGS 900
	Peak-limit category: 2;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		BM (Alveolar dust fraction)	0,5 mg/m3	DE TRGS 527

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

CaparolColor Vollton- und Abtönfarbe Sch

Version Revision Date: SDS Number: Date of last issue: 02.02.2023 4.0 05.09.2023 6002218 Date of first issue: 13.08.2019

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Routes of exposure	Potential health effects	Value
iron hydroxide oxide yellow	Workers	Inhalation	Long-term systemic effects	10,00 mg/m3
	Workers	Inhalation	Long-term local ef- fects	10,00 mg/m3
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm]	Consumers	Ingestion	Long-term systemic effects	700,00 mg/kg bw/day
	Workers	Inhalation	Long-term local ef- fects	10,00 mg/m3

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm]	Sewage treatment plant	100 mg/l
	Fresh water	0,184 mg/l
	Soil	100 mg/kg dry weight (d.w.)
	Sea water	0,0184 mg/l
	Fresh water sediment	1000 mg/kg dry weight (d.w.)
	Sea sediment	100 mg/kg dry weight (d.w.)
	Intermittent use/release	0,193 mg/l

8.2 Exposure controls

Personal protective equipment

Eye/face protection : DGUV Regulation 112-192 - Use of eye and face protection

Goggles

Hand protection

Material : Nitrile rubber Glove thickness : 0,2 mm Protective index : Class 3

Remarks : Before removing gloves clean them with soap and water.

Wear suitable gloves tested to EN374.

DGUV Regulation 112-195 - Use of protective gloves

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

CaparolColor Vollton- und Abtönfarbe Sch

Version Revision Date: SDS Number: Date of last issue: 02.02.2023 4.0 05.09.2023 6002218 Date of first issue: 13.08.2019

Skin and body protection : Safety shoes

Long sleeved clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Skin should be washed after contact.

Remove and wash contaminated clothing before re-use.

During spray application: impervious clothing

Respiratory protection : No personal respiratory protective equipment normally re-

quired.

DGUV Regulation 112-190 - Use of breathing equipment

During spray application: Do not breathe spray dust. Use

A2/P2 combination filter for paint spraying.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid

Color : dark gray

Odor : No data available

Melting point/freezing point : ca. 0 °C

Boiling point/boiling range : ca. 100 °C

Upper explosion limit / Upper

flammability limit

not determined

Lower explosion limit / Lower

flammability limit

not determined

Flash point : Not applicable

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

CaparolColor Vollton- und Abtönfarbe Sch

Version Revision Date: SDS Number: Date of last issue: 02.02.2023 4.0 05.09.2023 6002218 Date of first issue: 13.08.2019

Autoignition temperature : not determined

Decomposition temperature : Not applicable

pH : 8

Concentration: 100 %

Viscosity

Viscosity, dynamic : No data available

Solubility(ies)

Water solubility : completely miscible

Partition coefficient: n-

octanol/water

Not applicable

Vapor pressure : ca. 23,4 hPa (20 °C)

Relative density : not determined

Density : 1,2600 g/cm3

Relative vapor density : Not applicable

9.2 Other information

Explosives : Not applicable

Oxidizing properties : Not applicable

Flammability (liquids) : The product is not flammable.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

CaparolColor Vollton- und Abtönfarbe Sch

Version Revision Date: SDS Number: Date of last issue: 02.02.2023 4.0 05.09.2023 6002218 Date of first issue: 13.08.2019

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

10.4 Conditions to avoid

Conditions to avoid : Protect from frost, heat and sunlight.

10.5 Incompatible materials

Materials to avoid : Incompatible with acids and bases.

Incompatible with oxidizing agents.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

1,2-benzisothiazol-3(2H)-one:

Acute oral toxicity : LD50 (Rat): 532 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0,4 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg

2-methylisothiazol-3(2H)-one:

Acute oral toxicity : LD50 (Rat): 120 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0,145 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

CaparolColor Vollton- und Abtönfarbe Sch

Version Revision Date: SDS Number: Date of last issue: 02.02.2023 4.0 05.09.2023 6002218 Date of first issue: 13.08.2019

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one

(3:1):

Acute oral toxicity : LD50 (Rat): 66 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 0,17 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rat): > 141 mg/kg

Method: OECD Test Guideline 402

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

CaparolColor Vollton- und Abtönfarbe Sch

SDS Number: Version Revision Date: Date of last issue: 02.02.2023 05.09.2023 6002218 4.0 Date of first issue: 13.08.2019

The substance/mixture does not contain components consid-Assessment

> ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

1,2-benzisothiazol-3(2H)-one:

Toxicity to fish LC50 (Oncorhynchus mykiss (rainbow trout)): 2,2 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia): 3,27 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 (Selenastrum capricornutum (green algae)): 0,11 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

M-Factor (Acute aquatic tox-

icity)

M-Factor (Chronic aquatic

toxicity)

2-methylisothiazol-3(2H)-one:

M-Factor (Acute aquatic tox- : 10

icity)

M-Factor (Chronic aquatic

toxicity)

: 1

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):

M-Factor (Acute aquatic tox-

100

icity)

M-Factor (Chronic aquatic

toxicity)

100

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

CaparolColor Vollton- und Abtönfarbe Sch

Version Revision Date: SDS Number: Date of last issue: 02.02.2023 4.0 05.09.2023 6002218 Date of first issue: 13.08.2019

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

Components:

1,2-benzisothiazol-3(2H)-one:

Partition coefficient: n- : log Pow: 0,63 - 0,76

octanol/water pH: 7

2-methylisothiazol-3(2H)-one:

Partition coefficient: n- : log Pow: -0,486 (25 °C)

octanol/water pH: 7

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one

(3:1):

Partition coefficient: n- : log Pow: <= 0,75

octanol/water Method: OECD Test Guideline 117

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

CaparolColor Vollton- und Abtönfarbe Sch

Version Revision Date: SDS Number: Date of last issue: 02.02.2023 4.0 05.09.2023 6002218 Date of first issue: 13.08.2019

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product :

Waste should not be disposed of via wastewater.

Contaminated packaging : Only completely emptied containers should be given for recy-

cling.

Waste Code : used product

080112, waste paint and varnish other than those mentioned

in 08 01 11*

SECTION 14: Transport information

14.1 UN number or ID number

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.4 Packing group

ADN : Not regulated as a dangerous good

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

CaparolColor	Vollton- und	l Abtönfarbe	Sch
Japai Giggioi	VOIILOII GIIG	i Abtoiliai be	· OCII

Version Revision Date: SDS Number: Date of last issue: 02.02.2023 4.0 05.09.2023 6002218 Date of first issue: 13.08.2019

ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA (Cargo) : Not regulated as a dangerous good
IATA (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Remarks : Not classified as dangerous in the meaning of transport regu-

lations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 75, 3

If you intend to use this product as tattoo ink, please contact your vendor.

REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59).

This product is a mixture and does not contain Substances of Very High Concern (SVHC) equal or above 0.1%. Therefore no advised uses have to be defined and no chemical safety assessment has to be generated.

ated.

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

: Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Not applicable

REACH - List of substances subject to authorisation

(Annex XIV)

: None

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

CaparolColor Vollton- und Abtönfarbe Sch

Version Revision Date: SDS Number: Date of last issue: 02.02.2023 4.0 05.09.2023 6002218 Date of first issue: 13.08.2019

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

Water hazard class (Germa-

ny)

WGK 1 slightly water endangering

Classification according to AwSV, Annex 1 (5.2)

: BSW20 Coating materials, water-based

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial

emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: < 0,01 %

Volatile organic compounds : Directive 2004/42/EC

< 0.1 % < 1 g/l

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical Safety Assessment

A Chemical Safety Assessment is not required for this mixture.

SECTION 16: Other information

Full text of H-Statements

H301 : Toxic if swallowed.
H302 : Harmful if swallowed.
H310 : Fatal in contact with skin.
H311 : Toxic in contact with skin.

H314 : Causes severe skin burns and eye damage.

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction. H318 : Causes serious eye damage.

H330 : Fatal if inhaled.

H351 : Suspected of causing cancer if inhaled.

H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.H411 : Toxic to aquatic life with long lasting effects.

EUH071 : Corrosive to the respiratory tract.

Full text of other abbreviations

Acute Tox. : Acute toxicity

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

CaparolColor Vollton- und Abtönfarbe Sch

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 02.02.2023

 4.0
 05.09.2023
 6002218
 Date of first issue: 13.08.2019

Aquatic Acute : Short-term (acute) aquatic hazard Aquatic Chronic : Long-term (chronic) aquatic hazard

Carc. : Carcinogenicity
Eye Dam. : Serious eye damage
Skin Corr. : Skin corrosion
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitization

2004/37/EC : Europe. Directive 2004/37/EC on the protection of workers

from the risks related to exposure to carcinogens or mutagens

at work

DE TRGS 527 : Germany. TRGS 527 - Activities with nanomaterials

DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.

2004/37/EC / TWA : Long term exposure limit

DE TRGS 527 / BM : Assessment scale

DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AllC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EMS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Code for the Construction and Equipment of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Gorial Maritime Organization; IECSC - Inventy and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; DSO - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Conomic Co-operation and Development; OPPTS - Office of Chemicals Safety and Pollution Prevention; PBT

Further information

Other information:

No exposure scenario communication is required for this product according to REACH Regulation No. 1907/2006 EC.

Communication of Uses is not required in accordance with REACH Article 31(1)(a) - registered substances / mixtures do not meet the criteria for classification as hazardous in accordance with Regulations 1272/2008 EC or 1999/45/EC.

Sources of key data used to compile the Material Safety Data Sheet:

ECHA WebSite

ACGIH (American Conference of Government Industrial Hygienists). 2014 TLVs and BEIs. Threshold Limit Values (TLVs) for chemical substances and physical agents and Biological Exposure Indices (BEIs) with Seventh Edition documentation. 2014 ACGIH, Cincinnati OH

NIOSH - Registry of toxic effects of chemical substances

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX'S - Dangerous properties of industrial materials

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

CaparolColor Vollton- und Abtönfarbe Sch

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 02.02.2023

 4.0
 05.09.2023
 6002218
 Date of first issue: 13.08.2019

GESTIS - Database on hazardous substances - Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA, Institute for Occupational Safety and Health of the German Social Accident Insurance)

Toxnet - Toxicology Data Network

Classification of the mixture:

Classification procedure:

Skin Sens. 1

H317

Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

REACH Information

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our upstream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly.

DE / EN