according to Regulation (EC) No. 1907/2006



Capadur F7-LangzeitLasur Eiche

Version Revision Date: Print Date Date of last issue: -

1.0 25.01.2019 26.01.2019 Date of first issue: 25.01.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Capadur F7-LangzeitLasur Eiche

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Solvent-borne coatings

stance/Mixture

Recommended restrictions :

on use

within adequate application - none

1.3 Details of the supplier of the safety data sheet

Company : Caparol Farben Lacke GmbH

Roßdörfer Straße 50 64372 Ober-Ramstadt

Telephone : +496154710
Telefax : +49615471222
E-mail address Responsi- : msds@dr-rmi.com

ble/issuing person

1.4 Emergency telephone number

Emergency telephone num: +49615471202

ber 1

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 H226: Flammable liquid and vapour.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.

according to Regulation (EC) No. 1907/2006

Capadur F7-LangzeitLasur Eiche

Version Revision Date: Print Date Date of last issue: -

1.0 25.01.2019 26.01.2019 Date of first issue: 25.01.2019

Supplemental Hazard : EUH066 Repeated exposure may cause skin

Statements dryness or cracking.

Precautionary statements : P101 If medical advice is needed, have product container or

label at hand.

P102 Keep out of reach of children.

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open

flames and other ignition sources. No smoking.

P271 Use only outdoors or in a well-ventilated area.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immedi-

ately all contaminated clothing. Rinse skin with water.

Additional Labelling

EUH208 Contains 2-methyl-2H-isothiazol-3-one, bis(1,2,2,6,6-pentamethyl-4-piperidyl)

sebacate. May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Alkyd-resin-based wood varnish, solvent-containing

Components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Index-No.		
	Registration number		
naphtha (petroleum), hydrotreated	64742-48-9	Asp. Tox. 1; H304	>= 20 - < 30
heavy	265-150-3	EUH066	
	649-327-00-6		
	01-2119486659-16		
naphtha (petroleum), hydrotreated	64742-48-9	Flam. Liq. 3; H226	>= 10 - < 20
heavy	265-150-3	STOT SE 3; H336	
	649-327-00-6	Asp. Tox. 1; H304	
	01-2119463258-33	EUH066	
bis(1,2,2,6,6-pentamethyl-4-	41556-26-7	Skin Sens. 1; H317	>= 0,1 - < 0,25
piperidyl) sebacate	255-437-1	Aquatic Acute 1;	
	01-2119491304-40	H400	
		Aquatic Chronic 1;	
		H410	
2-methyl-2H-isothiazol-3-one	2682-20-4	Acute Tox. 2; H330	>= 0,0002 - <
	220-239-6	Acute Tox. 3; H311	0,0015
	01-2120764690-50	Acute Tox. 3; H301	
		Skin Corr. 1B; H314	

according to Regulation (EC) No. 1907/2006

Capadur F7-LangzeitLasur Eiche

Version Revision Date: Print Date Date of last issue: -

1.0 25.01.2019 26.01.2019 Date of first issue: 25.01.2019

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : First aider needs to protect himself.

Move out of dangerous area.

If you feel unwell, seek medical advice (show the label where

possible).

Never give anything by mouth to an unconscious person.

If inhaled : Move to fresh air.

If symptoms persist, call a physician.

If unconscious, place in recovery position and seek medical

advice.

If breathing is irregular or stopped, administer artificial respira-

tion.

Call a physician.

In case of skin contact : Take off all contaminated clothing immediately.

In case of contact, immediately flush skin with soap and plenty

of water.

Do NOT use solvents or thinners.

In case of eye contact : IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue

rinsing.

If eye irritation persists: Get medical advice/ attention.

If swallowed : If swallowed, DO NOT induce vomiting.

Clean mouth with water and drink afterwards plenty of water.

Seek medical advice.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No information available.

according to Regulation (EC) No. 1907/2006

Capadur F7-LangzeitLasur Eiche

Version Revision Date: Print Date Date of last issue: -

1.0 25.01.2019 26.01.2019 Date of first issue: 25.01.2019

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or car-

bon dioxide.

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Unsuitable extinguishing

media

None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

In case of fire hazardous decomposition products may be

produced such as:

Carbon monoxide, carbon dioxide and unburned hydrocar-

bons (smoke).

Cool closed containers exposed to fire with water spray.

5.3 Advice for firefighters

Special protective equipment :

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Further information : In the event of fire and/or explosion do not breathe fumes.

Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Remove all sources of ignition.

Ensure adequate ventilation.

When workers are facing concentrations above the exposure

limit they must use appropriate certified respirators.

Do not get in eyes, on skin, or on clothing.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Prevent further leakage or spillage if safe to do so.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal considerations see section 13., For personal protection see section 8., For further information see Section 7 of the safety data sheet.

according to Regulation (EC) No. 1907/2006

Capadur F7-LangzeitLasur Eiche

Version Revision Date: Print Date Date of last issue: -

1.0 25.01.2019 26.01.2019 Date of first issue: 25.01.2019

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Provide sufficient air exchange and/or exhaust in work rooms.

Avoid exceeding the given occupational exposure limits (see

section 8).

For personal protection see section 8.

Advice on protection against

fire and explosion

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Vapours are heavier than

air and may spread along floors. Vapours may form explosive

mixtures with air.

Hygiene measures : Do not eat, drink or smoke when using this product. Wash

hands before eating, drinking, or smoking. Avoid contact with

the skin and the eyes.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store between 5 and 25 °C in a dry, well ventilated place away from sources of heat, ignition

and direct sunlight. Store in original container.

Storage class (TRGS 510) : 3, Flammable liquids

7.3 Specific end use(s)

Specific use(s) : Please follow the technical information.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis	
naphtha (petrole- um), hydrotreated heavy	64742-48-9	AGW	1.500 mg/m3	DE TRGS 900	
Peak-limit: excursion factor (category)	2;(II)				
Further information	Group exposure limit for hydrocarbon solvent mixtures, Commission for dangerous substances, See also No. 2.9 of the TRGS 900				
		AGW	600 mg/m3	DE TRGS 900	
Peak-limit: excursion factor (category)	2;(II)				
Further information	Group exposure limit for hydrocarbon solvent mixtures, Commission for dangerous substances, See also No. 2.9 of the TRGS 900				
naphtha (petrole-	64742-48-9	AGW	1.500 mg/m3	DE TRGS	

according to Regulation (EC) No. 1907/2006

Capadur F7-LangzeitLasur Eiche

Version Revision Date: Print Date Date of last issue: -

1.0 25.01.2019 26.01.2019 Date of first issue: 25.01.2019

um), hydrotreated heavy				900	
Peak-limit: excursion factor (category)	2;(II)				
Further information	Group exposure limit for hydrocarbon solvent mixtures, Commission for dangerous substances, See also No. 2.9 of the TRGS 900				
		AGW	600 mg/m3	DE TRGS 900	
Peak-limit: excursion factor (category)	2;(II)				
Further information	Group exposure limit for hydrocarbon solvent mixtures, Commission for dangerous substances, See also No. 2.9 of the TRGS 900				
silicon dioxide	7631-86-9	AGW (Inhalable fraction)	4 mg/m3 (Silica)	DE TRGS 900	
Further information	Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission)., Colloidal amorphous silica, including pyrogenic silica and in wet processes manufactured silica (precipitated silica, silicagel)., When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child				

8.2 Exposure controls

Personal protective equipment

Eye protection : German trade association rules - BGR 192 Eye protection

Safety glasses

Hand protection

Material : Nitrile rubber Glove thickness : 0,2 mm Protective index : Class 3

Remarks : Wear suitable gloves tested to EN374. Before removing

gloves clean them with soap and water. Gloves should be discarded and replaced if there is any indication of degrada-

tion or chemical breakthrough.

German trade association leaflet: Carry gloves (ZH 1/706)

Skin and body protection : Long sleeved clothing

Safety shoes

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Skin should be washed after contact.

During spray application: impervious clothing

Respiratory protection : Roller application or brushing: This product should not be

used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to

standard EN 14387) is used.

according to Regulation (EC) No. 1907/2006

Capadur F7-LangzeitLasur Eiche

Version Revision Date: Print Date Date of last issue: -

1.0 25.01.2019 26.01.2019 Date of first issue: 25.01.2019

German trade association rules - BGR 190 Breathing protec-

tion

During spray application: Do not breathe spray dust. Use

A2/P2 combination filter for paint spraying.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : No data available

Odour : No data available

Odour Threshold : Not relevant

pH : not determined

Melting point/freezing point : not determined

Boiling point/boiling range : not determined

Flash point : 48 °C

Evaporation rate : Not applicable

Flammability (solid, gas) : Sustains combustion

Upper explosion limit / Upper

flammability limit

not determined

Lower explosion limit / Lower

flammability limit

not determined

Vapour pressure : not determined

Relative vapour density : not determined

Relative density : not determined

Density : 0,9600 g/cm3

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

: not determined

Auto-ignition temperature : not determined

Decomposition temperature : Not applicable

Viscosity

according to Regulation (EC) No. 1907/2006

Capadur F7-LangzeitLasur Eiche

Version Revision Date: Print Date Date of last issue: -

1.0 25.01.2019 26.01.2019 Date of first issue: 25.01.2019

Viscosity, dynamic : No data available

Viscosity, kinematic : > 20,5 mm2/s (40 °C)

Flow time : > 60 s at 23 °C

Cross section: 6 mm Method: ISO 2431

Explosive properties : Not applicable

Oxidizing properties : Not applicable

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Hazardous decomposition products formed under fire condi-

tions

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Protect from frost, heat and sunlight.

10.5 Incompatible materials

Materials to avoid : Incompatible with oxidizing agents.

Incompatible with acids and bases.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product:

Acute oral toxicity : Remarks: Based on available data, the classification criteria

are not met.

Acute inhalation toxicity : Remarks: Based on available data, the classification criteria

are not met.

Acute dermal toxicity : Remarks: Based on available data, the classification criteria

according to Regulation (EC) No. 1907/2006

Capadur F7-LangzeitLasur Eiche

Version Revision Date: Print Date Date of last issue: -

1.0 25.01.2019 26.01.2019 Date of first issue: 25.01.2019

are not met.

Components:

2-methyl-2H-isothiazol-3-one:

Acute oral toxicity : LD50 (Rat): 120 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0,145 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Remarks: see user defined free text

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg

silicon dioxide:

Acute oral toxicity : LD50 Oral (Rat): 10.000 mg/kg

Skin corrosion/irritation

Product:

Remarks : May cause skin irritation in susceptible persons.

Serious eye damage/eye irritation

Product:

Remarks : According to the classification criteria of the European Union,

the product is not considered as being an eye irritant.

Respiratory or skin sensitisation

Product:

Remarks : Repeated contact may cause allergic reactions in very sus-

ceptible persons.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other :

aquatic invertebrates

Remarks: No data available

Components:

2-methyl-2H-isothiazol-3-one:

M-Factor (Acute aquatic tox- :

icity)

10

M-Factor (Chronic aquatic :

9/14

according to Regulation (EC) No. 1907/2006

Capadur F7-LangzeitLasur Eiche

Version Revision Date: Print Date Date of last issue: -

1.0 25.01.2019 26.01.2019 Date of first issue: 25.01.2019

toxicity)

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

12.6 Other adverse effects

Product:

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : .

Waste should not be disposed of via wastewater.

Contaminated packaging : Only completely emptied containers should be given for recy-

cling.

Waste Code : used product

080112, waste paint and varnish other than those mentioned

in 08 01 11*

SECTION 14: Transport information

14.1 UN number

ADN : UN 1263
ADR : UN 1263
RID : UN 1263
IMDG : UN 1263
IATA : UN 1263

14.2 UN proper shipping name

according to Regulation (EC) No. 1907/2006

Capadur F7-LangzeitLasur Eiche

Version Revision Date: Print Date Date of last issue: -

1.0 25.01.2019 26.01.2019 Date of first issue: 25.01.2019

ADN : PAINT
ADR : PAINT
RID : PAINT
IMDG : PAINT
IATA : Paint

14.3 Transport hazard class(es)

 ADN
 : 3

 ADR
 : 3

 RID
 : 3

 IMDG
 : 3

 IATA
 : 3

14.4 Packing group

ADN

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

ADR

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : (D/E)

RID

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

IMDG

Packing group : III
Labels : 3
EmS Code : F-E, <u>S-E</u>

IATA (Cargo)

Packing instruction (cargo : 366

aircraft)

Packing instruction (LQ) : Y344
Packing group : III

Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passen- : 355

ger aircraft)

Packing instruction (LQ) : Y344
Packing group : III

Labels : Flammable Liquids

14.5 Environmental hazards

according to Regulation (EC) No. 1907/2006

Capadur F7-LangzeitLasur Eiche

Version Revision Date: Print Date Date of last issue: -

1.0 25.01.2019 26.01.2019 Date of first issue: 25.01.2019

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

Remarks : ADR: Packages smaller than or equal to 450 litres, not

goods/merchandise of Class 3

see sections 6-8

IMDG: Packages smaller than or equal to 30 litres, not

None

goods/merchandise of Class 3

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).

This product is a mixture and does not contain Substances of Very High Concern (SVHC) equal or above 0.1%. Therefore no advised uses have to be defined and no chemical safety assessment has to be generated.

REACH - List of substances subject to authorisation

(Annex XIV)

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P5c FLAMMABLE LIQUIDS

34 Petroleum products: (a)

gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar

according to Regulation (EC) No. 1907/2006

Capadur F7-LangzeitLasur Eiche

Version Revision Date: Print Date Date of last issue: -

1.0 25.01.2019 26.01.2019 Date of first issue: 25.01.2019

properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)

Water contaminating class

(Germany)

1 slightly water endangering

Classification according to AwSV, Annex 1 (5.2)

Product code for laquers and

paints / Giscode

: M-KH02 Solvent-based varnishes/wood glaze, aromatics re-

moved

. : BSL40 Coating materials, strongly solvent-based, aromatic-

free, classified

Volatile organic compounds : Directive 2004/42/EC

< 40 % < 390 g/l

Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

SECTION 16: Other information

Full text of H-Statements

EUH066 : Repeated exposure may cause skin dryness or cracking.

H226 : Flammable liquid and vapour.

H301 : Toxic if swallowed.

H304 : May be fatal if swallowed and enters airways.

H311 : Toxic in contact with skin.

H314 : Causes severe skin burns and eye damage.
H317 : May cause an allergic skin reaction.

H318 : Causes serious eye damage.

H330 : Fatal if inhaled.

H336 : May cause drowsiness or dizziness.

H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard

Asp. Tox. : Aspiration hazard

Eye Dam. : Serious eye damage

Flam. Liq. : Flammable liquids

Skin Corr. : Skin corrosion

Skin Sens. : Skin sensitisation

STOT SE : Specific target organ toxicity - single exposure

DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.

DE TRGS 900 / AGW : Time Weighted Average

according to Regulation (EC) No. 1907/2006

Capadur F7-LangzeitLasur Eiche

Version Revision Date: Print Date Date of last issue: -

1.0 25.01.2019 26.01.2019 Date of first issue: 25.01.2019

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; EIx - Loading rate associated with x% response; EMS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances;

Further information

Classification of the mixture:

Classification procedure:

Flam. Liq. 3 H226

Based on product data or assessment

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

REACH Information

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our upstream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly. This will be put into practice depending on the register-deadline of the substances involved during the transition period from December 1, 2010 till May 31, 2018.

DE / EN