according to Regulation (EC) No. 1907/2006

CAPAROL

DE / EN

Capalac mix Venti Basis Weiß

Version Revision Date: SDS Number: Date of last issue: 17.12.2020 3.0 14.03.2023 6005691 Date of first issue: 10.12.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Capalac mix Venti Basis Weiß

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Solvent-borne coatings

stance/Mixture

Recommended restrictions

on use

: within adequate application - none

1.3 Details of the supplier of the safety data sheet

Company : Caparol Farben Lacke GmbH

Roßdörfer Straße 50 64372 Ober-Ramstadt

Telephone : +496154710

Telefax : +4961547170222

Website

E-mail address Responsi-

ble/issuing person

: msds@dr-rmi.com

1.4 Emergency telephone

Emergency telephone 1 : +49613284463 GBK GmbH

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 H226: Flammable liquid and vapor.

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008)

Hazard pictograms

Signal Word : Warning

according to Regulation (EC) No. 1907/2006

DE / EN



Capalac mix Venti Basis Weiß

Version Revision Date: SDS Number: Date of last issue: 17.12.2020 3.0 14.03.2023 6005691 Date of first issue: 10.12.2019

Hazard Statements : H226 Flammable liquid and vapor.

Precautionary Statements : P101 If medical advice is needed, have product container or

label at hand.

P102 Keep out of reach of children.

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open

flames and other ignition sources. No smoking. P271 Use only outdoors or in a well-ventilated area.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immedi-

ately all contaminated clothing. Rinse skin with water.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Additional Labeling

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not

breathe spray or mist.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤	13463-67-7 236-675-5 022-006-00-2	Carc. 2; H351	>= 20 - < 30

according to Regulation (EC) No. 1907/2006

CAPAROL

DE / EN

Capalac mix Venti Basis Weiß

Version Revision Date: SDS Number: Date of last issue: 17.12.2020 3.0 14.03.2023 6005691 Date of first issue: 10.12.2019

10 μm]	01-2119489379-17			
Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha	64742-48-9 265-150-3 649-327-00-6 01-2119457273-39, 01-2119463258-33, 01-2119486659-16	Asp. Tox. 1; H304 EUH066	>= 10 - < 20	
Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha	64742-48-9 265-150-3 649-327-00-6 01-2119457273-39, 01-2119463258-33	Flam. Liq. 3; H226 STOT SE 3; H336 Asp. Tox. 1; H304 EUH066	>= 1 - < 10	
2-dimethylaminoethanol	108-01-0 203-542-8 603-047-00-0 01-2119492298-24	Flam. Liq. 3; H226 Acute Tox. 4; H302 Acute Tox. 3; H331 Acute Tox. 4; H312 Skin Corr. 1B; H314 STOT SE 3; H335 (Respiratory system) specific concentration limit STOT SE 3; H335 >= 5 %	>= 0,1 - < 1	
propylidynetrimethanol	77-99-6 201-074-9 01-2119486799-10	Repr. 2; H361fd	>= 0,1 - < 1	
Substances with a workplace exposure limit :				
Silica gel, pptd., crystfree	112926-00-8 231-545-4 01-2119379499-16, 01-2120105300-82		>= 1 - < 10	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice : Never give anything by mouth to an unconscious person.

If you feel unwell, seek medical advice (show the label where

possible).

Move out of dangerous area. First aider needs to protect himself.

If inhaled : If symptoms persist, call a physician.

Move to fresh air.

according to Regulation (EC) No. 1907/2006

DE / EN



Capalac mix Venti Basis Weiß

Version Revision Date: SDS Number: Date of last issue: 17.12.2020 14.03.2023 6005691 Date of first issue: 10.12.2019 3.0

In case of skin contact Do NOT use solvents or thinners.

In case of contact, immediately flush skin with soap and plenty

of water.

Take off all contaminated clothing immediately.

In case of eye contact If eye irritation persists: Get medical advice/ attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing.

If swallowed Seek medical advice.

Clean mouth with water and drink afterwards plenty of water.

If swallowed, DO NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Use water spray, alcohol-resistant foam, dry chemical or car-

bon dioxide.

Do not use a solid water stream as it may scatter and spread

fire.

Unsuitable extinguishing

media

None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire

fighting

Cool closed containers exposed to fire with water spray. In case of fire hazardous decomposition products may be

produced such as:

Carbon monoxide, carbon dioxide and unburned hydrocar-

bons (smoke).

5.3 Advice for firefighters

for fire-fighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information Standard procedure for chemical fires.

In the event of fire and/or explosion do not breathe fumes.

according to Regulation (EC) No. 1907/2006



DE / EN

Capalac mix Venti Basis Weiß

Version Revision Date: SDS Number: Date of last issue: 17.12.2020 14.03.2023 6005691 Date of first issue: 10.12.2019 3.0

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions Do not get in eyes, on skin, or on clothing.

> Ensure adequate ventilation. Remove all sources of ignition.

6.2 Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Do not flush into surface water or sanitary sewer system.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up Keep in suitable, closed containers for disposal.

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

6.4 Reference to other sections

For further information see Section 7 of the safety data sheet.

, For personal protection see section 8., For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling Non-sparking tools should be used.

For personal protection see section 8.

Avoid exceeding the given occupational exposure limits (see

section 8).

Provide sufficient air exchange and/or exhaust in work rooms.

In addition, the current technical information for this product and its application on www.caparol.com must be observed.

Advice on protection against

fire and explosion

Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking.

Hygiene measures Avoid contact with the skin and the eyes. Wash hands before

> eating, drinking, or smoking. Do not eat, drink or smoke when using this product. Remove contaminated clothing and protec-

tive equipment before entering eating areas.

according to Regulation (EC) No. 1907/2006



DE / EN

Capalac mix Venti Basis Weiß

Version Revision Date: SDS Number: Date of last issue: 17.12.2020 3.0 14.03.2023 6005691 Date of first issue: 10.12.2019

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Store in original container. Store between 41 and 77 °F in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Storage class (TRGS 510) : 3

7.3 Specific end use(s)

Specific use(s) : This information is not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form	Control parameters	Basis
•		of exposure)	•	
titanium dioxide; [in powder form con-	13463-67-7	AGW (Inhalable fraction)	10 mg/m3 (Titanium dioxide)	DE TRGS 900
taining 1 % or				
more of particles with aerodynamic				
diameter ≤ 10 µm]				
	Peak-limit cat	egory: 2;(II)		
		<u> </u>	compliance with the OEL ar	nd biological
	tolerance valu	ies, there is no risk o	of harming the unborn child	
		AGW (Alveolate	1,25 mg/m3	DE TRGS
		fraction)	(Titanium dioxide)	900
	Peak-limit category: 2;(II)			
	Further information: When there is compliance with the OEL and biological			
	tolerance values, there is no risk of harming the unborn child			
		BM (Alveolar	0,5 mg/m3	DE TRGS
		dust fraction)		527
Naphtha (petrole- um), hydrotreated heavy; Low boiling point ydrogen treated naphtha	64742-48-9	AGW	300 mg/m3	DE TRGS 900
	Peak-limit category: 2;(II)			
	Further information: Group exposure limit for hydrocarbon solvent mixtures			
Naphtha (petrole- um), hydrotreated heavy; Low boiling point ydrogen treated naphtha	64742-48-9	AGW	300 mg/m3	DE TRGS 900
	Peak-limit category: 2;(II)			

according to Regulation (EC) No. 1907/2006



DE / EN

Capalac mix Venti Basis Weiß

Version Revision Date: SDS Number: Date of last issue: 17.12.2020 3.0 14.03.2023 6005691 Date of first issue: 10.12.2019

	Further inform	Further information: Group exposure limit for hydrocarbon solvent mixtures			
Silica gel, pptd.,	112926-00-	AGW (Inhalable	4 mg/m3	DE TRGS	
crystfree	8	fraction)	(Silica)	900	
	Further information: When there is compliance with the OEL and biological				
	tolerance values, there is no risk of harming the unborn child				

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Routes of expo- sure	Potential health effects	Value
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm]	Consumers	Ingestion	Long-term systemic effects	700,00 mg/kg bw/day
	Workers	Inhalation	Long-term local ef- fects	10,00 mg/m3
2- dimethylaminoethanol	Workers	Inhalation	Acute systemic effects	22,00 mg/m3
	Workers	Inhalation	Acute local effects	22,00 mg/m3
	Workers	Inhalation	Long-term systemic effects	7,40 mg/m3
	Workers	Inhalation	Long-term local ef- fects	7,40 mg/m3
	Workers	Skin contact	Acute systemic effects	5,00 mg/kg bw/day
	Workers	Skin contact	Acute local effects	80,00 µg/cm2
	Workers	Skin contact	Long-term systemic effects	1,04 mg/kg bw/day
propylidynetrimetha- nol	Consumers	Skin contact	Acute systemic effects	83,30 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	1,68 mg/kg bw/day
	Consumers	Inhalation	Acute systemic effects	925,00 mg/m3
	Consumers	Ingestion	Acute systemic effects	50,00 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	5,03 mg/m3
	Consumers	Skin contact	Long-term systemic effects	1,68 mg/kg bw/day
	Workers	Inhalation	Acute systemic ef- fects	3037,30 mg/m3
	Workers	Inhalation	Long-term systemic effects	19,54 mg/m3
	Workers	Skin contact	Acute systemic ef- fects	138,80 mg/kg bw/day
	Workers	Skin contact	Long-term systemic effects	2,79 mg/kg bw/day

according to Regulation (EC) No. 1907/2006

CAPAROL

DE / EN

Capalac mix Venti Basis Weiß

Version Revision Date: SDS Number: Date of last issue: 17.12.2020 3.0 14.03.2023 6005691 Date of first issue: 10.12.2019

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
titanium dioxide; [in powder form	Sewage treatment plant	100 mg/l
containing 1 % or more of parti-		
cles with aerodynamic diameter ≤		
10 μm]		
	Fresh water	0,184 mg/l
	Soil	100 mg/kg dry
		weight (d.w.)
	Sea water	0,0184 mg/l
	Fresh water sediment	1000 mg/kg dry
		weight (d.w.)
	Sea sediment	100 mg/kg dry
		weight (d.w.)
	Intermittent use/release	0,193 mg/l
2-dimethylaminoethanol	Sewage treatment plant	10 mg/l
	Sea water	0,00661 mg/l
	Fresh water sediment	0,0529 mg/kg dry
		weight (d.w.)
	Intermittent use/release	0,0661 mg/l
	Soil	0,0177 mg/kg dry
		weight (d.w.)
	Fresh water	0,0661 mg/l
propylidynetrimethanol	Fresh water	1 mg/l
	Sewage treatment plant	100 mg/l
	Sea sediment	0,351 mg/kg dry
		weight (d.w.)
	Sea water	0,1 mg/l
	Soil	0,241 mg/kg dry
		weight (d.w.)
	Fresh water sediment	3,505 mg/kg dry
		weight (d.w.)
	Intermittent use/release	10 mg/l

8.2 Exposure controls

Personal protective equipment

Eye/face protection : DGUV Regulation 112-192 - Use of eye and face protection

Goggles

Hand protection

Material : Nitrile rubber Glove thickness : 0,2 mm Protective index : Class 3

Remarks : Gloves should be discarded and replaced if there is any indi-

cation of degradation or chemical breakthrough. Before re-

according to Regulation (EC) No. 1907/2006

DE / EN



Capalac mix Venti Basis Weiß

Version Revision Date: SDS Number: Date of last issue: 17.12.2020 3.0 14.03.2023 6005691 Date of first issue: 10.12.2019

moving gloves clean them with soap and water. Wear suita-

ble gloves tested to EN374.

DGUV Regulation 112-195 - Use of protective gloves

Skin and body protection : Safety shoes

Long sleeved clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Skin should be washed after contact.

During spray application: impervious clothing

Respiratory protection : No personal respiratory protective equipment normally re-

quired.

DGUV Regulation 112-190 - Use of breathing equipment

During spray application: Do not breathe spray dust. Use

A2/P2 combination filter for paint spraying.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid

Color : white

Odor : No data available

Odor Threshold : Not relevant

Melting point/freezing point : not determined

Boiling point/boiling range : not determined

Upper explosion limit / Upper

flammability limit

not determined

Lower explosion limit / Lower

flammability limit

not determined

Flash point : 52 °C

Autoignition temperature : not determined

Decomposition temperature : Not applicable

according to Regulation (EC) No. 1907/2006

CAPAROL

DE / EN

Capalac mix Venti Basis Weiß

Version Revision Date: SDS Number: Date of last issue: 17.12.2020 3.0 14.03.2023 6005691 Date of first issue: 10.12.2019

pH : 6,95

Concentration: 10 %

Viscosity

Viscosity, dynamic : 1,000 mPa.s (20 °C)

Viscosity, kinematic : > 20,5 mm2/s (40 °C)

Solubility(ies)

Water solubility : partly miscible

Partition coefficient: n-

octanol/water

: not determined

Vapor pressure : not determined

Relative density : not determined

Density : 1,4400 g/cm3

Relative vapor density : Heavier than air.

9.2 Other information

Explosives : Not applicable

Oxidizing properties : Not applicable

Flammability (liquids) : Sustains combustion

Evaporation rate : Not applicable

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Vapors may form explosive mixture with air.

Hazardous decomposition products formed under fire condi-

tions.

10.4 Conditions to avoid

Conditions to avoid : Protect from frost, heat and sunlight.

according to Regulation (EC) No. 1907/2006

CAPAROL

DE / EN

Capalac mix Venti Basis Weiß

Version Revision Date: SDS Number: Date of last issue: 17.12.2020 3.0 14.03.2023 6005691 Date of first issue: 10.12.2019

10.5 Incompatible materials

Materials to avoid : Incompatible with acids and bases.

Incompatible with oxidizing agents.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Product:

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l

Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Components:

2-dimethylaminoethanol:

Acute oral toxicity : LD50 (Rat): 1.183 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 6,1 mg/l

Exposure time: 4 h
Test atmosphere: vapor

Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): 1.219 mg/kg

Method: OECD Test Guideline 402

Silica gel, pptd., cryst.-free:

Acute oral toxicity : LD50 Oral (Rat): > 10.000 mg/kg

Acute dermal toxicity : LD50 (Rat): > 5.000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Components:

2-dimethylaminoethanol:

according to Regulation (EC) No. 1907/2006

CAPAROL

DE / EN

Capalac mix Venti Basis Weiß

Version Revision Date: SDS Number: Date of last issue: 17.12.2020 3.0 14.03.2023 6005691 Date of first issue: 10.12.2019

Species : Rabbit Assessment : Corrosive

Method : OECD Test Guideline 404

Result : Corrosive

Serious eye damage/eye irritation

Not classified based on available information.

Components:

2-dimethylaminoethanol:

Species : Rabbit

Assessment : Risk of serious damage to eyes.

Method : OECD Test Guideline 405

Result : Irreversible effects on the eye

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:

2-dimethylaminoethanol:

Test Type : Buehler Test Routes of exposure : Dermal Species : Guinea pig

Assessment : Does not cause skin sensitization.

Method : OECD Test Guideline 406

Result : Does not cause skin sensitization.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

Components:

2-dimethylaminoethanol:

Routes of exposure : Inhalation

according to Regulation (EC) No. 1907/2006



DE / EN

Capalac mix Venti Basis Weiß

Version Revision Date: SDS Number: Date of last issue: 17.12.2020 3.0 14.03.2023 6005691 Date of first issue: 10.12.2019

Target Organs : Upper respiratory tract

Assessment : May cause respiratory irritation.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

according to Regulation (EC) No. 1907/2006

DE / EN



Capalac mix Venti Basis Weiß

Version Revision Date: SDS Number: Date of last issue: 17.12.2020 3.0 14.03.2023 6005691 Date of first issue: 10.12.2019

levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product :

Waste should not be disposed of via wastewater.

Contaminated packaging : Only completely emptied containers should be given for recy-

cling.

Waste Code : used product

080112, waste paint and varnish other than those mentioned

in 08 01 11*

SECTION 14: Transport information

14.1 UN number or ID number

ADN : UN 1263
ADR : UN 1263
RID : UN 1263
IMDG : UN 1263
IATA : UN 1263

14.2 UN proper shipping name

ADN : PAINT
ADR : PAINT
RID : PAINT
IMDG : PAINT
IATA : Paint

14.3 Transport hazard class(es)

Class Subsidiary risks

according to Regulation (EC) No. 1907/2006

CAPAROL

DE / EN

Capalac mix Venti Basis Weiß

Version Revision Date: SDS Number: Date of last issue: 17.12.2020 3.0 14.03.2023 6005691 Date of first issue: 10.12.2019

ADN : 3
ADR : 3
RID : 3
IMDG : 3
IATA : 3

14.4 Packing group

ADN

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

ADR

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : (D/E)

RID

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

IMDG

Packing group : III
Labels : 3
EmS Code : F-E, <u>S-E</u>

IATA (Cargo)

Packing instruction (cargo : 366

aircraft)

Packing instruction (LQ) : Y344
Packing group : III

Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passen: 355

ger aircraft)

Packing instruction (LQ) : Y344
Packing group : III

Labels : Flammable Liquids

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

according to Regulation (EC) No. 1907/2006

DE / EN



Capalac mix Venti Basis Weiß

Version Revision Date: SDS Number: Date of last issue: 17.12.2020 14.03.2023 6005691 Date of first issue: 10.12.2019 3.0

Environmentally hazardous no

Environmentally hazardous no

IMDG

Marine pollutant no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)

Conditions of restriction for the following entries should be considered: Number on list 3

REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59).

This product is a mixture and does not contain Substances of Very High Concern (SVHC) equal or above 0.1%. Therefore no advised uses have to be defined and no chemical safety assessment has to be generated.

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Not applicable

REACH - List of substances subject to authorisation

(Annex XIV)

None

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

FLAMMABLE LIQUIDS

34 Petroleum products: (a) gasolines and naphthas, (b) kerosenes

P5c

according to Regulation (EC) No. 1907/2006

DE / EN



Capalac mix Venti Basis Weiß

Version Revision Date: SDS Number: Date of last issue: 17.12.2020 3.0 14.03.2023 6005691 Date of first issue: 10.12.2019

(including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a)

to (d)

Water hazard class (Germa-

ny)

WGK 1 slightly water endangering

Classification according to AwSV, Annex 1 (5.2)

: BSL20 Coating materials, solvent-based, aromatic-free, clas-

sified

Volatile organic compounds : Directive 2004/42/EC

< 21 % < 300 g/l

Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

15.2 Chemical Safety Assessment

A Chemical Safety Assessment is not required for this mixture.

SECTION 16: Other information

Full text of H-Statements

H226 : Flammable liquid and vapor.

H302 : Harmful if swallowed.

H304 : May be fatal if swallowed and enters airways.

H312 : Harmful in contact with skin.

H314 : Causes severe skin burns and eye damage.

H331 : Toxic if inhaled.

H335 : May cause respiratory irritation.
H336 : May cause drowsiness or dizziness.
H351 : Suspected of causing cancer if inhaled.

H361fd : Suspected of damaging fertility. Suspected of damaging the

unborn child.

EUH066 : Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

Acute Tox. : Acute toxicity

according to Regulation (EC) No. 1907/2006

DE / EN



Capalac mix Venti Basis Weiß

Version Revision Date: SDS Number: Date of last issue: 17.12.2020 3.0 14.03.2023 6005691 Date of first issue: 10.12.2019

Asp. Tox. : Aspiration hazard
Carc. : Carcinogenicity
Flam. Liq. : Flammable liquids
Repr. : Reproductive toxicity
Skin Corr. : Skin corrosion

STOT SE : Specific target organ toxicity - single exposure
DE TRGS 527 : Germany. TRGS 527 - Activities with nanomaterials
DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.

DE TRGS 527 / BM : Assessment scale
DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AlIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELX - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; CDCD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persi

Further information

Other information:

No exposure scenario communication is required for this product according to REACH Regulation No. 1907/2006 EC.

Communication of Uses is not required in accordance with REACH Article 31(1)(a) - registered substances / mixtures do not meet the criteria for classification as hazardous in accordance with Regulations 1272/2008 EC or 1999/45/EC.

Sources of key data used to compile the Material Safety Data Sheet:

ECHA WebSite

ACGIH (American Conference of Government Industrial Hygienists). 2014 TLVs and BEIs. Threshold Limit Values (TLVs) for chemical substances and physical agents and Biological Exposure Indices (BEIs) with Seventh Edition documentation. 2014 ACGIH, Cincinnati OH

NIOSH - Registry of toxic effects of chemical substances

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX'S - Dangerous properties of industrial materials

GESTIS - Database on hazardous substances - Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA, Institute for Occupational Safety and Health of the German Social Accident Insurance)

Toxnet - Toxicology Data Network

Classification of the mixture:

Classification procedure:

according to Regulation (EC) No. 1907/2006

DE / EN



Capalac mix Venti Basis Weiß

Version Revision Date: SDS Number: Date of last issue: 17.12.2020 3.0 14.03.2023 6005691 Date of first issue: 10.12.2019

Flam. Liq. 3 H226 Based on product data or assessment

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

REACH Information

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our upstream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly.

DE / EN