according to Regulation (EC) No. 1907/2006



# CaparolColor Vollton- und Abtönfarbe

Version Revision Date: Print Date Date of last issue: 18.11.2019 2.1 30.01.2021 Date of first issue: 30.01.2021

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : CaparolColor Vollton- und Abtönfarbe

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Water-borne coatings

stance/Mixture

Recommended restrictions

on use

: within adequate application - none

1.3 Details of the supplier of the safety data sheet

Company : Caparol Farben Lacke GmbH

Roßdörfer Straße 50 64372 Ober-Ramstadt

Telephone : +496154710
Telefax : +4961547170222
E-mail address Responsi- : msds@dr-rmi.com

ble/issuing person

1.4 Emergency telephone number

Emergency telephone num: +49613284463 GBK GmbH

ber 1

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

#### Classification (REGULATION (EC) No 1272/2008)

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

#### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



Signal word : Warning

Hazard statements : H317 May cause an allergic skin reaction.

according to Regulation (EC) No. 1907/2006



# CaparolColor Vollton- und Abtönfarbe

Version Revision Date: Print Date Date of last issue: 18.11.2019 2.1 30.01.2021 Date of first issue: 30.01.2021

Precautionary statements : P101 If medical advice is needed, have product container or

label at hand.

P102 Keep out of reach of children.

**Prevention:** 

P262 Do not get in eyes, on skin, or on clothing. P280 Wear protective gloves/ eye protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and

water.

#### Hazardous components which must be listed on the label:

1,2-benzisothiazol-3(2H)-one

2-methylisothiazol-3(2H)-one

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

Chemical nature : Emulsion paint, aqueous

Components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Index-No.		
	Registration number		
titanium dioxide	13463-67-7	Carc. 2; H351	>= 0,1 - < 1
	236-675-5		
	022-006-00-2		
	01-2119489379-17		
1,2-benzisothiazol-3(2H)-one	2634-33-5	Acute Tox. 4; H302	>= 0,0025 - <
	220-120-9	Skin Irrit. 2; H315	0,025
	613-088-00-6	Eye Dam. 1; H318	
	01-2120761540-60	Skin Sens. 1; H317	
		Aquatic Acute 1;	
		H400	
		Aquatic Chronic 2;	
		H411	

according to Regulation (EC) No. 1907/2006



# CaparolColor Vollton- und Abtönfarbe

VersionRevision Date:Print DateDate of last issue: 18.11.20192.130.01.202102.02.2021Date of first issue: 30.01.2021

	•		
		Acute Tox. 2; H330	
		M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	
2-methylisothiazol-3(2H)-one	2682-20-4 220-239-6 613-326-00-9 01-2120764690-50	Acute Tox. 2; H330 Acute Tox. 3; H311 Acute Tox. 3; H301 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 0,0025 - < 0,025
		M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 1	
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	55965-84-9 613-167-00-5 01-2120764691-48	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 2; H310 Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 0,0002 - < 0,0015
		M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100	
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	55965-84-9 613-167-00-5 01-2120764691-48	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 2; H310 Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 0,0002 - < 0,0015
		M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic	

according to Regulation (EC) No. 1907/2006



# CaparolColor Vollton- und Abtönfarbe

Version Revision Date: Print Date Date of last issue: 18.11.2019 2.1 30.01.2021 Date of first issue: 30.01.2021

		aquatic toxicity): 100		
Substances with a workplace exp	Substances with a workplace exposure limit :			
barium sulfate	7727-43-7		>= 1 - < 10	
	231-784-4			
	01-2119491274-35			
kaolin	1332-58-7		>= 1 - < 10	
	310-194-1			
chromium (III) oxide	1308-38-9		>= 1 - < 10	
, ,	215-160-9			
	01-2119433951-39			
manganese ferrite black spinel	68186-94-7		>= 1 - < 10	
	269-056-3			
	01-2119457599-19			

For explanation of abbreviations see section 16.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

General advice : Never give anything by mouth to an unconscious person.

If you feel unwell, seek medical advice (show the label where

possible).

Move out of dangerous area. First aider needs to protect himself.

If inhaled : Move to fresh air.

In case of skin contact : Do NOT use solvents or thinners.

In case of contact, immediately flush skin with soap and plenty

of water.

In case of eye contact : If eye irritation persists: Get medical advice/ attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing.

If swallowed : Seek medical advice.

Clean mouth with water and drink afterwards plenty of water.

If swallowed, DO NOT induce vomiting.

#### 4.2 Most important symptoms and effects, both acute and delayed

None known.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No information available.

according to Regulation (EC) No. 1907/2006



# CaparolColor Vollton- und Abtönfarbe

Version Revision Date: Print Date Date of last issue: 18.11.2019 2.1 30.01.2021 Date of first issue: 30.01.2021

#### **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or car-

bon dioxide.

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Unsuitable extinguishing

media

None known.

#### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

In case of fire hazardous decomposition products may be

produced such as:

Carbon monoxide, carbon dioxide and unburned hydrocar-

bons (smoke).

#### 5.3 Advice for firefighters

Special protective equipment:

for firefighters

Wear self-contained breathing apparatus for firefighting if nec-

essary.

Further information : Standard procedure for chemical fires.

The product itself does not burn.

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use protective shoes or boots with rough rubber sole.

Material can create slippery conditions. Do not get in eyes, on skin, or on clothing.

#### 6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Do not flush into surface water or sanitary sewer system.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Keep in suitable, closed containers for disposal.

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

according to Regulation (EC) No. 1907/2006



## CaparolColor Vollton- und Abtönfarbe

Version Revision Date: Print Date Date of last issue: 18.11.2019 2.1 30.01.2021 Date of first issue: 30.01.2021

#### 6.4 Reference to other sections

For further information see Section 7 of the safety data sheet.

,For personal protection see section 8.,For disposal considerations see section 13.

#### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Advice on safe handling : For personal protection see section 8.

No special technical protective measures required.

In addition, the current technical information for this product and its application on www.caparol.com must be observed.

Hygiene measures : Wash hands before eating, drinking, or smoking. Do not eat,

drink or smoke when using this product.

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Perishable if frozen. To maintain product quality, do not store in heat or direct sunlight. Store at room temperature in the original container. Containers which are opened must be care-

fully resealed and kept upright to prevent leakage.

Advice on common storage : Keep away from oxidizing agents and strongly acid or alkaline

materials.

Storage class (TRGS 510) : 12, Non Combustible Liquids

7.3 Specific end use(s)

Specific use(s) : This information is not available.

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

#### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form	Control parameters	Basis
		of exposure)		
barium sulfate	7727-43-7	AGW (Inhalable	10 mg/m3	DE TRGS
		fraction)	_	900
	Peak-limit: excursion factor (category): 2;(II)			
	Further information: Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission)., Commission for dangerous substances, General dust value. For this substance no specific			
	occupational exposure limit value is established, since the AGS does not yet have information regarding unspecific action on the respiratory organs in ex-			

according to Regulation (EC) No. 1907/2006



# CaparolColor Vollton- und Abtönfarbe

VersionRevision Date:Print DateDate of last issue: 18.11.20192.130.01.202102.02.2021Date of first issue: 30.01.2021

	cess of the no	rmal values.				
		AGW (Alveolate fraction)	1,25 mg/m3	DE TRGS 900		
	Peak-limit: ex	cursion factor (categ	orv): 2:(II)			
			nission for the review of com	pounds at the		
	work place da dangerous su occupational	ingerous for the heal bstances, General d exposure limit value ion regarding unspe	th (MAK-commission)., Comust value. For this substance is established, since the AG cific action on the respiratory	nmission for e no specific S does not yet		
kaolin	1332-58-7	TWA (Respirable dust)	0,1 mg/m3	2004/37/EC		
	Further inform	ation: Carcinogens	or mutagens			
chromium (III) ox-	1308-38-9	AGW (Inhalable	2 mg/m3	DE TRGS		
ide		fraction)	(chromium)	900		
	Peak-limit: ex	cursion factor (categ	ory): 1:(I)	•		
			I value is based on the elem-	ent content of		
	the correspon		an Union (The EU has estab			
		TWA	2 mg/m3	2006/15/EC		
			(chromium)			
	Further inform	nation: Indicative	,			
manganese ferrite	68186-94-7	AGW (Inhalable	0,2 mg/m3	DE TRGS		
black spinel		fraction)	(Manganese)	900		
Peak-limit: excursion factor (category): 8;(II)						
	Further information: When there is compliance with the OEL and biological					
	tolerance values, there is no risk of harming the unborn child, The threshold					
			ntent of the corresponding m			
	commission for the review of compounds at the work place dangerous for the					
	health (MAK-	commission).	•	-		
	,	AGW (Alveolate	0,02 mg/m3	DE TRGS		
		fraction)	(Manganese)	900		
	Peak-limit: ex	cursion factor (categ		•		
			s compliance with the OEL a	nd biological		
	tolerance values, there is no risk of harming the unborn child, The threshold					
	value is based on the element content of the corresponding metal., Senate					
			pounds at the work place da			
		health (MAK-commission).				
	,	TWA (inhalable	0,2 mg/m3	2017/164/EU		
		fraction)	(Manganese)			
	Further inform	nation: Indicative	, , , , , , , , , , , , , , , , , , , ,	•		
		TWA (Respirable	0,05 mg/m3	2017/164/EU		
		fraction)	(Manganese)			
	Further information: Indicative					
titanium dioxide	13463-67-7	AGW (Inhalable	10 mg/m3	DE TRGS		
maniani dioxido	1010001	fraction)	(Titanium dioxide)	900		
	Peak-limit: ev	cursion factor (categ		1 300		
	i carallille. ex	AGW (Alveolate	1,25 mg/m3	DE TRGS		
		AGW (Alveolate	1,23 mg/m3	DE IKGO		

according to Regulation (EC) No. 1907/2006



# CaparolColor Vollton- und Abtönfarbe

VersionRevision Date:Print DateDate of last issue: 18.11.20192.130.01.202102.02.2021Date of first issue: 30.01.2021

	fra	raction)	(Titanium dioxide)	900
	Peak-limit: excur	rsion factor (catego	ory): 2;(II)	

## Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
barium sulfate	Consumers	Inhalation	Long-term systemic effects	10,00 mg/m3
	Consumers	Ingestion	Long-term systemic effects	13000,00 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	10,00 mg/m3
	Workers	Inhalation	Long-term local ef- fects	10,00 mg/m3
chromium (III) oxide	Consumers	Inhalation	Long-term local ef- fects	0,50 mg/m3
	Workers	Inhalation	Acute local effects	2,00 mg/m3
	Workers	Inhalation	Long-term local ef- fects	0,50 mg/m3
manganese ferrite black spinel	Workers	Inhalation	Long-term systemic effects	10,00 mg/m3
	Workers	Inhalation	Long-term local ef- fects	10,00 mg/m3
titanium dioxide	Consumers	Ingestion	Long-term systemic effects	700,00 mg/kg bw/day
	Workers	Inhalation	Long-term local ef- fects	10,00 mg/m3

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
barium sulfate	Fresh water	115 µg/l
	Fresh water sediment	600,4 mg/kg dry weight (d.w.)
	Soil	207,7 mg/kg dry weight (d.w.)
	Sewage treatment plant	62,2 mg/l
chromium (III) oxide	Sewage treatment plant	10 mg/l
	Intermittent use/release	0,0047 mg/l
	Soil	3,2 mg/kg dry weight (d.w.)
	Marine water	0,0047 mg/l
	Fresh water sediment	18,2 mg/kg dry weight (d.w.)
	Marine sediment	1,31 mg/kg dry weight (d.w.)
	Fresh water	0,0047 mg/l
titanium dioxide	Sewage treatment plant	100 mg/l
	Fresh water	0,184 mg/l
	Soil	100 mg/kg dry

according to Regulation (EC) No. 1907/2006



# CaparolColor Vollton- und Abtönfarbe

Version Revision Date: Print Date Date of last issue: 18.11.2019 2.1 30.01.2021 Date of first issue: 30.01.2021

	weight (d.w.)
Marine water	0,0184 mg/l
Fresh water sediment	1000 mg/kg dry weight (d.w.)
Marine sediment	100 mg/kg dry weight (d.w.)
Intermittent use/release	0,193 mg/l

#### 8.2 Exposure controls

Personal protective equipment

Eye protection : German trade association rules - BGR 192 Eye protection

Goggles

Hand protection

Material : Nitrile rubber Glove thickness : 0,2 mm Protective index : Class 3

Remarks : Before removing gloves clean them with soap and water.

Wear suitable gloves tested to EN374.

German trade association leaflet: Carry gloves (ZH 1/706)

Skin and body protection : Safety shoes

Long sleeved clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Skin should be washed after contact.

Remove and wash contaminated clothing before re-use.

During spray application: impervious clothing

Respiratory protection : No personal respiratory protective equipment normally re-

quired.

German trade association rules - BGR 190 Breathing protec-

tion

During spray application: Do not breathe spray dust. Use

A2/P2 combination filter for paint spraying.

#### **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

according to Regulation (EC) No. 1907/2006



# CaparolColor Vollton- und Abtönfarbe

Version Revision Date: Print Date Date of last issue: 18.11.2019 2.1 30.01.2021 Date of first issue: 30.01.2021

Appearance : liquid

Colour : No data available

Odour : No data available

Odour Threshold : Not relevant

pH : 8-9

Concentration: 100 %

Melting point/freezing point : not determined

Boiling point/boiling range : not determined

100 °C

Flash point : Not applicable

Evaporation rate : Not applicable

Upper explosion limit / Upper

flammability limit

not determined

Lower explosion limit / Lower

flammability limit

not determined

Vapour pressure : not determined

Relative vapour density : not determined

Relative density : not determined

Density : 1,3170 g/cm3

Solubility(ies)

Water solubility : completely miscible

insoluble

Partition coefficient: n-

octanol/water

: not determined

Auto-ignition temperature : not determined

Decomposition temperature : Not applicable

Viscosity

Viscosity, dynamic : No data available

according to Regulation (EC) No. 1907/2006



# CaparolColor Vollton- und Abtönfarbe

Version Revision Date: Print Date Date of last issue: 18.11.2019 2.1 30.01.2021 Date of first issue: 30.01.2021

Explosive properties : Not applicable

Oxidizing properties : Not applicable

9.2 Other information

Flammability (liquids) : The product is not flammable.

#### **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No decomposition if stored and applied as directed.

#### 10.2 Chemical stability

No decomposition if stored and applied as directed.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

10.4 Conditions to avoid

Conditions to avoid : Protect from frost, heat and sunlight.

10.5 Incompatible materials

Materials to avoid : Incompatible with acids and bases.

Incompatible with oxidizing agents.

#### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

### **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

#### **Acute toxicity**

**Product:** 

Acute oral toxicity : Remarks: Based on available data, the classification criteria

are not met.

Acute inhalation toxicity : Remarks: Based on available data, the classification criteria

are not met.

Acute dermal toxicity : Remarks: Based on available data, the classification criteria

are not met.

according to Regulation (EC) No. 1907/2006



### CaparolColor Vollton- und Abtönfarbe

Version Revision Date: Print Date Date of last issue: 18.11.2019 2.1 30.01.2021 Date of first issue: 30.01.2021

### **Components:**

1,2-benzisothiazol-3(2H)-one:

Acute oral toxicity : LD50 (Rat): 532 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0,4 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg

2-methylisothiazol-3(2H)-one:

Acute oral toxicity : LD50 (Rat): 120 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0,145 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one

(3:1):

Acute oral toxicity : LD50 (Rat): 66 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 0,17 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rat): > 141 mg/kg

Method: OECD Test Guideline 402

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one

(3:1):

Acute oral toxicity : LD50 (Rat): 66 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 0,17 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rat): > 141 mg/kg

Method: OECD Test Guideline 402

chromium (III) oxide:

Acute oral toxicity : LD50 Oral (Rat): 10.000 mg/kg

according to Regulation (EC) No. 1907/2006



# CaparolColor Vollton- und Abtönfarbe

Version Print Date Date of last issue: 18.11.2019 **Revision Date:** 2.1 30.01.2021 02.02.2021 Date of first issue: 30.01.2021

#### Skin corrosion/irritation

**Product:** 

Remarks According to the classification criteria of the European Union,

the product is not considered as being a skin irritant.

Serious eye damage/eye irritation

**Product:** 

Remarks According to the classification criteria of the European Union,

the product is not considered as being an eye irritant.

Respiratory or skin sensitisation

**Product:** 

Remarks Causes sensitisation.

**SECTION 12: Ecological information** 

12.1 Toxicity

**Product:** 

Remarks: No data available Toxicity to fish

Toxicity to daphnia and other : Remarks: No data available

aquatic invertebrates

**Components:** 

1,2-benzisothiazol-3(2H)-one:

Toxicity to fish LC50 (Oncorhynchus mykiss (rainbow trout)): 2,2 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia (water flea)): 3,27 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 (Selenastrum capricornutum (green algae)): 0,11 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

M-Factor (Acute aquatic tox-

icity)

M-Factor (Chronic aquatic

toxicity)

1

according to Regulation (EC) No. 1907/2006



# CaparolColor Vollton- und Abtönfarbe

Version Revision Date: Print Date Date of last issue: 18.11.2019 2.1 30.01.2021 Date of first issue: 30.01.2021

2-methylisothiazol-3(2H)-one:

M-Factor (Acute aquatic tox- : 10

icity)

M-Factor (Chronic aquatic : 1

toxicity)

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one

(3:1):

M-Factor (Acute aquatic tox- : 100

icity)

M-Factor (Chronic aquatic

toxicity)

100

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):

M-Factor (Acute aquatic tox-:

icity)

M-Factor (Chronic aquatic

toxicity)

100

100

barium sulfate:

Toxicity to fish : Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other

aquatic invertebrates

Remarks: No toxicity at the limit of solubility

Toxicity to algae/aquatic

plants

Remarks: No toxicity at the limit of solubility

Toxicity to fish (Chronic tox-

icity)

Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

Remarks: No toxicity at the limit of solubility

chromium (III) oxide:

Toxicity to fish : Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other :

aquatic invertebrates

Remarks: No toxicity at the limit of solubility

according to Regulation (EC) No. 1907/2006



# CaparolColor Vollton- und Abtönfarbe

Version Print Date Date of last issue: 18.11.2019 Revision Date: 2.1 30.01.2021 02.02.2021 Date of first issue: 30.01.2021

Toxicity to algae/aquatic

plants

Remarks: No toxicity at the limit of solubility

Toxicity to fish (Chronic tox-

Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

Remarks: No toxicity at the limit of solubility

#### 12.2 Persistence and degradability

No data available

#### 12.3 Bioaccumulative potential

#### **Components:**

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):

Partition coefficient: nlog Pow: <= 0,71

octanol/water Method: OECD Test Guideline 117

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one

(3:1):

Partition coefficient: nlog Pow: <= 0,71

octanol/water Method: OECD Test Guideline 117

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

**Product:** 

Assessment This substance/mixture contains no components considered

> to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

#### 12.6 Other adverse effects

Product:

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

#### **SECTION 13: Disposal considerations**

## 13.1 Waste treatment methods

according to Regulation (EC) No. 1907/2006



### CaparolColor Vollton- und Abtönfarbe

Version Revision Date: Print Date Date of last issue: 18.11.2019 2.1 30.01.2021 Date of first issue: 30.01.2021

Product :

Waste should not be disposed of via wastewater.

Contaminated packaging : Only completely emptied containers should be given for recy-

cling.

Waste Code : used product

080112, waste paint and varnish other than those mentioned

in 08 01 11\*

#### **SECTION 14: Transport information**

#### 14.1 UN number

Not regulated as a dangerous good

#### 14.2 UN proper shipping name

Not regulated as a dangerous good

#### 14.3 Transport hazard class(es)

Not regulated as a dangerous good

#### 14.4 Packing group

Not regulated as a dangerous good

#### 14.5 Environmental hazards

Not regulated as a dangerous good

#### 14.6 Special precautions for user

Remarks : Not classified as dangerous in the meaning of transport regu-

lations.

#### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

#### **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 3

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).

This product is a mixture and does not contain Substances of Very High Concern (SVHC) equal or above 0.1%. Therefore no advised uses have to be defined and no chemical

according to Regulation (EC) No. 1907/2006



## CaparolColor Vollton- und Abtönfarbe

Version Revision Date: Print Date Date of last issue: 18.11.2019 2.1 30.01.2021 Date of first issue: 30.01.2021

safety assessment has to be gener-

ated.

REACH - List of substances subject to authorisation : None

(Annex XIV)

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

Water contaminating class : 1 slightly water endangering

(Germany) Classification according to AwSV, Annex 1 (5.2)

Volatile organic compounds : Directive 2004/42/EC

< 0.1 % < 1 g/l

#### Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

Contains a substance which is subject to the TRGS 905 : cobalt chromite blue green spinel list of carcinogenic, germ cell mutagenic and reproductive toxic substances.

#### 15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

#### **SECTION 16: Other information**

#### **Full text of H-Statements**

H301 : Toxic if swallowed.
H302 : Harmful if swallowed.
H310 : Fatal in contact with skin.
H311 : Toxic in contact with skin.

H314 : Causes severe skin burns and eye damage.

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction. H318 : Causes serious eye damage.

H330 : Fatal if inhaled.

H351 : Suspected of causing cancer if inhaled.

H400 : Very toxic to aquatic life.

according to Regulation (EC) No. 1907/2006



### CaparolColor Vollton- und Abtönfarbe

Version Revision Date: Print Date Date of last issue: 18.11.2019 2.1 30.01.2021 Date of first issue: 30.01.2021

H410 : Very toxic to aquatic life with long lasting effects.H411 : Toxic to aquatic life with long lasting effects.

#### Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Acute : Short-term (acute) aquatic hazard Aquatic Chronic : Long-term (chronic) aquatic hazard

Carc. : Carcinogenicity
Eye Dam. : Serious eye damage
Skin Corr. : Skin corrosion
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation

2004/37/EC : Europe. Directive 2004/37/EC on the protection of workers

from the risks related to exposure to carcinogens or mutagens

at work

2006/15/EC : Europe. Indicative occupational exposure limit values : Europe. Commission Directive 2017/164/EU establishing a

fourth list of indicative occupational exposure limit values

DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.

2004/37/EC / TWA : Long term exposure limit 2006/15/EC / TWA : Limit Value - eight hours 2017/164/EU / TWA : Limit Value - eight hours DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELX - Loading rate associated with x% response; EMS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Coil Aviation Organization; IECSC - International Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; IECSC - International Maritime Dangerous Goods; IMO - International Maritime Organization; ICAO - International Maritime Dangerous Goods; IMO - International Maritime Organization; ICAO - International Maritime Organization; ICAO - International Maritime Dangerous Goods; IMO - International Maritime Organization; ICAO - International Maritime Dangerous Goods; IMO - International Maritime Danger

#### **Further information**

#### Other information:

No exposure scenario communication is required for this product according to REACH Regulation No. 1907/2006 EC.

Communication of Uses is not required in accordance with REACH Article 31(1)(a) - registered substances / mixtures do not meet the criteria for classification as hazardous in accordance with Regulations 1272/2008 EC or 1999/45/EC.

#### Sources of key data used to compile the Safety Data Sheet:

ECHA WebSite

according to Regulation (EC) No. 1907/2006



# CaparolColor Vollton- und Abtönfarbe

Version Revision Date: Print Date Date of last issue: 18.11.2019 2.1 30.01.2021 Date of first issue: 30.01.2021

ACGIH (American Conference of Government Industrial Hygienists). 2014 TLVs and BEIs. Threshold Limit Values (TLVs) for chemical substances and physical agents and Biological Expo-

sure Indices (BEIs) with Seventh Edition documentation. 2014 ACGIH, Cincinnati OH

NIOSH - Registry of toxic effects of chemical substances

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre,

Commission of the European Communities

SAX'S - Dangerous properties of industrial materials

GESTIS - Database on hazardous substances - Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA, Institute for Occupational Safety and Health of the German Social Accident Insurance)

Toxnet - Toxicology Data Network

#### Classification of the mixture:

Classification procedure:

Skin Sens. 1 H317 Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

#### **REACH Information**

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our upstream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly.

DE / EN