according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

# Capadur UniversalLasur Renovierfarbton

Version Revision Date: SDS Number: Date of last issue: 14.03.2023 3.0 25.01.2024 6007018 Date of first issue: 09.07.2019

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Capadur UniversalLasur Renovierfarbton

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Solvent-borne coatings

stance/Mixture

Recommended restrictions

on use

: within adequate application - none

1.3 Details of the supplier of the safety data sheet

Company : Caparol Farben Lacke GmbH

Roßdörfer Straße 50 64372 Ober-Ramstadt

Telephone : +496154710 Telefax : +4961547170222

Website

E-mail address Responsi-

ble/issuing person

msds@dr-rmi.com

1.4 Emergency telephone

Emergency telephone 1 : +49613284463 GBK GmbH

#### **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

### Classification (REGULATION (EC) No 1272/2008)

| Skin sensitization, Category 1                 | H317: May cause an allergic skin reaction.               |
|--|--|
| Long-term (chronic) aquatic hazard, Category 3 | H412: Harmful to aquatic life with long lasting effects. |

### 2.2 Label elements

### Labeling (REGULATION (EC) No 1272/2008)

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

# Capadur UniversalLasur Renovierfarbton

SDS Number: Version Revision Date: Date of last issue: 14.03.2023 25.01.2024 6007018 3.0 Date of first issue: 09.07.2019

Hazard pictograms

Signal Word Warning

Hazard Statements H317 May cause an allergic skin reaction.

> H412 Harmful to aquatic life with long lasting effects.

Supplemental Hazard **EUH066** Repeated exposure may cause skin

Statements dryness or cracking.

If medical advice is needed, have product container or **Precautionary Statements** 

label at hand.

P102 Keep out of reach of children.

Prevention:

P261 Avoid breathing mist or vapors. Avoid release to the environment. P273

P280 Wear protective gloves.

Disposal:

Dispose of contents/ container to an approved waste

disposal plant.

### Hazardous ingredients which must be listed on the label:

Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6pentamethyl-4-piperidyl sebacate 4,5-dichloro-2-octyl-2H-isothiazol-3-one octhilinone (ISO) maleic anhydride

### **Additional Labeling**

Warning! Hazardous respirable droplets may be formed when sprayed. Do not EUH211

breathe spray or mist.

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

# Capadur UniversalLasur Renovierfarbton

Version Revision Date: SDS Number: Date of last issue: 14.03.2023 3.0 25.01.2024 6007018 Date of first issue: 09.07.2019

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

.

# **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

Chemical nature : Alkyd-resin-based wood varnish, solvent-containing, with film

protection

Components

| Chemical name  | CAS-No. EC-No. Index-No. Registration number  | Classification   | Concentration<br>(% w/w) |
|--|---|--|--------------------------|
| Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha                                     | 64742-48-9<br>265-150-3<br>649-327-00-6<br>01-2119457273-39,<br>01-2119463258-33,<br>01-2119486659-16 | Asp. Tox. 1; H304<br>EUH066  | >= 30 - < 50             |
| titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm]               | 13463-67-7<br>236-675-5<br>022-006-00-2<br>01-2119489379-17   | Carc. 2; H351  | >= 1 - < 10              |
| 1-isopropyl-2,2-<br>dimethyltrimethylene diisobutyrate   | 6846-50-0<br>229-934-9<br>01-2119451093-47  | Repr. 2; H361d<br>Aquatic Chronic 3;<br>H412   | >= 1 - < 2,5             |
| Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate | 1065336-91-5<br>915-687-0<br>01-2119491304-40   | Skin Sens. 1A; H317<br>Aquatic Acute 1;<br>H400<br>Aquatic Chronic 1;<br>H410<br>Repr. 2; H361f  | >= 0,25 - < 1            |
| 4,5-dichloro-2-octyl-2H-isothiazol-<br>3-one   | 64359-81-5<br>264-843-8<br>613-335-00-8   | Acute Tox. 4; H302 Acute Tox. 2; H330 Skin Corr. 1; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071 | >= 0,0025 - <<br>0,025   |

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

| Capadur UniversalLasur Renovierfarbton |                              |  |  |               |
|--|------------------------------|--|--|---------------|
|  | Revision Date:<br>25.01.2024 |  |  |               |
| Version<br>3.0                         | Revision Date:               | SDS Number: 6007018                      | Date of last issue: 14.03.2023 Date of first issue: 09.07.2019  M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100  specific concentration limit Skin Irrit. 2; H315 0,025 - < 5 % Eye Irrit. 2; H319 0,025 - < 3 % Skin Sens. 1A; H317 >= 0,0015 %  Acute toxicity estimate  Acute oral toxicity: 567 mg/kg Acute inhalation toxicity (dust/mist): 0,16 mg/l  Acute Tox. 3; H301 | >= 0,0025 - < |
|  |                              | 247-761-7<br>613-112-00-5<br>01-21207689 |  | 0,025         |

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

| Capadur | UniversalLasur | Renovierfarbton |
|---------|----------------|-----------------|
|---------|----------------|-----------------|

Version Revision Date: SDS Number: Date of last issue: 14.03.2023 3.0 25.01.2024 6007018 Date of first issue: 09.07.2019

| maleic anhydride                  | 108-31-6<br>203-571-6<br>607-096-00-9<br>01-2119472428-31,<br>01-2120759691-45 | Acute toxicity estimate  Acute oral toxicity: 125 mg/kg Acute inhalation toxicity (dust/mist): 0,27 mg/l Acute dermal toxicity: 311 mg/kg Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Resp. Sens. 1; H334 Skin Sens. 1A; H317 STOT RE 1; H372 (Respiratory system, Inhalation) EUH071  specific concentration limit Skin Sens. 1A; H317 >= 0,001 % | < 0,001     |
|-----------------------------------|--|--|-------------|
| Substances with a workplace expos |  | <u> </u>   |             |
| Silica gel, pptd., crystfree      | 112926-00-8<br>231-545-4<br>01-2119379499-16,<br>01-2120105300-82              |  | >= 1 - < 10 |

For explanation of abbreviations see section 16.

### **SECTION 4: First aid measures**

# 4.1 Description of first-aid measures

General advice : Never give anything by mouth to an unconscious person.

If you feel unwell, seek medical advice (show the label where

possible).

Move out of dangerous area. First aider needs to protect himself.

If inhaled : Call a physician.

If breathing is irregular or stopped, administer artificial respira-

tion.

If unconscious, place in recovery position and seek medical

advice.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Capadur UniversalLasur Renovierfarbton

Version Revision Date: SDS Number: Date of last issue: 14.03.2023 3.0 25.01.2024 6007018 Date of first issue: 09.07.2019

If symptoms persist, call a physician.

Move to fresh air.

In case of skin contact : Do NOT use solvents or thinners.

In case of contact, immediately flush skin with soap and plenty

of water.

Take off all contaminated clothing immediately.

In case of eye contact : If eye irritation persists: Get medical advice/ attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing.

If swallowed : Seek medical advice.

Clean mouth with water and drink afterwards plenty of water.

If swallowed, DO NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Risks : May cause an allergic skin reaction.

Repeated exposure may cause skin dryness or cracking.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No information available.

### **SECTION 5: Firefighting measures**

# 5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Use water spray, alcohol-resistant foam, dry chemical or car-

bon dioxide.

Do not use a solid water stream as it may scatter and spread

fire.

Unsuitable extinguishing

media

None known.

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire

fighting

Cool closed containers exposed to fire with water spray.
 In case of fire hazardous decomposition products may be

produced such as:

Carbon monoxide, carbon dioxide and unburned hydrocar-

bons (smoke).

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

# Capadur UniversalLasur Renovierfarbton

Version Revision Date: SDS Number: Date of last issue: 14.03.2023 6007018 3.0 25.01.2024 Date of first issue: 09.07.2019

### 5.3 Advice for firefighters

for fire-fighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information Standard procedure for chemical fires.

In the event of fire and/or explosion do not breathe fumes.

# **SECTION 6: Accidental release measures**

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions Do not get in eyes, on skin, or on clothing.

When workers are facing concentrations above the exposure

limit they must use appropriate certified respirators.

Ensure adequate ventilation. Remove all sources of ignition.

### 6.2 Environmental precautions

**Environmental precautions** Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Do not flush into surface water or sanitary sewer system.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up Keep in suitable, closed containers for disposal.

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

### 6.4 Reference to other sections

For further information see Section 7 of the safety data sheet.

, For personal protection see section 8., For disposal considerations see section 13.

### **SECTION 7: Handling and storage**

### 7.1 Precautions for safe handling

Advice on safe handling Non-sparking tools should be used.

For personal protection see section 8.

Avoid exceeding the given occupational exposure limits (see

section 8).

Provide sufficient air exchange and/or exhaust in work rooms.

In addition, the current technical information for this product and its application on www.caparol.com must be observed.

Advice on protection against : Vapors may form explosive mixtures with air. Vapors are

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Capadur UniversalLasur Renovierfarbton

Version Revision Date: SDS Number: Date of last issue: 14.03.2023 3.0 25.01.2024 6007018 Date of first issue: 09.07.2019

fire and explosion heavier than air and may spread along floors. Keep away from

heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

Hygiene measures : Avoid contact with the skin and the eyes. Wash hands before

eating, drinking, or smoking. Do not eat, drink or smoke when using this product. Remove contaminated clothing and protec-

tive equipment before entering eating areas.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage

areas and containers

: Store in original container. Store between 41 and 77 °F in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Storage class (TRGS 510) : 10

7.3 Specific end use(s)

Specific use(s) : This information is not available.

### **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

### **Occupational Exposure Limits**

| Components   | CAS-No.   | Value type (Form of exposure) | Control parameters            | Basis          |
|--|---|-------------------------------|-------------------------------|----------------|
| Naphtha (petrole-<br>um), hydrotreated<br>heavy; Low boiling<br>point ydrogen<br>treated naphtha | 64742-48-9  | AGW                           | 300 mg/m3                     | DE TRGS<br>900 |
|  | Peak-limit cat  |                               |                               |                |
|  | Further inform  | ation: Group exposu           | re limit for hydrocarbon solv |                |
| titanium dioxide; [in  | 13463-67-7  | AGW (Inhalable                | 10 mg/m3                      | DE TRGS        |
| powder form con-   |   | fraction)                     | (Titanium dioxide)            | 900            |
| taining 1 % or   |   |                               |                               |                |
| more of particles  |   |                               |                               |                |
| with aerodynamic   |   |                               |                               |                |
| diameter ≤ 10 µm]  |   |                               |                               |                |
|  | Peak-limit cat  | • • • •                       |                               |                |
|  | Further information: When there is compliance with the OEL and biological |                               |                               |                |
|  | tolerance values, there is no risk of harming the unborn child            |                               |                               |                |
|  |   | AGW (Alveolate                | 1,25 mg/m3                    | DE TRGS        |
|  |   | fraction)                     | (Titanium dioxide)            | 900            |
|  | Peak-limit category: 2;(II)   |                               |                               |                |

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

# Capadur UniversalLasur Renovierfarbton

Version Revision Date: SDS Number: Date of last issue: 14.03.2023 3.0 25.01.2024 6007018 Date of first issue: 09.07.2019

|                    | Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child |                               |                                |               |
|--------------------|--|-------------------------------|--------------------------------|---------------|
|                    |  | BM (Alveolar 0,5 mg/m3 DE TRG |                                |               |
|                    |  | dust fraction)                |                                | 527           |
| Silica gel, pptd., | 112926-00-   | AGW (Inhalable                | 4 mg/m3                        | DE TRGS       |
| crystfree          | 8  | fraction)                     | (Silica)                       | 900           |
|                    |  |                               | compliance with the OEL ar     | nd biological |
|                    | tolerance valu   | ies, there is no risk o       | of harming the unborn child    |               |
| octhilinone (ISO)  | 26530-20-1   | AGW (Inhalable                | 0,05 mg/m3                     | DE TRGS       |
|                    |  | fraction)                     |                                | 900           |
|                    | Peak-limit cat   | egory: 2;(I)                  |                                |               |
|                    |  |                               | on, When there is compliance   |               |
|                    | and biological   | tolerance values, th          | ere is no risk of harming the  | unborn child  |
| maleic anhydride   | 108-31-6   | AGW (Vapour                   | 0,02 ppm                       | DE TRGS       |
|                    |  | and aerosols)                 | 0,081 mg/m3                    | 900           |
|                    | Peak-limit cat   | egory: 1; =2.5=(I)            |                                |               |
|                    | Further information: In well-found cases also a momentary value can be es-   |                               |                                |               |
|                    | tablished, that never can be exceeded. This substance will be indicated by = =   |                               |                                |               |
|                    | in combination with an exceeding value., When there is compliance with the   |                               |                                |               |
|                    | OEL and biological tolerance values, there is no risk of harming the unborn  |                               |                                |               |
|                    | child, Substar   | nce sensitizing throu         | gh the skin and respiratory sy | ystem         |

# Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

| Substance name   | End Use   | Routes of expo-<br>sure | Potential health effects   | Value                  |
|--|-----------|-------------------------|----------------------------|------------------------|
| titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm] | Consumers | Ingestion               | Long-term systemic effects | 700,00 mg/kg<br>bw/day |
|  | Workers   | Inhalation              | Long-term local effects    | 10,00 mg/m3            |
| iron hydroxide oxide yellow  | Workers   | Inhalation              | Long-term systemic effects | 10,00 mg/m3            |
|  | Workers   | Inhalation              | Long-term local effects    | 10,00 mg/m3            |
| 1-isopropyl-2,2-<br>dimethyltrimethylene<br>diisobutyrate  | Consumers | Ingestion               | Long-term systemic effects | 18,80 mg/kg<br>bw/day  |
|  | Consumers | Skin contact            | Long-term systemic effects | 18,80 mg/kg<br>bw/day  |
|  | Consumers | Inhalation              | Long-term systemic effects | 32,60 mg/m3            |
|  | Workers   | Inhalation              | Long-term systemic effects | 110,00 mg/m3           |
|  | Workers   | Skin contact            | Long-term systemic effects | 31,20 mg/kg<br>bw/day  |

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

# Capadur UniversalLasur Renovierfarbton

VersionRevision Date:SDS Number:Date of last issue: 14.03.20233.025.01.20246007018Date of first issue: 09.07.2019

| Reaction mass of<br>bis(1,2,2,6,6-<br>pentamethyl-4-<br>piperidyl) sebacate<br>and methyl 1,2,2,6,6-<br>pentamethyl-4-<br>piperidyl sebacate | Consumers | Inhalation   | Acute local effects          | 0,58 mg/m3           |
|--|-----------|--------------|------------------------------|----------------------|
| p.ponay. cosacato  | Consumers | Ingestion    | Long-term systemic effects   | 1,25 mg/kg<br>bw/day |
|  | Consumers | Inhalation   | Long-term systemic effects   | 0,58 mg/m3           |
|  | Consumers | Inhalation   | Acute systemic ef-<br>fects  | 0,58 mg/m3           |
|  | Consumers | Skin contact | Long-term systemic effects   | 1,25 mg/kg<br>bw/day |
|  | Consumers | Skin contact | Acute systemic effects       | 1,25 mg/kg<br>bw/day |
|  | Consumers | Ingestion    | Acute systemic effects       | 1,25 mg/kg<br>bw/day |
|  | Workers   | Inhalation   | Acute systemic effects       | 2,35 mg/m3           |
|  | Workers   | Inhalation   | Acute local effects          | 2,35 mg/m3           |
|  | Workers   | Inhalation   | Long-term systemic effects   | 2,35 mg/m3           |
|  | Workers   | Skin contact | Acute systemic ef-<br>fects  | 2,50 mg/kg<br>bw/day |
|  | Workers   | Skin contact | Long-term systemic effects   | 2,50 mg/kg<br>bw/day |
| maleic anhydride   | Consumers | Inhalation   | Long-term systemic effects   | 0,05 mg/m3           |
|  | Consumers | Ingestion    | Long-term systemic effects   | 0,06 mg/kg<br>bw/day |
|  | Consumers | Ingestion    | Acute systemic ef-<br>fects  | 0,10 mg/kg<br>bw/day |
|  | Consumers | Skin contact | Acute systemic ef-<br>fects  | 0,10 mg/kg<br>bw/day |
|  | Consumers | Inhalation   | Long-term local ef-<br>fects | 0,08 mg/m3           |
|  | Consumers | Skin contact | Long-term systemic effects   | 0,10 mg/kg<br>bw/day |
|  | Workers   | Inhalation   | Acute systemic ef-<br>fects  | 0,80 mg/m3           |
|  | Workers   | Inhalation   | Acute systemic ef-<br>fects  | 0,95 mg/m3           |
|  | Workers   | Inhalation   | Acute local effects          | 0,80 mg/m3           |
|  | Workers   | Inhalation   | Long-term systemic effects   | 0,40 mg/m3           |
|  | Workers   | Inhalation   | Long-term systemic           | 0,19 mg/m3           |

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

# Capadur UniversalLasur Renovierfarbton

Version Revision Date: SDS Number: Date of last issue: 14.03.2023 3.0 25.01.2024 6007018 Date of first issue: 09.07.2019

|     |         |              | effects                      |                      |
|-----|---------|--------------|------------------------------|----------------------|
| Wo  | orkers  | Inhalation   | Long-term local ef-<br>fects | 0,40 mg/m3           |
| Wo  | orkers  | Inhalation   | Long-term local ef-<br>fects | 0,32 mg/m3           |
| Wo  | orkers  | Skin contact | Acute systemic effects       | 0,20 mg/kg<br>bw/day |
| Wo  | orkers  | Skin contact | Long-term systemic effects   | 0,20 mg/kg<br>bw/day |
| Col | nsumers | Inhalation   | Acute systemic effects       |                      |

# Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

| Substance name   | Environmental Compartment | Value                            |
|--|---------------------------|----------------------------------|
| titanium dioxide; [in powder form containing 1 % or more of parti-   | Sewage treatment plant    | 100 mg/l                         |
| cles with aerodynamic diameter ≤   |                           |                                  |
| 10 μm]   |                           |                                  |
|  | Fresh water               | 0,184 mg/l                       |
|  | Soil                      | 100 mg/kg dry<br>weight (d.w.)   |
|  | Sea water                 | 0,0184 mg/l                      |
|  | Fresh water sediment      | 1000 mg/kg dry<br>weight (d.w.)  |
|  | Sea sediment              | 100 mg/kg dry<br>weight (d.w.)   |
|  | Intermittent use/release  | 0,193 mg/l                       |
| 1-isopropyl-2,2-<br>dimethyltrimethylene diisobutyr-<br>ate  | Sea water                 | 0,0014 mg/l                      |
|  | Sewage treatment plant    | 3 mg/l                           |
|  | Sea sediment              | 0,529 mg/kg dry<br>weight (d.w.) |
|  | Secondary Poisoning       | 83,3 mg/kg food                  |
|  | Fresh water               | 0,014 mg/l                       |
|  | Soil                      | 1,05 mg/kg dry<br>weight (d.w.)  |
|  | Fresh water sediment      | 5,29 mg/kg dry<br>weight (d.w.)  |
| Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate | Sea water                 | 0,00022 mg/l                     |
|  | Soil                      | 0,21 mg/kg dry<br>weight (d.w.)  |
|  | Fresh water               | 0,0022 mg/l                      |
|  | Sewage treatment plant    | 1 mg/l                           |
|  | Fresh water sediment      | 1,05 mg/kg dry                   |

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

# Capadur UniversalLasur Renovierfarbton

Version Revision Date: SDS Number: Date of last issue: 14.03.2023 3.0 25.01.2024 6007018 Date of first issue: 09.07.2019

|                  |                          | weight (d.w.)    |
|------------------|--------------------------|------------------|
|                  | Intermittent use/release | 0,009 mg/l       |
|                  | Sea sediment             | 0,11 mg/kg dry   |
|                  |                          | weight (d.w.)    |
| maleic anhydride | Fresh water              | 0,075 mg/l       |
|                  | Fresh water sediment     | 0,334 mg/kg dry  |
|                  |                          | weight (d.w.)    |
|                  | Soil                     | 0,0415 mg/kg dry |
|                  |                          | weight (d.w.)    |
|                  | Sea water                | 0,01 mg/l        |
|                  | Intermittent use/release | 0,4281 mg/l      |
|                  | Sewage treatment plant   | 44,6 mg/l        |
|                  | Soil                     | 0,01 mg/kg dry   |
|                  |                          | weight (d.w.)    |
|                  | Sea water                | 0,0075 mg/l      |
|                  | Secondary Poisoning      | 6,67 mg/kg food  |
|                  | Fresh water              | 0,1 mg/l         |
|                  | Sewage treatment plant   | 4,46 mg/l        |
|                  | Sea sediment             | 0,006 mg/kg dry  |
|                  |                          | weight (d.w.)    |
|                  | Fresh water sediment     | 0,06 mg/kg dry   |
|                  |                          | weight (d.w.)    |
|                  | Intermittent use/release | 0,75 mg/l        |
|                  | Sea sediment             | 0,0334 mg/kg dry |
|                  |                          | weight (d.w.)    |

### 8.2 Exposure controls

Personal protective equipment

Eye/face protection : DGUV Regulation 112-192 - Use of eye and face protection

Goggles

Hand protection

Material : Nitrile rubber Glove thickness : 0,2 mm Protective index : Class 3

Remarks : Gloves should be discarded and replaced if there is any indi-

cation of degradation or chemical breakthrough. Before removing gloves clean them with soap and water. Wear suita-

ble gloves tested to EN374.

DGUV Regulation 112-195 - Use of protective gloves

Skin and body protection : Safety shoes

Long sleeved clothing

Choose body protection according to the amount and con-

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Capadur UniversalLasur Renovierfarbton

Version Revision Date: SDS Number: Date of last issue: 14.03.2023 3.0 25.01.2024 6007018 Date of first issue: 09.07.2019

centration of the dangerous substance at the work place.

Skin should be washed after contact.

Remove and wash contaminated clothing before re-use.

During spray application: impervious clothing

Respiratory protection : Roller application or brushing: This product should not be

used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to

standard EN 14387) is used.

DGUV Regulation 112-190 - Use of breathing equipment

During spray application: Do not breathe spray dust. Use

A2/P2 combination filter for paint spraying.

# **SECTION 9: Physical and chemical properties**

9.1 Information on basic physical and chemical properties

Physical state : liquid

Color : white

Odor : characteristic

Odor Threshold : Not relevant

Melting point/freezing point : not determined

Boiling point/boiling range : not determined

Upper explosion limit / Upper

flammability limit

not determined

Lower explosion limit / Lower

flammability limit

not determined

Flash point :  $> 60 \, ^{\circ}\text{C}$ 

Method: ISO 1523

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Capadur UniversalLasur Renovierfarbton

Version Revision Date: SDS Number: Date of last issue: 14.03.2023 3.0 25.01.2024 6007018 Date of first issue: 09.07.2019

Autoignition temperature : not determined

Decomposition temperature : Not applicable

pH : substance/mixture is non-soluble (in water)

Viscosity

Viscosity, dynamic : > 100 mPa.s (40 °C)

Method: ISO 3219

Viscosity, kinematic : >= 21 mm2/s (40 °C)

> 20,5 mm2/s (40 °C) Method: ISO 3104/3105

Flow time : Not applicable

> 60 s at 23 °C Cross section: 6 mm Method: ISO 2431

Solubility(ies)

Water solubility : partly miscible

Partition coefficient: n-

octanol/water

not determined

Vapor pressure : not determined

Relative density : not determined

Density : 0,99 g/cm3 (20 °C)

Method: DIN EN ISO 2811-1

Bulk density : Not applicable

Relative vapor density : Heavier than air.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

# Capadur UniversalLasur Renovierfarbton

Version Revision Date: SDS Number: Date of last issue: 14.03.2023 3.0 25.01.2024 6007018 Date of first issue: 09.07.2019

### 9.2 Other information

Explosives : Not applicable

Oxidizing properties : Not applicable

Flammability (liquids) : Sustains combustion

Evaporation rate : Not applicable

### **SECTION 10: Stability and reactivity**

### 10.1 Reactivity

No decomposition if stored and applied as directed.

#### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Vapors may form explosive mixture with air.

Hazardous decomposition products formed under fire condi-

tions.

10.4 Conditions to avoid

Conditions to avoid : Protect from frost, heat and sunlight.

10.5 Incompatible materials

Materials to avoid : Incompatible with acids and bases.

Incompatible with oxidizing agents.

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

### **SECTION 11: Toxicological information**

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

### **Acute toxicity**

Not classified based on available information.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

# Capadur UniversalLasur Renovierfarbton

Version Revision Date: SDS Number: Date of last issue: 14.03.2023 3.0 25.01.2024 6007018 Date of first issue: 09.07.2019

#### **Components:**

### 4,5-dichloro-2-octyl-2H-isothiazol-3-one:

Acute oral toxicity : Acute toxicity estimate: 567 mg/kg

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

Acute inhalation toxicity : Acute toxicity estimate: 0,16 mg/l

Test atmosphere: dust/mist

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

octhilinone (ISO):

Acute oral toxicity : Acute toxicity estimate: 125 mg/kg

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

Acute inhalation toxicity : Acute toxicity estimate: 0,27 mg/l

Test atmosphere: dust/mist

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

Acute dermal toxicity : Acute toxicity estimate: 311 mg/kg

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

maleic anhydride:

Acute oral toxicity : LD50 (Rat, male and female): 1.090 mg/kg

Method: OECD Test Guideline 401

Silica gel, pptd., cryst.-free:

Acute oral toxicity : LD50 Oral (Rat): > 10.000 mg/kg

Acute dermal toxicity : LD50 (Rat): > 5.000 mg/kg

### Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking

#### Components:

maleic anhydride:

Species : Rabbit

Assessment : Causes burns.

### Serious eye damage/eye irritation

Not classified based on available information.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

# Capadur UniversalLasur Renovierfarbton

Version Revision Date: SDS Number: Date of last issue: 14.03.2023 3.0 25.01.2024 6007018 Date of first issue: 09.07.2019

### **Components:**

### maleic anhydride:

Species : Rabbit

Assessment : Causes burns.

#### Respiratory or skin sensitization

#### Skin sensitization

May cause an allergic skin reaction.

### Respiratory sensitization

Not classified based on available information.

### **Components:**

#### maleic anhydride:

Species : Rat

Result : Causes sensitization.

### Germ cell mutagenicity

### Not classified based on available information.

### Carcinogenicity

Not classified based on available information.

#### Reproductive toxicity

Not classified based on available information.

### STOT-single exposure

Not classified based on available information.

#### **STOT-repeated exposure**

Not classified based on available information.

#### **Aspiration toxicity**

Not classified based on available information.

### 11.2 Information on other hazards

#### **Endocrine disrupting properties**

#### **Product:**

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

# Capadur UniversalLasur Renovierfarbton

Version Revision Date: SDS Number: Date of last issue: 14.03.2023 3.0 25.01.2024 6007018 Date of first issue: 09.07.2019

### **SECTION 12: Ecological information**

#### 12.1 Toxicity

#### **Components:**

### 4,5-dichloro-2-octyl-2H-isothiazol-3-one:

M-Factor (Acute aquatic tox- : 100

icity)

M-Factor (Chronic aquatic

100

toxicity)

### octhilinone (ISO):

M-Factor (Acute aquatic tox- : 100

icity)

M-Factor (Chronic aquatic

100

toxicity)

#### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

#### **Components:**

### Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha:

Partition coefficient: n- : log Pow: 1,99 - 18,02 (20 °C)

octanol/water pH: 7

### 1-isopropyl-2,2-dimethyltrimethylene diisobutyrate:

Partition coefficient: n- : log Pow: 4,49 (25 °C)

octanol/water

# Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate:

Partition coefficient: n- : log Pow: 2,37 - 2,77 (25 °C)

octanol/water pH: 7,0

octhilinone (ISO):

Partition coefficient: n- : log Pow: 2,61 (25 °C)

octanol/water pH: 7

### maleic anhydride:

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

# Capadur UniversalLasur Renovierfarbton

Version Revision Date: SDS Number: Date of last issue: 14.03.2023 3.0 25.01.2024 6007018 Date of first issue: 09.07.2019

Partition coefficient: n- : log Pow: -2,61 (19,8 °C)

octanol/water pH: 4 - 9

### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

**Product:** 

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

### 12.6 Endocrine disrupting properties

**Product:** 

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

#### 12.7 Other adverse effects

**Product:** 

Additional ecological infor-

mation

: Harmful to aquatic organisms, may cause long-term adverse

effects in the aquatic environment.

# **SECTION 13: Disposal considerations**

# 13.1 Waste treatment methods

Product : .

Waste should not be disposed of via wastewater.

Contaminated packaging : Only completely emptied containers should be given for recy-

cling.

Waste Code : used product

080112, waste paint and varnish other than those mentioned

in 08 01 11\*

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

# Capadur UniversalLasur Renovierfarbton

Version Revision Date: SDS Number: Date of last issue: 14.03.2023 3.0 25.01.2024 6007018 Date of first issue: 09.07.2019

### **SECTION 14: Transport information**

#### 14.1 UN number or ID number

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

### 14.3 Transport hazard class(es)

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.4 Packing group

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA (Cargo) : Not regulated as a dangerous good
IATA (Passenger) : Not regulated as a dangerous good

### 14.5 Environmental hazards

Not regulated as a dangerous good

### 14.6 Special precautions for user

Not applicable

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

# Capadur UniversalLasur Renovierfarbton

Version Revision Date: SDS Number: Date of last issue: 14.03.2023 6007018 3.0 25.01.2024 Date of first issue: 09.07.2019

### **SECTION 15: Regulatory information**

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)

Conditions of restriction for the following entries should be considered: Number on list 75, 3

If you intend to use this product as tattoo ink, please contact your ven-

dor.

REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59).

This product is a mixture and does not contain Substances of Very High Concern (SVHC) equal or above 0.1%. Therefore no advised uses have to be defined and no chemical safety assessment has to be generated.

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer

Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast)

Not applicable

REACH - List of substances subject to authorisation (Annex XIV)

None

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a)

to (d)

Water hazard class (Germa-WGK 2 obviously hazardous to water

Classification according to AwSV, Annex 1 (5.2) ny)

34

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

# Capadur UniversalLasur Renovierfarbton

Version Revision Date: SDS Number: Date of last issue: 14.03.2023 3.0 25.01.2024 6007018 Date of first issue: 09.07.2019

Product code for laquers and

paints / Giscode

: M-KH02F Solvent-based varnishes / wood glaze, aromatics

removed, active agents

: BSL40 Coating materials, strongly solvent-based, aromatic-

free, classified

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial

emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 36,41 %

Volatile organic compounds : Directive 2004/42/EC

< 37 % < 370 g/l

#### Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

#### 15.2 Chemical Safety Assessment

A Chemical Safety Assessment is not required for this mixture.

#### **SECTION 16: Other information**

#### **Full text of H-Statements**

H301 : Toxic if swallowed. H302 : Harmful if swallowed.

H304 : May be fatal if swallowed and enters airways.

H311 : Toxic in contact with skin.

H314 : Causes severe skin burns and eye damage.

H317 : May cause an allergic skin reaction.

H318 : Causes serious eye damage.

H330 : Fatal if inhaled.

H334 : May cause allergy or asthma symptoms or breathing difficul-

ties if inhaled.

H351 : Suspected of causing cancer if inhaled. H361d : Suspected of damaging the unborn child.

H361f : Suspected of damaging fertility.

H372 : Causes damage to organs through prolonged or repeated

exposure.

H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.
H412 : Harmful to aquatic life with long lasting effects.

EUH066 : Repeated exposure may cause skin dryness or cracking.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

# Capadur UniversalLasur Renovierfarbton

VersionRevision Date:SDS Number:Date of last issue: 14.03.20233.025.01.20246007018Date of first issue: 09.07.2019

EUH071 : Corrosive to the respiratory tract.

#### Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Acute : Short-term (acute) aquatic hazard Aquatic Chronic : Long-term (chronic) aquatic hazard

Asp. Tox. : Aspiration hazard
Carc. : Carcinogenicity
Eye Dam. : Serious eye damage
Repr. : Reproductive toxicity
Resp. Sens. : Respiratory sensitization

Skin Corr. : Skin corrosion Skin Sens. : Skin sensitization

STOT RE : Specific target organ toxicity - repeated exposure DE TRGS 527 : Germany. TRGS 527 - Activities with nanomaterials

DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.

DE TRGS 527 / BM : Assessment scale
DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AlIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; (EQ) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELX - Loading rate associated with x% response; EMS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Coil Aviation Organization; IECSC - Inventy of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Convention of Pollution organization; IECSC - Inventy of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Convention for the Prevention of Pollution from Ships; no.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observed (Adverse) Effect Sandardisteries) Str

#### **Further information**

#### Other information:

No exposure scenario communication is required for this product according to REACH Regulation No. 1907/2006 EC.

Communication of Uses is not required in accordance with REACH Article 31(1)(a) - registered substances / mixtures do not meet the criteria for classification as hazardous in accordance with Regulations 1272/2008 EC or 1999/45/EC.

#### Sources of key data used to compile the Material Safety Data Sheet:

ECHA WebSite

ACGIH (American Conference of Government Industrial Hygienists). 2014 TLVs and BEIs. Threshold Limit Values (TLVs) for chemical substances and physical agents and Biological Exposure Indices (BEIs) with Seventh Edition documentation. 2014 ACGIH, Cincinnati OH NIOSH - Registry of toxic effects of chemical substances

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

# Capadur UniversalLasur Renovierfarbton

Version Revision Date: SDS Number: Date of last issue: 14.03.2023 3.0 25.01.2024 6007018 Date of first issue: 09.07.2019

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX'S - Dangerous properties of industrial materials

GESTIS - Database on hazardous substances - Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA, Institute for Occupational Safety and Health of the German Social Accident Insurance)

Toxnet - Toxicology Data Network

#### Classification of the mixture:

#### Classification procedure:

| Skin Sens. 1      | H317 | Calculation method |
|-------------------|------|--------------------|
| Aquatic Chronic 3 | H412 | Calculation method |

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

### **REACH Information**

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our upstream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly.

DE / EN