according to Regulation (EC) No. 1907/2006



DE / EN

Capadur UniversalLasur Teak

Version Revision Date: SDS Number: Date of last issue: 19.10.2020 3.0 16.03.2023 6007580 Date of first issue: 29.07.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Capadur UniversalLasur Teak

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Solvent-borne coatings

stance/Mixture

Recommended restrictions

on use

within adequate application - none

1.3 Details of the supplier of the safety data sheet

Company : Caparol Farben Lacke GmbH

Roßdörfer Straße 50 64372 Ober-Ramstadt

Telephone : +496154710 Telefax : +4961547170222

Website

E-mail address Responsi-

ble/issuing person

: msds@dr-rmi.com

1.4 Emergency telephone

Emergency telephone 1 : +49613284463 GBK GmbH

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Long-term (chronic) aquatic hazard, Cat-

H412: Harmful to aquatic life with long lasting ef-

egory 3 fects.

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008)

Hazard Statements : H412 Harmful to aquatic life with long lasting effects.

Supplemental Hazard : EUH066 Repeated exposure may cause skin

Statements dryness or cracking.

according to Regulation (EC) No. 1907/2006

DE / EN



Capadur UniversalLasur Teak

Version Revision Date: SDS Number: Date of last issue: 19.10.2020 3.0 16.03.2023 6007580 Date of first issue: 29.07.2019

Precautionary Statements : P101 If medical advice is needed, have product container or

label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

Prevention:

P273 Avoid release to the environment.

Additional Labeling

EUH208 Contains 4,5-dichloro-2-octyl-2H-isothiazol-3-one, octhilinone (ISO), maleic anhydride, bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate. May produce an

allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Alkyd-resin-based wood varnish, solvent-containing, with film

protection

Components

Chemical name	CAS-No. EC-No.	Classification	Concentration (% w/w)
	Index-No.		(/o vv/ vv)
	Registration number		
Naphtha (petroleum), hydrotreat-	64742-48-9	Asp. Tox. 1; H304	>= 30 - < 50
ed heavy; Low boiling point ydro-	265-150-3	EUH066	
gen treated naphtha	649-327-00-6		
	01-2119457273-39,		
	01-2119463258-33,		
	01-2119486659-16		
1-isopropyl-2,2-	6846-50-0	Repr. 2; H361d	>= 1 - < 2,5
dimethyltrimethylene diisobutyrate	229-934-9	Aquatic Chronic 3;	

according to Regulation (EC) No. 1907/2006



DE / EN

Capadur UniversalLasur Teak

Version Revision Date: SDS Number: Date of last issue: 19.10.2020 3.0 16.03.2023 6007580 Date of first issue: 29.07.2019

	01-2119451093-47	H412	
bis(1,2,2,6,6-pentamethyl-4- piperidyl) sebacate	41556-26-7 255-437-1 01-2119491304-40	Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 Repr. 2; H361f	>= 0,1 - < 0,25
2-methylpentane-2,4-diol	107-41-5 203-489-0 603-053-00-3 01-2119539582-35	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Repr. 2; H361d	>= 0,1 - < 1
4,5-dichloro-2-octyl-2H-isothiazol-3-one	64359-81-5 264-843-8 613-335-00-8	Acute Tox. 4; H302 Acute Tox. 2; H330 Skin Corr. 1; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071 M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100 specific concentration limit Skin Irrit. 2; H315 0,025 - < 5 % Eye Irrit. 2; H319 0,025 - < 3 % Skin Sens. 1A; H317 >= 0,0015 % Acute toxicity estimate Acute oral toxicity: 567 mg/kg Acute inhalation toxicity (dust/mist): 0,16	>= 0,0025 - < 0,025
octhilinone (ISO)	26530-20-1 247-761-7 613-112-00-5	mg/l Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 3; H311	>= 0,0025 - < 0,025

according to Regulation (EC) No. 1907/2006



DE / EN

Capadur UniversalLasur Teak

Version	Revision Date:	SDS Number:	Date of last issue: 19.10.2020
3.0	16.03.2023	6007580	Date of first issue: 29.07.2019

	01-2120768921-45	Skin Corr. 1; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071	
		M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100	
		specific concentration limit Skin Sens. 1A; H317 >= 0,0015 %	
		Acute toxicity esti- mate	
		Acute oral toxicity: 125 mg/kg Acute inhalation tox- icity (dust/mist): 0,27 mg/l Acute dermal toxicity: 311 mg/kg	
maleic anhydride	108-31-6 203-571-6 607-096-00-9 01-2119472428-31, 01-2120759691-45	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Resp. Sens. 1; H334 Skin Sens. 1A; H317 STOT RE 1; H372 (Respiratory system, Inhalation) EUH071	< 0,001
		specific concentration limit Skin Sens. 1A; H317 >= 0,001 %	
Substances with a workp			
Silica gel, pptd., crystfre	e 112926-00-8		>= 1 - < 10

according to Regulation (EC) No. 1907/2006



DE / EN

Capadur UniversalLasur Teak

Version Revision Date: SDS Number: Date of last issue: 19.10.2020 3.0 16.03.2023 6007580 Date of first issue: 29.07.2019

231-545-4 01-2119379499-16, 01-2120105300-82

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice : Never give anything by mouth to an unconscious person.

If you feel unwell, seek medical advice (show the label where

possible).

Move out of dangerous area.

First aider needs to protect himself.

If inhaled : Call a physician.

If breathing is irregular or stopped, administer artificial respira-

tion.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

Move to fresh air.

In case of skin contact : Do NOT use solvents or thinners.

In case of contact, immediately flush skin with soap and plenty

of water.

Take off all contaminated clothing immediately.

In case of eye contact : If eye irritation persists: Get medical advice/ attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing.

If swallowed : Seek medical advice.

Clean mouth with water and drink afterwards plenty of water.

If swallowed, DO NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Risks : Repeated exposure may cause skin dryness or cracking.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No information available.

according to Regulation (EC) No. 1907/2006

DE / EN



Capadur UniversalLasur Teak

Version Revision Date: SDS Number: Date of last issue: 19.10.2020 3.0 16.03.2023 6007580 Date of first issue: 29.07.2019

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Use water spray, alcohol-resistant foam, dry chemical or car-

bon dioxide.

Do not use a solid water stream as it may scatter and spread

fire.

Unsuitable extinguishing

media

None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire

fighting

Cool closed containers exposed to fire with water spray. In case of fire hazardous decomposition products may be

produced such as:

Carbon monoxide, carbon dioxide and unburned hydrocar-

bons (smoke).

5.3 Advice for firefighters

Special protective equipment :

for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

Further information : Standard procedure for chemical fires.

In the event of fire and/or explosion do not breathe fumes.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Do not get in eyes, on skin, or on clothing.

When workers are facing concentrations above the exposure

limit they must use appropriate certified respirators.

Ensure adequate ventilation. Remove all sources of ignition.

6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Do not flush into surface water or sanitary sewer system.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Keep in suitable, closed containers for disposal.

according to Regulation (EC) No. 1907/2006

DE / EN



Capadur UniversalLasur Teak

Version Revision Date: SDS Number: Date of last issue: 19.10.2020 3.0 16.03.2023 6007580 Date of first issue: 29.07.2019

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

6.4 Reference to other sections

For further information see Section 7 of the safety data sheet.

, For personal protection see section 8., For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Non-sparking tools should be used.

For personal protection see section 8.

Avoid exceeding the given occupational exposure limits (see

section 8).

Provide sufficient air exchange and/or exhaust in work rooms.

In addition, the current technical information for this product and its application on www.caparol.com must be observed.

Advice on protection against

fire and explosion

Vapors may form explosive mixtures with air. Vapors are

heavier than air and may spread along floors. Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

Hygiene measures : Avoid contact with the skin and the eyes. Wash hands before

eating, drinking, or smoking. Do not eat, drink or smoke when using this product. Remove contaminated clothing and protec-

tive equipment before entering eating areas.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Store in original container. Store between 41 and 77 °F in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Storage class (TRGS 510) : 10

7.3 Specific end use(s)

Specific use(s) : This information is not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

according to Regulation (EC) No. 1907/2006



DE / EN

Capadur UniversalLasur Teak

Version Revision Date: SDS Number: Date of last issue: 19.10.2020 3.0 16.03.2023 6007580 Date of first issue: 29.07.2019

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Naphtha (petrole- um), hydrotreated heavy; Low boiling point ydrogen treated naphtha	64742-48-9	AGW	300 mg/m3	DE TRGS 900
	Peak-limit cat	egory: 2;(II)		
	Further inform	nation: Group exposi	ure limit for hydrocarbon solv	ent mixtures
Silica gel, pptd., crystfree	112926-00- 8	AGW (Inhalable fraction)	4 mg/m3 (Silica)	DE TRGS 900
	Further information: When there is compliance with the OEL and biological			
	tolerance values, there is no risk of harming the unborn child			
octhilinone (ISO)	26530-20-1	AGW (Inhalable	0,05 mg/m3	DE TRGS
		fraction)		900
	Peak-limit category: 2;(I)			
	Further information: Skin absorption, When there is compliance with the OEL			
	and biological	tolerance values, th	ere is no risk of harming the	unborn child
maleic anhydride	108-31-6	AGW (Vapour	0,02 ppm	DE TRGS
		and aerosols)	0,081 mg/m3	900
	Peak-limit category: 1; =2.5=(I)			
	Further information: In well-found cases also a momentary value can be es-			
	tablished, that never can be exceeded. This substance will be indicated by = =			
	in combination with an exceeding value., When there is compliance with the			
	OEL and biological tolerance values, there is no risk of harming the unborn			
	child, Substance sensitizing through the skin and respiratory system			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Routes of expo- sure	Potential health effects	Value
1-isopropyl-2,2- dimethyltrimethylene diisobutyrate	Consumers	Ingestion	Long-term systemic effects	18,80 mg/kg bw/day
	Consumers	Skin contact	Long-term systemic effects	18,80 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	32,60 mg/m3
	Workers	Inhalation	Long-term systemic effects	110,00 mg/m3
	Workers	Skin contact	Long-term systemic effects	31,20 mg/kg bw/day
2-methylpentane-2,4- diol	Consumers	Inhalation	Long-term local ef- fects	25,00 mg/m3
	Consumers	Inhalation	Long-term systemic effects	3,50 mg/m3
	Consumers	Ingestion	Long-term systemic effects	1,00 mg/kg bw/day
	Consumers	Inhalation	Acute local effects	49,00 mg/m3
	Consumers	Skin contact	Long-term systemic	1,00 mg/kg

according to Regulation (EC) No. 1907/2006

DE / EN



Capadur UniversalLasur Teak

Version Revision Date: SDS Number: Date of last issue: 19.10.2020 3.0 16.03.2023 6007580 Date of first issue: 29.07.2019

		1	effects	bw/day
	Workers	Inhalation	Acute local effects	98,00 mg/m3
	Workers	Inhalation	Long-term systemic effects	14,00 mg/m3
	Workers	Inhalation	Long-term local ef- fects	49,00 mg/m3
	Workers	Skin contact	Long-term systemic effects	2,00 mg/kg bw/day
maleic anhydride	Consumers	Inhalation	Long-term systemic effects	0,05 mg/m3
	Consumers	Ingestion	Long-term systemic effects	0,06 mg/kg bw/day
	Consumers	Ingestion	Acute systemic ef- fects	0,10 mg/kg bw/day
	Consumers	Skin contact	Acute systemic ef- fects	0,10 mg/kg bw/day
	Consumers	Inhalation	Long-term local ef- fects	0,08 mg/m3
	Consumers	Skin contact	Long-term systemic effects	0,10 mg/kg bw/day
	Workers	Inhalation	Acute systemic ef- fects	0,80 mg/m3
	Workers	Inhalation	Acute systemic ef- fects	0,95 mg/m3
	Workers	Inhalation	Acute local effects	0,80 mg/m3
	Workers	Inhalation	Long-term systemic effects	0,40 mg/m3
	Workers	Inhalation	Long-term systemic effects	0,19 mg/m3
	Workers	Inhalation	Long-term local ef- fects	0,40 mg/m3
	Workers	Inhalation	Long-term local ef- fects	0,32 mg/m3
	Workers	Skin contact	Acute systemic ef- fects	0,20 mg/kg bw/day
	Workers	Skin contact	Long-term systemic effects	0,20 mg/kg bw/day
	Consumers	Inhalation	Acute systemic ef- fects	

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
1-isopropyl-2,2- dimethyltrimethylene diisobutyr-	Sea water	0,0014 mg/l
ate		
	Sewage treatment plant	3 mg/l
	Sea sediment	0,529 mg/kg dry weight (d.w.)
	Secondary Poisoning	83,3 mg/kg food

according to Regulation (EC) No. 1907/2006



DE / EN

Capadur UniversalLasur Teak

Version Revision Date: SDS Number: Date of last issue: 19.10.2020 3.0 16.03.2023 6007580 Date of first issue: 29.07.2019

	Fresh water	0,014 mg/l
	Soil	1,05 mg/kg dry
		weight (d.w.)
	Fresh water sediment	5,29 mg/kg dry
		weight (d.w.)
2-methylpentane-2,4-diol	Soil	0,11 mg/kg dry
		weight (d.w.)
	Intermittent use/release	4,29 mg/l
	Secondary Poisoning	100 mg/kg food
	Fresh water sediment	1,79 mg/kg dry
		weight (d.w.)
	Sea water	0,0429 mg/l
	Sewage treatment plant	20 mg/l
	Sea sediment	0,179 mg/kg dry
		weight (d.w.)
	Fresh water	0,429 mg/l
maleic anhydride	Fresh water	0,075 mg/l
	Fresh water sediment	0,334 mg/kg dry
		weight (d.w.)
	Soil	0,0415 mg/kg dry
		weight (d.w.)
	Sea water	0,01 mg/l
	Intermittent use/release	0,4281 mg/l
	Sewage treatment plant	44,6 mg/l
	Soil	0,01 mg/kg dry
		weight (d.w.)
	Sea water	0,0075 mg/l
	Secondary Poisoning	6,67 mg/kg food
	Fresh water	0,1 mg/l
	Sewage treatment plant	4,46 mg/l
	Sea sediment	0,006 mg/kg dry
		weight (d.w.)
	Fresh water sediment	0,06 mg/kg dry
		weight (d.w.)
	Intermittent use/release	0,75 mg/l
	Sea sediment	0,0334 mg/kg dry
		weight (d.w.)

8.2 Exposure controls

Personal protective equipment

Eye/face protection : DGUV Regulation 112-192 - Use of eye and face protection

Goggles

Hand protection

Material : Nitrile rubber Glove thickness : 0,2 mm Protective index : Class 3

according to Regulation (EC) No. 1907/2006

DE / EN



Capadur UniversalLasur Teak

Version Revision Date: SDS Number: Date of last issue: 19.10.2020 3.0 16.03.2023 6007580 Date of first issue: 29.07.2019

Remarks : Gloves should be discarded and replaced if there is any indi-

cation of degradation or chemical breakthrough. Before removing gloves clean them with soap and water. Wear suita-

ble gloves tested to EN374.

DGUV Regulation 112-195 - Use of protective gloves

Skin and body protection : Safety shoes

Long sleeved clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Skin should be washed after contact.

During spray application: impervious clothing

Respiratory protection : Roller application or brushing: This product should not be

used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to

standard EN 14387) is used.

DGUV Regulation 112-190 - Use of breathing equipment

During spray application: Do not breathe spray dust. Use

A2/P2 combination filter for paint spraying.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid

Color : brown

Odor : characteristic

Odor Threshold : Not relevant

Melting point/freezing point : not determined

Boiling point/boiling range : not determined

Upper explosion limit / Upper

flammability limit

not determined

Lower explosion limit / Lower

flammability limit

not determined

according to Regulation (EC) No. 1907/2006

CAPAROL

DE / EN

Capadur UniversalLasur Teak

Version Revision Date: SDS Number: Date of last issue: 19.10.2020 3.0 16.03.2023 6007580 Date of first issue: 29.07.2019

Flash point : $> 60 \, ^{\circ}\text{C}$

Method: ISO 1523

Autoignition temperature : not determined

Decomposition temperature : Not applicable

pH : substance/mixture is non-soluble (in water)

Viscosity

Viscosity, dynamic : > 100 mPa.s (40 °C)

Method: ISO 3219

Viscosity, kinematic : >= 21 mm2/s (40 °C)

Flow time : Not applicable

Solubility(ies)

Water solubility : partly miscible

Partition coefficient: n-

octanol/water

: not determined

Vapor pressure : not determined

Relative density : not determined

Density : 0,935 g/cm3 (20 °C)

Method: DIN EN ISO 2811-1

Bulk density : Not applicable

Relative vapor density : Heavier than air.

9.2 Other information

Explosives : Not applicable

Oxidizing properties : Not applicable

Flammability (liquids) : Sustains combustion

Evaporation rate : Not applicable

according to Regulation (EC) No. 1907/2006

CAPAROL

DE / EN

Capadur UniversalLasur Teak

Version Revision Date: SDS Number: Date of last issue: 19.10.2020 3.0 16.03.2023 6007580 Date of first issue: 29.07.2019

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Vapors may form explosive mixture with air.

Hazardous decomposition products formed under fire condi-

tions.

10.4 Conditions to avoid

Conditions to avoid : Protect from frost, heat and sunlight.

10.5 Incompatible materials

Materials to avoid : Incompatible with acids and bases.

Incompatible with oxidizing agents.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

4,5-dichloro-2-octyl-2H-isothiazol-3-one:

Acute oral toxicity : Acute toxicity estimate: 567 mg/kg

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

Acute inhalation toxicity : Acute toxicity estimate: 0,16 mg/l

Test atmosphere: dust/mist

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

octhilinone (ISO):

Acute oral toxicity : Acute toxicity estimate: 125 mg/kg

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

according to Regulation (EC) No. 1907/2006

CAPAROL

DE / EN

Capadur UniversalLasur Teak

Version Revision Date: SDS Number: Date of last issue: 19.10.2020 3.0 16.03.2023 6007580 Date of first issue: 29.07.2019

Acute inhalation toxicity : Acute toxicity estimate: 0,27 mg/l

Test atmosphere: dust/mist

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

Acute dermal toxicity : Acute toxicity estimate: 311 mg/kg

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

maleic anhydride:

Acute oral toxicity : LD50 (Rat, male and female): 1.090 mg/kg

Method: OECD Test Guideline 401

Silica gel, pptd., cryst.-free:

Acute oral toxicity : LD50 Oral (Rat): > 10.000 mg/kg

Acute dermal toxicity : LD50 (Rat): > 5.000 mg/kg

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking

Components:

maleic anhydride:

Species : Rabbit

Assessment : Causes burns.

Serious eye damage/eye irritation

Not classified based on available information.

Components:

maleic anhydride:

Species : Rabbit

Assessment : Causes burns.

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Product:

Remarks : Not skin sensitising on the basis of the results of similar tested

mixtures, applying bridging principles in accordance with CLP Regulation Article 9(4). Result of studies: Sensitization OECD

according to Regulation (EC) No. 1907/2006

DE / EN



Capadur UniversalLasur Teak

Version Revision Date: SDS Number: Date of last issue: 19.10.2020 3.0 16.03.2023 6007580 Date of first issue: 29.07.2019

429 (LLNA) (mouse) not sensitizing

Components:

maleic anhydride:

Species : Rat

Result : Causes sensitization.

Germ cell mutagenicity

Not classified based on available information

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

4,5-dichloro-2-octyl-2H-isothiazol-3-one:

M-Factor (Acute aquatic tox- : 100

icity)

M-Factor (Chronic aquatic

toxicity)

100

according to Regulation (EC) No. 1907/2006



DE / EN

Capadur UniversalLasur Teak

Version Revision Date: SDS Number: Date of last issue: 19.10.2020 16.03.2023 6007580 Date of first issue: 29.07.2019 3.0

octhilinone (ISO):

M-Factor (Acute aquatic tox- : 100

icity)

M-Factor (Chronic aquatic 100

toxicity)

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

Components:

1-isopropyl-2,2-dimethyltrimethylene diisobutyrate:

: log Pow: 4,49 (25 °C) Partition coefficient: n-

octanol/water

octhilinone (ISO):

Partition coefficient: nlog Pow: 2,92

octanol/water Method: OECD Test Guideline 117

maleic anhydride:

Partition coefficient: nlog Pow: -2,61 (19,8 °C)

octanol/water pH: 4 - 9

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment This substance/mixture contains no components considered

> to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment The substance/mixture does not contain components consid-

> ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006



DE / EN

Capadur UniversalLasur Teak

Version Revision Date: SDS Number: Date of last issue: 19.10.2020 16.03.2023 6007580 Date of first issue: 29.07.2019 3.0

12.7 Other adverse effects

Product:

Additional ecological infor-

mation

Harmful to aquatic organisms, may cause long-term adverse

effects in the aquatic environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste should not be disposed of via wastewater.

Contaminated packaging Only completely emptied containers should be given for recy-

cling.

Waste Code used product

080112, waste paint and varnish other than those mentioned

in 08 01 11*

SECTION 14: Transport information

14.1 UN number or ID number

ADN Not regulated as a dangerous good **ADR** Not regulated as a dangerous good RID Not regulated as a dangerous good **IMDG** Not regulated as a dangerous good **IATA** Not regulated as a dangerous good

14.2 UN proper shipping name

ADN Not regulated as a dangerous good **ADR** Not regulated as a dangerous good RID Not regulated as a dangerous good **IMDG** Not regulated as a dangerous good IATA Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADN Not regulated as a dangerous good **ADR** Not regulated as a dangerous good **RID** Not regulated as a dangerous good

according to Regulation (EC) No. 1907/2006

DE / EN



Capadur UniversalLasur Teak

Version Revision Date: SDS Number: Date of last issue: 19.10.2020 3.0 16.03.2023 6007580 Date of first issue: 29.07.2019

IMDG : Not regulated as a dangerous goodIATA : Not regulated as a dangerous good

14.4 Packing group

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA (Cargo) : Not regulated as a dangerous good
IATA (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 3

REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59).

This product is a mixture and does not contain Substances of Very High Concern (SVHC) equal or above 0.1%. Therefore no advised uses have to be defined and no chemical safety assessment has to be generated.

ated.

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

: Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Not applicable

REACH - List of substances subject to authorisation

(Annex XIV)

: None

according to Regulation (EC) No. 1907/2006

DE / EN



Capadur UniversalLasur Teak

Version Revision Date: SDS Number: Date of last issue: 19.10.2020 3.0 16.03.2023 6007580 Date of first issue: 29.07.2019

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)

Water hazard class (Germa-

ny)

WGK 2 obviously hazardous to water

34

Classification according to AwSV, Annex 1 (5.2)

Product code for laquers and

paints / Giscode

: M-KH02F Solvent-based varnishes / wood glaze, aromatics

removed, active agents

. : BSL40 Coating materials, strongly solvent-based, aromatic-

free, classified

Volatile organic compounds : Directive 2004/42/EC

< 40 % < 370 g/l

Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

15.2 Chemical Safety Assessment

A Chemical Safety Assessment is not required for this mixture.

SECTION 16: Other information

Full text of H-Statements

H319

H301 Toxic if swallowed. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H311 Toxic in contact with skin. H314 Causes severe skin burns and eye damage. Causes skin irritation. H315 May cause an allergic skin reaction. H317 Causes serious eye damage. H318

Causes serious eye irritation.

according to Regulation (EC) No. 1907/2006



DE / EN

Capadur UniversalLasur Teak

Version	Revision Date:	SDS Number:	Date of last issue: 19.10.2020
3.0	16.03.2023	6007580	Date of first issue: 29.07.2019

H330 : Fatal if inhaled.

H334 : May cause allergy or asthma symptoms or breathing difficul-

ties if inhaled.

H361d : Suspected of damaging the unborn child.

H361f : Suspected of damaging fertility.

H372 : Causes damage to organs through prolonged or repeated

exposure.

H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.H412 : Harmful to aquatic life with long lasting effects.

EUH066 : Repeated exposure may cause skin dryness or cracking.

EUH071 : Corrosive to the respiratory tract.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard

Asp. Tox. : Aspiration hazard Eye Dam. : Serious eye damage

Eye Irrit. : Eye irritation

Repr. : Reproductive toxicity
Resp. Sens. : Respiratory sensitization

Skin Corr. : Skin corrosion
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitization

STOT RE : Specific target organ toxicity - repeated exposure

DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.

DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AllC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EMS - Emergency Schedule; ENCS - Existing and New Femical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Givil Aviation Organization; IECSC - Inventy and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; DSO - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Concentration and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance;

Further information

Other information:

No exposure scenario communication is required for this product according to REACH Regulation No. 1907/2006 EC.

Communication of Uses is not required in accordance with REACH Article 31(1)(a) - registered substances / mixtures do not meet the criteria for classification as hazardous in accordance with Regulations 1272/2008 EC or 1999/45/EC.

according to Regulation (EC) No. 1907/2006

DE / EN



Capadur UniversalLasur Teak

Version Revision Date: SDS Number: Date of last issue: 19.10.2020 3.0 16.03.2023 6007580 Date of first issue: 29.07.2019

Sources of key data used to compile the Material Safety Data Sheet:

ECHA WebSite

ACGIH (American Conference of Government Industrial Hygienists). 2014 TLVs and BEIs. Threshold Limit Values (TLVs) for chemical substances and physical agents and Biological Exposure Indices (BEIs) with Seventh Edition documentation. 2014 ACGIH, Cincinnati OH

NIOSH - Registry of toxic effects of chemical substances

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX'S - Dangerous properties of industrial materials

GESTIS - Database on hazardous substances - Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA, Institute for Occupational Safety and Health of the German Social Accident Insurance)

Toxnet - Toxicology Data Network

Classification of the mixture:

Classification procedure:

Aquatic Chronic 3 H412 Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

REACH Information

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our upstream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly.

DE / EN