

Capadur UniversalLasur Kalkweiß				
Version 3.0	Revision Date: 23.01.2024	SDS Number: 6007582	Date of last issue: 14.03.2023 Date of first issue: 29.07.2019	

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier		
Trade name	:	Capadur UniversalLasur Kalkweiß
1.2 Relevant identified uses of	of the s	ubstance or mixture and uses advised against
Use of the Sub- stance/Mixture	:	Solvent-borne coatings
Recommended restrictions on use	<b>3</b> :	within adequate application - none
1.3 Details of the supplier of t	the saf	ety data sheet
Company	:	Caparol Farben Lacke GmbH Roßdörfer Straße 50

Telephone Telefax	Roßdörfer Straße 50 64372 Ober-Ramstadt : +496154710 : +4961547170222
Website E-mail address Responsi- ble/issuing person	: : msds@dr-rmi.com

#### 1.4 Emergency telephone

Emergency telephone 1	: +49613284463 GBK Gmb	Н
-----------------------	------------------------	---

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

#### Classification (REGULATION (EC) No 1272/2008)

Skin sensitization, Category 1	H317: May cause an allergic skin reaction.
Long-term (chronic) aquatic hazard, Cat-	H412: Harmful to aquatic life with long lasting ef-
egory 3	fects.

#### 2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Capadı	ur UniversalLas	sur	Kalkweiß	
/ersion 3.0	Revision Date: 23.01.2024	-	DS Number: 007582	Date of last issue: 14.03.2023 Date of first issue: 29.07.2019
Hazaı	rd pictograms	:		
Signa	l Word	:	Warning	
Hazaı	rd Statements	:		e an allergic skin reaction. Daquatic life with long lasting effects.
	emental Hazard ments	:	EUH066 dryness or crackir	Repeated exposure may cause skin ng.
Preca	Precautionary Statements		label at hand.	advice is needed, have product container o of reach of children.
			Prevention:	
			P273 Avoid rele	athing mist or vapors. ease to the environment. ective gloves.
			Disposal:	
			P501 Dispose o disposal plant.	f contents/ container to an approved waste

#### Hazardous ingredients which must be listed on the label:

Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6pentamethyl-4-piperidyl sebacate 4,5-dichloro-2-octyl-2H-isothiazol-3-one octhilinone (ISO)

#### **Additional Labeling**

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.



# Capadur UniversalLasur Kalkweiß

Version	Revision Date:	SDS Number:	Date of last issue: 14.03.2023
3.0	23.01.2024	6007582	Date of first issue: 29.07.2019

# **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

.

Chemical nature : Alkyd-resin-based wood varnish, solvent-containing, with film protection

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Naphtha (petroleum), hydrotreat- ed heavy; Low boiling point ydro- gen treated naphtha	64742-48-9 265-150-3 649-327-00-6 01-2119457273-39, 01-2119463258-33, 01-2119486659-16	Asp. Tox. 1; H304 EUH066	>= 30 - < 50
titanium dioxide; [in powder form containing 1 % or more of parti- cles with aerodynamic diameter ≤ 10 µm]	13463-67-7 236-675-5 022-006-00-2 01-2119489379-17	Carc. 2; H351	>= 10 - < 20
1-isopropyl-2,2- dimethyltrimethylene diisobutyrate	6846-50-0 229-934-9 01-2119451093-47	Repr. 2; H361d Aquatic Chronic 3; H412	>= 1 - < 2,5
Reaction mass of bis(1,2,2,6,6- pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl- 4-piperidyl sebacate	1065336-91-5 915-687-0 01-2119491304-40	Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 Repr. 2; H361f	>= 0,1 - < 0,25
4,5-dichloro-2-octyl-2H-isothiazol- 3-one	64359-81-5 264-843-8 613-335-00-8	Acute Tox. 4; H302 Acute Tox. 2; H330 Skin Corr. 1; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071	>= 0,0025 - < 0,025
		M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic	

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

ersion Revision Date:		SDS Number:	Date of last issue: 14.03.2023			
.0 23.01.2024		6007582	Date of first issue: 29.07.2019			
octhil	inone (ISO)	26530-20-1 247-761-7 613-112-00-5 01-21207689	· · · · · · · · · · · · · · · · · · ·			



# Capadur UniversalLasur Kalkweiß

ersion	Revision Date: 23.01.2024	SDS Number: 6007582	Date of last issue: 14.03.2023 Date of first issue: 29.07.2019
J	23.01.2024	6007582	Date of first issue. 29.07.2019
			Acute oral toxicity: 125 mg/kg Acute inhalation tox- icity (dust/mist): 0,27 mg/l Acute dermal toxicity: 311 mg/kg
Subs	tances with a workplae	ce exposure limit :	
Silica	gel, pptd., crystfree	112926-00-8	>= 1 - < 10
		231-545-4	
		01-21193794	99-16,
		01-21201053	00-82

For explanation of abbreviations see section 16.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first-aid measures

General advice	:	Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). Move out of dangerous area. First aider needs to protect himself.
If inhaled	:	Call a physician. If breathing is irregular or stopped, administer artificial respira- tion. If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician. Move to fresh air.
In case of skin contact	:	Do NOT use solvents or thinners. In case of contact, immediately flush skin with soap and plenty of water. Take off all contaminated clothing immediately.
In case of eye contact	:	If eye irritation persists: Get medical advice/ attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If swallowed	:	Seek medical advice. Clean mouth with water and drink afterwards plenty of water. If swallowed, DO NOT induce vomiting.

#### 4.2 Most important symptoms and effects, both acute and delayed



Version	Revision Date:	SE	S Number:	Date of last issue: 14.03.2023			
3.0	23.01.2024	60	07582	Date of first issue: 29.07.2019			
Risks		: May cause an allergic skin reaction. Repeated exposure may cause skin dryness or cracking.					
4.3 Indica	tion of any immediate	meo	lical attention a	and special treatment needed			
Treat	ment	:	No information	available.			
SECTION	1 5: Firefighting meas	sur	es				
5.1 Exting	uishing media						
Suitable extinguishing media		:	Use extinguishing measures that are appropriate to local ci cumstances and the surrounding environment. Use water spray, alcohol-resistant foam, dry chemical or ca bon dioxide. Do not use a solid water stream as it may scatter and sprea fire.				
Unsu media	itable extinguishing a	: None known.					
5.2 Specia	al hazards arising from	the	substance or	mixture			
Speci fightir	fic hazards during fire	:	In case of fire I produced such	ntainers exposed to fire with water spray. nazardous decomposition products may be as: ide, carbon dioxide and unburned hydrocar-			
5.3 Advice	e for firefighters						
	al protective equipment e-fighters	: In the event of fire, wear self-contained breathing apparatus.					
Furth	Further information : Standard procedure for chemical fires. In the event of fire and/or explosion do not breathe fu						

6.1 Personal precautions, protect	tive equipment and emergency procedures
Personal precautions	<ul> <li>Do not get in eyes, on skin, or on clothing.</li> <li>When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.</li> <li>Ensure adequate ventilation.</li> <li>Remove all sources of ignition.</li> </ul>



Version 3.0	Revision Date: 23.01.2024	SDS Number: 6007582	Date of last issue: 14.03.2023 Date of first issue: 29.07.2019
0.0	20.01.2021	0001002	
6.2 Envir	onmental precautions		
Envi	ronmental precautions	If the product respective aut	er leakage or spillage if safe to do so. contaminates rivers and lakes or drains inform chorities. nto surface water or sanitary sewer system.
6.3 Metho	ods and material for co	ontainment and cle	aning up
Meth	ods for cleaning up	Soak up with	ble, closed containers for disposal. inert absorbent material (e.g. sand, silica gel, niversal binder, sawdust).
	N 7: Handling and st	•	
	utions for safe handling	•	
Advi	ce on safe handling	For personal p Avoid exceed section 8).	tools should be used. protection see section 8. ing the given occupational exposure limits (see ient air exchange and/or exhaust in work rooms
			e current technical information for this product ation on www.caparol.com must be observed.
	ce on protection against Ind explosion		orm explosive mixtures with air. Vapors are air and may spread along floors. Keep away fro
iiie a		heat, hot surfa sources. No s	aces, sparks, open flames and other ignition moking.

Hygiene measures: Avoid contact with the skin and the eyes. Wash hands before<br/>eating, drinking, or smoking. Do not eat, drink or smoke when<br/>using this product. Remove contaminated clothing and protec-<br/>tive equipment before entering eating areas.

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers	:	Store in original container. Store between 41 and 77 °F in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Storage class (TRGS 510)	:	10

7.3 Specific end use(s)



# Capadur UniversalLasur Kalkweiß

3.0         23.01.2024         6007582         Date of first issue: 29.07.2019	Version 3.0	Revision Date: 23.01.2024	SDS Number: 6007582	Date of last issue: 14.03.2023 Date of first issue: 29.07.2019	
--	----------------	---------------------------	------------------------	---	--

Specific use(s)

: This information is not available.

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis	
Naphtha (petrole- um), hydrotreated heavy; Low boiling point ydrogen treated naphtha	64742-48-9	AGW	300 mg/m3	DE TRGS 900	
	Peak-limit cat				
	Further inform	ation: Group exposu	ure limit for hydrocarbon solv	ent mixtures	
titanium dioxide; [in powder form con- taining 1 % or more of particles with aerodynamic diameter $\leq$ 10 µm]	13463-67-7	AGW (Inhalable fraction)	10 mg/m3 (Titanium dioxide)	DE TRGS 900	
	Peak-limit category: 2;(II) Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child				
	AGW (Alveolate 1,25 mg/m3 DE TRG fraction) (Titanium dioxide) 900				
	Peak-limit category: 2;(II) Further information: When there is compliance with the OEL and biologi tolerance values, there is no risk of harming the unborn child				
		BM (Alveolar dust fraction)	0,5 mg/m3	DE TRGS 527	
Silica gel, pptd., crystfree	112926-00- 8	AGW (Inhalable fraction)	4 mg/m3 (Silica)	DE TRGS 900	
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child				
octhilinone (ISO)	26530-20-1	AGW (Inhalable fraction)	0,05 mg/m3	DE TRGS 900	
	Peak-limit cat	egory: 2;(I)			
	Further information: Skin absorption, When there is compliance with the OE and biological tolerance values, there is no risk of harming the unborn child				

#### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Routes of expo- sure	Potential health ef- fects	Value
titanium dioxide; [in powder form contain-	Consumers	Ingestion	Long-term systemic effects	700,00 mg/kg bw/day

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

sion	Revision Date: 23.01.2024	SDS Nur 6007582		e of last issue: 14.03.2023 of first issue: 29.07.2019	
particl	% or more of es with aerody- adiameter ≤ 10				
		Workers	Inhalation	Long-term local ef- fects	10,00 mg/m
dimet	propyl-2,2- hyltrimethylene utyrate	Consumers	Ingestion	Long-term systemic effects	18,80 mg/kg bw/day
		Consumers	Skin contact	Long-term systemic effects	18,80 mg/kg bw/day
		Consumers	Inhalation	Long-term systemic effects	32,60 mg/m
		Workers	Inhalation	Long-term systemic effects	110,00 mg/r
		Workers	Skin contact	Long-term systemic effects	31,20 mg/kg bw/day
bis(1,2 pentar piperio and m pentar	ion mass of 2,2,6,6- methyl-4- dyl) sebacate nethyl 1,2,2,6,6- methyl-4- dyl sebacate	Consumers	Inhalation	Acute local effects	0,58 mg/m3
		Consumers	Ingestion	Long-term systemic effects	1,25 mg/kg bw/day
		Consumers	Inhalation	Long-term systemic effects	0,58 mg/m3
		Consumers	Inhalation	Acute systemic ef- fects	0,58 mg/m3
		Consumers	Skin contact	Long-term systemic effects	1,25 mg/kg bw/day
		Consumers	Skin contact	Acute systemic ef- fects	1,25 mg/kg bw/day
		Consumers	Ingestion	Acute systemic ef- fects	1,25 mg/kg bw/day
		Workers	Inhalation	Acute systemic ef- fects	2,35 mg/m3
		Workers	Inhalation	Acute local effects	2,35 mg/m3
		Workers	Inhalation	Long-term systemic effects	2,35 mg/m3
		Workers	Skin contact	Acute systemic ef- fects	2,50 mg/kg bw/day
		Workers	Skin contact	Long-term systemic effects	2,50 mg/kg bw/day

#### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substa	nce name	Environmental Compartment	Value
titaniur	n dioxide; [in powder form	Sewage treatment plant	100 mg/l

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

ersion )		SDS Number: 6007582	Date of last issue: Date of first issue:	
	ining 1 % or more of parti- vith aerodynamic diamete n]			
		Fresh water		0,184 mg/l
		Soil		100 mg/kg dry weight (d.w.)
		Sea water		0,0184 mg/l
		Fresh water	sediment	1000 mg/kg dry weight (d.w.)
		Sea sedimer	nt	100 mg/kg dry weight (d.w.)
		Intermittent u	use/release	0,193 mg/l
1-isopropyl-2,2- dimethyltrimethylene diisobutyr- ate		- Sea water		0,0014 mg/l
		Sewage trea	tment plant	3 mg/l
		Sea sedimer	nt	0,529 mg/kg dr weight (d.w.)
		Secondary F	oisoning	83,3 mg/kg foo
		Fresh water		0,014 mg/l
		Soil		1,05 mg/kg dry weight (d.w.)
		Fresh water	sediment	5,29 mg/kg dry weight (d.w.)
Reaction mass of bis(1,2,2,6,6- pentamethyl-4-piperidyl) seba- cate and methyl 1,2,2,6,6- pentamethyl-4-piperidyl sebacate				0,00022 mg/l
		Soil		0,21 mg/kg dry weight (d.w.)
		Fresh water		0,0022 mg/l
		Sewage trea	tment plant	1 mg/l
		Fresh water		1,05 mg/kg dry weight (d.w.)
		Intermittent u	use/release	0,009 mg/l
		Sea sedimer	nt	0,11 mg/kg dry weight (d.w.)

#### 8.2 Exposure controls

#### Personal protective equipment

Eye/face protection

: DGUV Regulation 112-192 - Use of eye and face protection

Goggles

Hand protection	
Material	: Nitrile rubber
Glove thickness	: 0,2 mm
Protective index	: Class 3



Capad	ur UniversalLas	sur Kalkweiß					
Version 3.0	Revision Date: 23.01.2024	SDS Number: 6007582	Date of last issue: 14.03.2023 Date of first issue: 29.07.2019				
Remarks		cation of degr moving gloves ble gloves tes	Gloves should be discarded and replaced if there is any indi- cation of degradation or chemical breakthrough. Before re- moving gloves clean them with soap and water. Wear suita- ble gloves tested to EN374. DGUV Regulation 112-195 - Use of protective gloves				
Skin a	Skin and body protection		clothing				
			protection according to the amount and con- he dangerous substance at the work place.				
		Skin should b	e washed after contact.				
			wash contaminated clothing before re-use. application: impervious clothing				
Respiratory protection :		used under co mask with an	tion or brushing: This product should not be onditions of poor ventilation unless a protective appropriate gas filter (i.e. type A1 according to 14387) is used.				
		DGUV Regula	ation 112-190 - Use of breathing equipment				
		0, ,	application: Do not breathe spray dust. Use nation filter for paint spraying.				

# **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Boiling point/boiling range	:	not determined
Melting point/freezing point	:	not determined
Odor Threshold	:	Not relevant
Odor	:	characteristic
Color	:	white
Physical state	:	liquid



Capad	Capadur UniversalLasur Kalkweiß					
Version 3.0	Revision Date: 23.01.2024	SD	S Number: )7582	Date of last issue: 14.03.2023 Date of first issue: 29.07.2019		
	er explosion limit / Upper mability limit	:	not determined			
	Lower explosion limit / Lower flammability limit		not determined			
Flasl	n point	:	> 60 °C Method: ISO 152	3		
Auto	ignition temperature	:	not determined			
Deco	omposition temperature	:	Not applicable			
рН		:	substance/mixtu	e is non-soluble (in water)		
Visco V	osity iscosity, dynamic	:	> 100 mPa.s (40 Method: ISO 321			
V	iscosity, kinematic	:	>= 21 mm2/s (40	°C)		
Flow	time	:	Not applicable			
	bility(ies) /ater solubility	:	partly miscible			
	tion coefficient: n- nol/water	:	not determined			
Vapo	or pressure	:	not determined			
Rela	tive density	:	not determined			
Dens	sity	:	1,1 g/cm3 (20 °C Method: DIN EN	) ISO 2811-1		



Cap	Capadur UniversalLasur Kalkweiß						
Versio 3.0	on	Revision Date: 23.01.2024		S Number: 07582	Date of last issue: 14.03.2023 Date of first issue: 29.07.2019		
5.0		23.01.2024	00	01302	Date of first 13506. 23.07.2013		
E	Bulk de	ensity	:	Not applicable			
F	Relative	e vapor density	:	Heavier than air.			
920	ther in	formation					
	Explosi		:	Not applicable			
C	Oxidizir	ng properties	:	Not applicable			
F	Flamma	ability (liquids)	:	Sustains combu	stion		
E	Evapor	ation rate	:	Not applicable			

#### **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No decomposition if stored and applied as directed.

#### 10.2 Chemical stability

No decomposition if stored and applied as directed.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions	<ul> <li>Vapors may form explosive mixture with air. Hazardous decomposition products formed under fire cond tions.</li> </ul>	i-
10.4 Conditions to avoid		
Conditions to avoid	: Protect from frost, heat and sunlight.	
10.5 Incompatible materials		

#### Materials to avoid : Incompatible with acids and bases. Incompatible with oxidizing agents.

#### **10.6 Hazardous decomposition products**

No decomposition if stored and applied as directed.



Capadur UniversalLasur Kalkweiß							
Version	Revision Date: 23.01.2024	SDS Number:	Date of last issue: 14.03.2023				
3.0		6007582	Date of first issue: 29.07.2019				

#### **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity								
Not classified based on available information.								
Components:	Components:							
4,5-dichloro-2-octyl-2H-isothiazol-3-one:								
Acute oral toxicity	:	Acute toxicity estimate: 567 mg/kg Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008						
Acute inhalation toxicity	:	Acute toxicity estimate: 0,16 mg/l Test atmosphere: dust/mist Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008						
octhilinone (ISO):								
Acute oral toxicity	:	Acute toxicity estimate: 125 mg/kg Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008						
Acute inhalation toxicity	:	Acute toxicity estimate: 0,27 mg/l Test atmosphere: dust/mist Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008						
Acute dermal toxicity	:	Acute toxicity estimate: 311 mg/kg Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008						
Silica gel, pptd., crystfree								
Acute oral toxicity	:	LD50 Oral (Rat): > 10.000 mg/kg						
Acute dermal toxicity	:	LD50 (Rat): > 5.000 mg/kg						
Skin corrosion/irritation								
Repeated exposure may cause	se s	kin dryness or cracking.						
Serious eye damage/eye irritation								

Not classified based on available information.



Capad	ur UniversalLa	sur Kalkweiß						
Version	Revision Date:	SDS Number:	Date of last issue: 14.03.2023					
3.0	23.01.2024	6007582	Date of first issue: 29.07.2019					
Resr	piratory or skin sensi	itization						
Skin sensitization								
May cause an allergic skin reaction.								
	biratory sensitization							
	classified based on ava							
	n cell mutagenicity	ailable information						
	classified based on ava							
	inogenicity							
Not c	Not classified based on available information.							
	oductive toxicity							
Not c	Not classified based on available information.							
STO	T-single exposure							
Not o	lassified based on ava	ailable information.						
STO	T-repeated exposure	•						
Not o	lassified based on ava	ailable information.						
Aspi	ration toxicity							
•	lassified based on ava	ailable information.						
	11.2 Information on other hazards							
Endo	ocrine disrupting pro	perties						
Prod	luct:							
Asse	ssment		mixture does not contain components consid-					

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### **SECTION 12: Ecological information**

#### 12.1 Toxicity

**Components:** 

4,5-dichloro-2-octyl-2H-isothiazol-3-one:

M-Factor (Acute aquatic tox- : 100 icity) M-Factor (Chronic aquatic : 100 toxicity)



Capad	ur UniversalLas	ur Kalkweiß	
Version 3.0	Revision Date: 23.01.2024	SDS Number: 6007582	Date of last issue: 14.03.2023 Date of first issue: 29.07.2019
	linone (ISO): ctor (Acute aquatic tox-	: 100	
icity)		. 100	
	M-Factor (Chronic aquatic toxicity)		
	i <b>stence and degradabi</b> ata available	lity	
12.3 Bioa	ccumulative potential		
Com	ponents:		
Naph	tha (petroleum), hydro	otreated heavy;	Low boiling point ydrogen treated naphtha:
	ion coefficient: n- ol/water	: log Pow: 1,9 pH: 7	99 - 18,02 (20 °C)
1-iso	propyl-2,2-dimethyltrii	methylene diisol	putyrate:
	ion coefficient: n- ol/water	: log Pow: 4,	49 (25 °C)
	tion mass of bis(1,2,2, amethyl-4-piperidyl se		-4-piperidyl) sebacate and methyl 1,2,2,6,6-
	ion coefficient: n- ol/water	: log Pow: 2, pH: 7,0	37 - 2,77 (25 °C)
octhi	linone (ISO):		
	ion coefficient: n- ol/water	: log Pow: 2, pH: 7	61 (25 °C)
	lity in soil		
	ata available		
12.5 Resu	ilts of PBT and vPvB a	issessment	
Prod		<b>-</b>	
Asse	ssment	to be either	nce/mixture contains no components considered persistent, bioaccumulative and toxic (PBT), or ent and very bioaccumulative (vPvB) at levels of her.
12.6 Endo	ocrine disrupting prop	erties	
Prod	uct:		
Asse	ssment	: The substa	nce/mixture does not contain components consid-



3.0

# Capadur UniversalLasur Kalkweiß Version Revision Date: SDS Number: Date of last issue: 14.03.2023

6007582 Date of first issue: 29.07.2019 ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation

(EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

#### 12.7 Other adverse effects

23.01.2024

#### Product:

•	aquatic organisms, may cause long-term adverse ne aquatic environment.
---	--

levels of 0.1% or higher.

#### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product	:	
		Waste should not be disposed of via wastewater.
Contaminated packaging	:	Only completely emptied containers should be given for recy- cling.
Waste Code	:	used product 080112, waste paint and varnish other than those mentioned in 08 01 11*

#### **SECTION 14: Transport information**

#### 14.1 UN number or ID number ADN : Not regulated as a dangerous good ADR Not regulated as a dangerous good : RID Not regulated as a dangerous good : IMDG Not regulated as a dangerous good ΙΑΤΑ Not regulated as a dangerous good : 14.2 UN proper shipping name ADN : Not regulated as a dangerous good ADR Not regulated as a dangerous good : RID Not regulated as a dangerous good 5 IMDG Not regulated as a dangerous good 5 ΙΑΤΑ Not regulated as a dangerous good 1



Version	ur UniversalLa Revision Date:	SDS Number:	Date of last issue: 14.03.2023				
3.0	23.01.2024	6007582	Date of first issue: 29.07.2019				
14.3 Tran	sport hazard class(e	s)					
ADN		: Not regulated	l as a dangerous good				
ADR		: Not regulated	l as a dangerous good				
RID		: Not regulated	l as a dangerous good				
IMDO	3	: Not regulated	l as a dangerous good				
ΙΑΤΑ		: Not regulated	l as a dangerous good				
14.4 Pack	king group						
ADN		: Not regulated	l as a dangerous good				
ADR		: Not regulated	l as a dangerous good				
RID		: Not regulated	l as a dangerous good				
IMDO	6	: Not regulated	l as a dangerous good				
ΙΑΤΑ	(Cargo)	: Not regulated	: Not regulated as a dangerous good				
ΙΑΤΑ	(Passenger)	: Not regulated	l as a dangerous good				
-	ronmental hazards egulated as a dangero	ous good					
-	cial precautions for u	ser					
14.7 Mari	time transport in bul	k according to IMO	instruments				
Not a	pplicable for product a	as supplied.					
SECTIO	N 15: Regulatory in	formation					
0201101		lonnation					
15.1 Safe ture	ty, health and enviro	nmental regulations	s/legislation specific for the substance or mix-				
REA the m	CH - Restrictions on the narket and use of certa and articles (Anne	in dangerous substa					
			If you intend to use this product as tattoo ink, please contact your ven- dor.				
	CH - Candidate List of ern for Authorization (	-	High : This product is a mixture and does not contain Substances of Very High				

Concern (SVHC) equal or above 0.1%. Therefore no advised uses have to be defined and no chemical safety assessment has to be gener-

ated.



Ca	padu	r UniversalLası	ır	Kalkweiß					
	sion	Revision Date: 23.01.2024	S	DS Number: 07582		te of last issue: 14 te of first issue: 29			
		tion (EC) No 1005/200 e ozone layer	9 o	n substances that c	de-	: Not applicabl	e		
	Regulation (EU) 2019/1021 on persistent organic pollu- : Not applicable tants (recast)								
	REACH - List of substances subject to authorisation : None (Annex XIV)								
	pean P control	9 III: Directive 2012/18/ arliament and of the C of major-accident haza ous substances.	oun	cil on the		Petroleum produc and naphthas, (b) (including jet fuels (including diesel f heating oils and g streams),(d) heav alternative fuels s purposes and with ties as regards fla environmental has products referred to (d)	kerosenes s), (c) gas oils uels, home gas oil blending ty fuel oils (e) erving the same n similar proper- ammability and zards as the		
	Water I ny)	nazard class (Germa-	:	WGK 2 obviously Classification acc		ardous to water ng to AwSV, Anne>	(1 (5.2)		
		t code for laquers and Giscode	:	M-KH02F Solvent removed, active a			od glaze, aromatics		
			:	BSL40 Coating m free, classified	ateri	als, strongly solve	nt-based, aromatic-		
	Volatile	organic compounds	:	emissions (integra	ated	of 24 November 2 pollution preventic ounds (VOC) conte	on and control)		
	Volatile	organic compounds	:	Directive 2004/42 < 33 % < 360 g/l	2/EC				

#### Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.



# Capadur UniversalLasur Kalkweiß

Version	Revision Date:	SDS Number:	Date of last issue: 14.03.2023
3.0	23.01.2024	6007582	Date of first issue: 29.07.2019

#### **15.2 Chemical Safety Assessment**

A Chemical Safety Assessment is not required for this mixture.

#### **SECTION 16: Other information**

#### **Full text of H-Statements**

H301	:	Toxic if swallowed.
H302	:	Harmful if swallowed.
H304	:	May be fatal if swallowed and enters airways.
H311	:	Toxic in contact with skin.
H314	:	Causes severe skin burns and eye damage.
H317	:	May cause an allergic skin reaction.
H318	:	Causes serious eye damage.
H330	:	Fatal if inhaled.
H351	:	Suspected of causing cancer if inhaled.
H361d	:	Suspected of damaging the unborn child.
H361f	:	Suspected of damaging fertility.
H400	:	Very toxic to aquatic life.
H410	:	Very toxic to aquatic life with long lasting effects.
H412	:	Harmful to aquatic life with long lasting effects.
EUH066	:	Repeated exposure may cause skin dryness or cracking.
EUH071	:	Corrosive to the respiratory tract.

#### Full text of other abbreviations

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECX - Concentration associated with %' response; ELX - Loading rate associated with %' response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCX - Concentration associated with %' growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equiptory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Miritime Organization; IESC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Convention; IESC - Lental Concentration; IESC - Lethal Concentration to 50 % of a test population; LDS0 - Lethal Dose to 50% of a test population (KECI - Korea Existing Chemical Suventory; LC50 - Lethal Concentration from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIOC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Of-



# Capadur UniversalLasur Kalkweiß

Version	Revision Date:	SDS Number:	Date of last issue: 14.03.2023
3.0	23.01.2024	6007582	Date of first issue: 29.07.2019

fice of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemicals Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

#### Further information

#### Other information:

No exposure scenario communication is required for this product according to REACH Regulation No. 1907/2006 EC.

Communication of Uses is not required in accordance with REACH Article 31(1)(a) - registered substances / mixtures do not meet the criteria for classification as hazardous in accordance with Regulations 1272/2008 EC or 1999/45/EC.

#### Sources of key data used to compile the Material Safety Data Sheet:

ECHA WebSite

ACGIH (American Conference of Government Industrial Hygienists). 2014 TLVs and BEIs. Threshold Limit Values (TLVs) for chemical substances and physical agents and Biological Exposure Indices (BEIs) with Seventh Edition documentation. 2014 ACGIH, Cincinnati OH NIOSH - Registry of toxic effects of chemical substances

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX'S - Dangerous properties of industrial materials

GESTIS - Database on hazardous substances - Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA, Institute for Occupational Safety and Health of the German Social Accident Insurance)

Toxnet - Toxicology Data Network

Classification of the m	ixture:	Classification procedure:
Skin Sens. 1	H317	Calculation method
Aquatic Chronic 3	H412	Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.



# Capadur UniversalLasur Kalkweiß

Version	Revision Date:	SDS Number:	Date of last issue: 14.03.2023
3.0	23.01.2024	6007582	Date of first issue: 29.07.2019

#### **REACH Information**

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our upstream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly.

DE / EN