

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capatect ThermoSan Fassadenputz NQG K40

Version	Revision Date:	Print Date	Date of last issue: 20.02.2020
2.0	05.02.2021	09.02.2021	Date of first issue: 20.02.2020

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Capatect ThermoSan Fassadenputz NQG K40

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-  
stance/Mixture : Water-borne coatings

Recommended restrictions : within adequate application - none  
on use

#### 1.3 Details of the supplier of the safety data sheet

Company : Caparol Farben Lacke GmbH  
Roßdörfer Straße 50  
64372 Ober-Ramstadt

Telephone : +496154710  
Telefax : +4961547170222  
E-mail address Responsible/issuing person : msds@dr-rmi.com

#### 1.4 Emergency telephone number

Emergency telephone number 1 : +49613284463 GBK GmbH

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

Precautionary statements : P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.

##### Additional Labelling

**|| EUH211** Warning! Hazardous respirable droplets may be formed when sprayed. Do not

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capatect ThermoSan Fassadenputz NQG K40

Version 2.0      Revision Date: 05.02.2021      Print Date 09.02.2021      Date of last issue: 20.02.2020  
Date of first issue: 20.02.2020

breathe spray or mist.

**EUH208**

Contains reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). **May produce an allergic reaction.**

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
titanium dioxide	13463-67-7 236-675-5 022-006-00-2 01-2119489379-17	Carc. 2; H351	>= 1 - < 10
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	55965-84-9 613-167-00-5 01-2120764691-48	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 2; H310 Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410  M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100	>= 0,0002 - < 0,0015
Substances with a workplace exposure limit :			
Kieselguhr, soda ash flux-calcined	68855-54-9 272-489-0 21-2119488518-22		>= 1 - < 10

For explanation of abbreviations see section 16.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capatect ThermoSan Fassadenputz NQG K40

Version	Revision Date:	Print Date	Date of last issue: 20.02.2020
2.0	05.02.2021	09.02.2021	Date of first issue: 20.02.2020

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : Never give anything by mouth to an unconscious person.  
If you feel unwell, seek medical advice (show the label where possible).  
Move out of dangerous area.  
First aider needs to protect himself.
- If inhaled : Move to fresh air.
- In case of skin contact : Take off all contaminated clothing immediately.  
Do NOT use solvents or thinners.  
In case of contact, immediately flush skin with soap and plenty of water.
- In case of eye contact : If eye irritation persists: Get medical advice/ attention.  
IF IN EYES: Rinse cautiously with water for several minutes.  
Remove contact lenses, if present and easy to do. Continue rinsing.
- If swallowed : Seek medical advice.  
Clean mouth with water and drink afterwards plenty of water.  
If swallowed, DO NOT induce vomiting.

#### 4.2 Most important symptoms and effects, both acute and delayed

None known.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No information available.

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

- Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.  
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Unsuitable extinguishing media : None known.

#### 5.2 Special hazards arising from the substance or mixture

- Specific hazards during fire-fighting : In case of fire hazardous decomposition products may be produced such as:  
Carbon monoxide, carbon dioxide and unburned hydrocar-

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capatect ThermoSan Fassadenputz NQG K40

Version	Revision Date:	Print Date	Date of last issue: 20.02.2020
2.0	05.02.2021	09.02.2021	Date of first issue: 20.02.2020

bons (smoke).

### 5.3 Advice for firefighters

- Special protective equipment : Wear self-contained breathing apparatus for firefighting if necessary for firefighters
- Further information : Use water spray to cool unopened containers. Standard procedure for chemical fires. The product itself does not burn.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- Personal precautions : Use protective shoes or boots with rough rubber sole. Material can create slippery conditions. Do not get in eyes, on skin, or on clothing.

### 6.2 Environmental precautions

- Environmental precautions : Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities. Do not flush into surface water or sanitary sewer system.

### 6.3 Methods and material for containment and cleaning up

- Methods for cleaning up : Keep in suitable, closed containers for disposal. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

### 6.4 Reference to other sections

For further information see Section 7 of the safety data sheet.  
,For personal protection see section 8.,For disposal considerations see section 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

- Advice on safe handling : Use only with adequate ventilation. For personal protection see section 8. No special technical protective measures required.
- In addition, the current technical information for this product and its application on [www.caparol.com](http://www.caparol.com) must be observed.
- Hygiene measures : Wash hands before eating, drinking, or smoking. Do not eat, drink or smoke when using this product.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capatect ThermoSan Fassadenputz NQG K40

Version	Revision Date:	Print Date	Date of last issue: 20.02.2020
2.0	05.02.2021	09.02.2021	Date of first issue: 20.02.2020

### 7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Perishable if frozen. To maintain product quality, do not store in heat or direct sunlight. Store at room temperature in the original container. Containers which are opened must be carefully resealed and kept upright to prevent leakage.
- Advice on common storage : Keep away from oxidizing agents and strongly acid or alkaline materials.
- Storage class (TRGS 510) : 12, Non Combustible Liquids
- Further information on storage stability : No interior use.

### 7.3 Specific end use(s)

- Specific use(s) : This information is not available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Kieselguhr, soda ash flux-calcined	68855-54-9	AGW (Alveolate fraction)	0,3 mg/m <sup>3</sup>	DE TRGS 900
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child, Diatomeous earth can, depending on its origin, contain quartz. The calcining of silica leads to a higher content of cristobalite, activated silica can contain up to 60 vol.% cristobalite. In examining the exposure to (calcined) silica both the amorphous part (limit value for diatomeous earth resp. calcined silica) and the total of the cristobalite and quartz content (carcinogenic according to TRGS 906) should be established., Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
titanium dioxide	13463-67-7	AGW (Inhalable fraction)	10 mg/m <sup>3</sup> (Titanium dioxide)	DE TRGS 900
			Peak-limit: excursion factor (category): 2;(II)	
		AGW (Alveolate fraction)	1,25 mg/m <sup>3</sup> (Titanium dioxide)	DE TRGS 900
			Peak-limit: excursion factor (category): 2;(II)	

#### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
----------------	---------	-----------------	--------------------------	-------

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capatect ThermoSan Fassadenputz NQG K40

Version 2.0      Revision Date: 05.02.2021      Print Date 09.02.2021      Date of last issue: 20.02.2020  
Date of first issue: 20.02.2020

Kieselguhr, soda ash flux-calcined	Consumers	Ingestion	Long-term systemic effects	18,70 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0,05 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term systemic effects	0,05 mg/m <sup>3</sup>
titanium dioxide	Consumers	Ingestion	Long-term systemic effects	700,00 mg/kg bw/day
	Workers	Inhalation	Long-term local effects	10,00 mg/m <sup>3</sup>
Fatty acids, C16-18, zinc salts	Consumers	Ingestion	Long-term systemic effects	8,30 mg/kg bw/day
	Consumers	Skin contact	Long-term systemic effects	833,00 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	25,00 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term systemic effects	50,00 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	830,00 mg/kg bw/day

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Kieselguhr, soda ash flux-calcined	Sewage treatment plant	100 mg/l
titanium dioxide	Sewage treatment plant	100 mg/l
	Fresh water	0,184 mg/l
	Soil	100 mg/kg dry weight (d.w.)
	Marine water	0,0184 mg/l
	Fresh water sediment	1000 mg/kg dry weight (d.w.)
	Marine sediment	100 mg/kg dry weight (d.w.)
	Intermittent use/release	0,193 mg/l
Fatty acids, C16-18, zinc salts	Soil	35,6 mg/kg dry weight (d.w.)
	Fresh water	20,6 µg/l
	Marine sediment	56,5 mg/kg dry weight (d.w.)
	Sewage treatment plant	52 µg/l
	Fresh water sediment	117,8 mg/kg dry weight (d.w.)
	Marine water	6,1 µg/l

## 8.2 Exposure controls

### Personal protective equipment

Eye protection : German trade association rules - BGR 192 Eye protection

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capatect ThermoSan Fassadenputz NQG K40

Version	Revision Date:	Print Date	Date of last issue: 20.02.2020
2.0	05.02.2021	09.02.2021	Date of first issue: 20.02.2020

Goggles

Hand protection

Material : Nitrile rubber

Glove thickness : 0,2 mm

Protective index : Class 3

Remarks : Before removing gloves clean them with soap and water.  
Wear suitable gloves tested to EN374.

Skin and body protection : Safety shoes  
Long sleeved clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Skin should be washed after contact.

Respiratory protection : No personal respiratory protective equipment normally required.

German trade association rules - BGR 190 Breathing protection

During spray application: Do not breathe spray dust. Use A2/P2 combination filter for paint spraying.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Appearance : paste-like

Colour : No data available

Odour : No data available

Odour Threshold : Not relevant

pH : 8 - 9  
Concentration: 100 %

Melting point/freezing point : not determined

Boiling point/boiling range : not determined

Flash point : Not applicable

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capatect ThermoSan Fassadenputz NQG K40

Version	Revision Date:	Print Date	Date of last issue: 20.02.2020
2.0	05.02.2021	09.02.2021	Date of first issue: 20.02.2020

Evaporation rate	:	Not applicable
Upper explosion limit / Upper flammability limit	:	not determined
Lower explosion limit / Lower flammability limit	:	not determined
Vapour pressure	:	not determined
Relative vapour density	:	not determined
Relative density	:	not determined
Density	:	1,0 - 1,1 g/cm <sup>3</sup>
Solubility(ies) Water solubility	:	completely miscible
Partition coefficient: n-octanol/water	:	not determined
Auto-ignition temperature	:	not determined
Decomposition temperature	:	Not applicable
Viscosity Viscosity, dynamic	:	No data available
Explosive properties	:	Not applicable
Oxidizing properties	:	Not applicable

### 9.2 Other information

Flammability (liquids) : The product is not flammable.

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capatect ThermoSan Fassadenputz NQG K40

Version	Revision Date:	Print Date	Date of last issue: 20.02.2020
2.0	05.02.2021	09.02.2021	Date of first issue: 20.02.2020

### 10.4 Conditions to avoid

Conditions to avoid : Protect from frost, heat and sunlight.

### 10.5 Incompatible materials

Materials to avoid : Incompatible with acids and bases.  
Incompatible with oxidizing agents.

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

##### Product:

Acute oral toxicity : Remarks: Based on available data, the classification criteria are not met.

Acute inhalation toxicity : Remarks: Based on available data, the classification criteria are not met.

Acute dermal toxicity : Remarks: Based on available data, the classification criteria are not met.

##### Components:

#### reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):

Acute oral toxicity : LD50 (Rat): 66 mg/kg  
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 0,17 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rat): > 141 mg/kg  
Method: OECD Test Guideline 402

#### Skin corrosion/irritation

##### Product:

Remarks : According to the classification criteria of the European Union, the product is not considered as being a skin irritant.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capatect ThermoSan Fassadenputz NQG K40

Version	Revision Date:	Print Date	Date of last issue: 20.02.2020
2.0	05.02.2021	09.02.2021	Date of first issue: 20.02.2020

### Serious eye damage/eye irritation

**Product:**

Remarks : According to the classification criteria of the European Union, the product is not considered as being an eye irritant.

### Respiratory or skin sensitisation

**Product:**

Remarks : Repeated contact may cause allergic reactions in very susceptible persons.

## SECTION 12: Ecological information

### 12.1 Toxicity

**Product:**

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

**Components:**

**reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):**

M-Factor (Acute aquatic toxicity) : 100

M-Factor (Chronic aquatic toxicity) : 100

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

**Components:**

**reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):**

Partition coefficient: n-octanol/water : log Pow: <= 0,71  
Method: OECD Test Guideline 117

### 12.4 Mobility in soil

No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capatect ThermoSan Fassadenputz NQG K40

Version	Revision Date:	Print Date	Date of last issue: 20.02.2020
2.0	05.02.2021	09.02.2021	Date of first issue: 20.02.2020

### 12.5 Results of PBT and vPvB assessment

**Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

### 12.6 Other adverse effects

**Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : .  
Waste should not be disposed of via wastewater.

Contaminated packaging : Only completely emptied containers should be given for recycling.

Waste Code : used product  
080112, waste paint and varnish other than those mentioned in 08 01 11\*

## SECTION 14: Transport information

### 14.1 UN number

Not regulated as a dangerous good

### 14.2 UN proper shipping name

Not regulated as a dangerous good

### 14.3 Transport hazard class(es)

Not regulated as a dangerous good

### 14.4 Packing group

Not regulated as a dangerous good

### 14.5 Environmental hazards

Not regulated as a dangerous good

### 14.6 Special precautions for user

Remarks : Not classified as dangerous in the meaning of transport regu-

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capatect ThermoSan Fassadenputz NQG K40

Version	Revision Date:	Print Date	Date of last issue: 20.02.2020
2.0	05.02.2021	09.02.2021	Date of first issue: 20.02.2020

lations.

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : This product is a mixture and does not contain Substances of Very High Concern (SVHC) equal or above 0.1%. Therefore no advised uses have to be defined and no chemical safety assessment has to be generated.

REACH - List of substances subject to authorisation (Annex XIV) : None

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.  
Not applicable

Water contaminating class (Germany) : 1 slightly water endangering  
Classification according to AwSV, Annex 1 (5.2)

Product code for laquers and paints / Giscode : M-DF01F Water-based paints, solvent-free, active agents

. : BSW50 Coating materials, water-based, containing solvents, film-protected

Volatile organic compounds : Directive 2004/42/EC  
< 1 %  
< 10 g/l

### 15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capatect ThermoSan Fassadenputz NQG K40

Version	Revision Date:	Print Date	Date of last issue: 20.02.2020
2.0	05.02.2021	09.02.2021	Date of first issue: 20.02.2020

### SECTION 16: Other information

#### Full text of H-Statements

H301	: Toxic if swallowed.
H310	: Fatal in contact with skin.
H314	: Causes severe skin burns and eye damage.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H330	: Fatal if inhaled.
H351	: Suspected of causing cancer if inhaled.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.

#### Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Acute	: Short-term (acute) aquatic hazard
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Carc.	: Carcinogenicity
Eye Dam.	: Serious eye damage
Skin Corr.	: Skin corrosion
Skin Sens.	: Skin sensitisation
DE TRGS 900	: Germany. TRGS 900 - Occupational exposure limit values.
DE TRGS 900 / AGW	: Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

#### Further information

##### Other information:

No exposure scenario communication is required for this product according to REACH Regulation No. 1907/2006 EC.

Communication of Uses is not required in accordance with REACH Article 31(1)(a) - registered substances / mixtures do not meet the criteria for classification as hazardous in accordance with Regulations 1272/2008 EC or 1999/45/EC.

##### Sources of key data used to compile the Safety Data Sheet:

ECHA WebSite

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capatect ThermoSan Fassadenputz NQG K40

Version	Revision Date:	Print Date	Date of last issue: 20.02.2020
2.0	05.02.2021	09.02.2021	Date of first issue: 20.02.2020

ACGIH (American Conference of Government Industrial Hygienists). 2014 TLVs and BEIs. Threshold Limit Values (TLVs) for chemical substances and physical agents and Biological Exposure Indices (BEIs) with Seventh Edition documentation. 2014 ACGIH, Cincinnati OH  
NIOSH - Registry of toxic effects of chemical substances  
ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities  
SAX'S - Dangerous properties of industrial materials  
GESTIS - Database on hazardous substances - Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA, Institute for Occupational Safety and Health of the German Social Accident Insurance)  
Toxnet - Toxicology Data Network

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

### REACH Information

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our upstream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly.

DE / EN